

**Product List (Flat Sheet continuously rolled)**

current status:

**14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	Thickness (mm)	Width (mm)	Thickness (inch)	Width (inch)	Available	Me	Surface	AF
1	Foil NiTi SE508 acc. ASTM F2063	0,100	28,000	0,004	1,102	0,564 kg		light oxidized	Max. 15 °C
2	Sheet NiTi SE508 acc. ASTM F2063	0,150	28,000	0,006	1,102	1,829 kg		light oxidized	Max. 15 °C
3	Sheet NiTi acc. ASTM F2063	0,200	25,000	0,008	0,984	6,313 kg		light oxidized	Max. 15 °C
4	Sheet NiTi SE508 acc. ASTM F2063	0,250	28,000	0,010	1,102	0,728 kg		sandblasted	Max. 15 °C
5	Sheet NiTi SSM acc. ASTM F2063	0,300	28,000	0,012	1,102	0,080 kg		light oxidized	Max. 15 °C
6	Sheet NiTi SE508 acc. ASTM F2063	0,350	25,400	0,014	1,000	1,200 kg		oxidized	Max. 15 °C
7	Sheet NiTi SE508 acc. ASTM F2063	0,533	22,000	0,021	0,866	3,846 kg		light oxidized	Max. 15 °C