

Product List (Flat Sheet continuously rolled)

current status:

21.07.2021

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	Thickness (mm)	Width (mm)	Thickness (inch)	Width (inch)	Available	Me	Surface	AF
1	Foil NiTi SE508 acc. ASTM F2063	0,100	28,000	0,004	1,102	1,830 kg		light oxidized	Max. 15 °C
2	Sheet NiTi SE508 acc. ASTM F2063	0,200	28,000	0,008	1,102	1,327 kg		light oxidized	Max. 15 °C
3	Sheet NiTi SE508 acc. ASTM F2063	0,250	28,000	0,010	1,102	1,964 kg		light oxidized	Max. 15 °C
4	Sheet NiTi SSM acc. ASTM F2063	0,300	28,000	0,012	1,102	1,231 kg		light oxidized	Max. 15 °C
5	Sheet NiTi SE508 acc. ASTM F2063	0,350	25,400	0,014	1,000	2,582 kg		oxidized	Max. 15 °C
6	Sheet NiTi SE508 acc. ASTM F2063	0,500	22,000	0,020	0,866	2,326 kg		sandblasted	Max. 15 °C
7	Sheet NiTi SE508 acc. ASTM F2063	0,533	22,000	0,021	0,866	4,479 kg		light oxidized	Max. 15 °C