

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1	1.4301 (304)	0,356	0,075	0,206	0,0140	0,0030	0,0081	2,000	m		
2	1.4301 (304)	0,410	0,045	0,320	0,0161	0,0018	0,0126	21,284	m		
3	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
4	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	20,000	m		
5	1.4301 (304)	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
6	1.4301 (304)	2,515	0,051	2,413	0,0990	0,0020	0,0950	9,000	St		
7	1.4301 (304)	3,000	0,300	2,400	0,1181	0,0118	0,0945	4,369	m		
8	1.4301 (304)	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
9	1.4301 (304)	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
10	1.4301 (304)	6,700	0,500	5,700	0,2638	0,0197	0,2244	11,650	m		
11	1.4301 (304)	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
12	1.4301 (304)	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
13	1.4307	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
14	1.4452 (P 2000)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
15	1.4452 (P 2000)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
16	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
17	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	31,775	m		
18	1.4452 (P 2000)	4,500	0,220	4,060	0,1772	0,0087	0,1598	2,393	m		
19	1.4452 (P 2000)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
20	1.4541	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
21	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	14,722	m		

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	24,000	m		
23	1.4568	0,690	0,125	0,440	0,0272	0,0049	0,0173	8,854	m		
24	1.4568	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
25	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
26	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
27	1.4568	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
28	1.4568	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
29	1.4571	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
30	316L	0,457	0,070	0,317	0,0180	0,0028	0,0125	6,939	m		
31	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	33,244	m		
32	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	190,027	m		
33	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
34	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
35	316L	3,000	0,100	2,800	0,1181	0,0039	0,1102	10,732	m		
36	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	13,621	m		
37	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
38	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	107,000	St		
39	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
40	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	367,466	m		
41	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	135,886	m		
42	316LVM	0,450	0,075	0,300	0,0177	0,0030	0,0118	7,646	m		

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	57,000	m		
44	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	27,113	m		
45	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	17,572	m		
46	316LVM	0,724	0,100	0,524	0,0285	0,0039	0,0206	1,462	m		
47	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	37,212	m		
48	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	38,024	m		
49	316LVM	0,960	0,120	0,720	0,0378	0,0047	0,0283	5,727	m		
50	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	45,981	m		
51	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	72,562	m		
52	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	24,981	m		
53	316LVM	1,000	0,200	0,600	0,0394	0,0079	0,0236	47,383	m		
54	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
55	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	64,256	m		
56	316LVM	1,169	0,102	0,965	0,0460	0,0040	0,0380	4,104	m		
57	316LVM	1,300	0,075	1,150	0,0512	0,0030	0,0453	20,605	m		
58	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
59	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
60	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
61	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	2,986	m		
62	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
63	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	19,602	m		
65	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	11,761	m		
66	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	13,998	m		
67	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
68	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	48,700	m		
69	316LVM	2,100	0,100	1,900	0,0827	0,0039	0,0748	18,853	m		
70	316LVM	2,400	0,100	2,200	0,0945	0,0039	0,0866	25,027	m		
71	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	29,849	m		
72	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
73	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	77,395	m		
74	316LVM	3,110	0,105	2,900	0,1224	0,0041	0,1142	29,707	m		
75	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
76	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	46,767	m		
77	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
78	316LVM	4,572	0,229	4,114	0,1800	0,0090	0,1620	63,638	m		
79	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
80	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
81	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	22,012	m		
82	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	62,513	m		
83	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
84	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
86	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	30,982	m		
87	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	21,000	m		
88	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		
89	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	32,702	m		
90	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
91	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	8,287	m		
92	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		
93	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
94	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	6,251	m		
95	316LVM	10,000	0,500	9,000	0,3937	0,0197	0,3543	13,854	m		
96	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	73,113	m		
97	KC35N LT	0,356	0,102	0,152	0,0140	0,0040	0,0060	27,000	St		
98	KC35N LT	0,368	0,083	0,203	0,0145	0,0033	0,0080	30,000	St		
99	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	40,299	m		
100	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	2,100	m		
101	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2310,000	St		
102	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	935,000	St		
103	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	48,190	m		
104	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	9,886	m		
105	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	1,000	0,230	0,540	0,0394	0,0091	0,0213	17,092	m		
107	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		
108	KC35N LT	1,290	0,130	1,030	0,0508	0,0051	0,0406	545,000	m		
109	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
110	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
111	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
112	KC35N LT	1,500	0,130	1,240	0,0591	0,0051	0,0488	23,010	m		
113	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
114	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	1,816	m		
115	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	14,397	m		
116	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
117	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		
118	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
119	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
120	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		
121	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
122	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	50,256	m		
123	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	9,819	m		
124	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
125	KC35N LT	6,000	0,550	4,900	0,2362	0,0217	0,1929	13,402	m		
126	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
128	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	37,340	m		
129	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
130	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
131	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
132	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	16,160	m		
133	L605	0,762	0,127	0,508	0,0300	0,0050	0,0200	38,452	m		
134	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,451	m		
135	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
136	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	45,448	m		
137	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
138	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
139	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	10,764	m		
140	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	26,260	m		
141	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
142	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		
143	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
144	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
145	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
146	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
147	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
149	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
150	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		
151	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
152	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,532	m		
153	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
154	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
155	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	204,174	m		
156	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
157	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
158	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	66,860	m		
159	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		
160	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		
161	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	22,750	m		
162	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
163	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
164	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
165	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	533,998	m		
166	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
167	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
168	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		



**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
170	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
171	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
172	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	107,761	m		
173	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	21,220	m		
174	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	582,780	m		
175	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
176	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	8,711	m		
177	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	32,710	m		
178	L605	3,000	0,170	2,660	0,1181	0,0067	0,1047	61,836	m		
179	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	9,721	m		
180	L605	3,400	0,170	3,060	0,1339	0,0067	0,1205	174,524	m		
181	L605	3,800	0,150	3,500	0,1496	0,0059	0,1378	107,801	m		
182	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	100,710	m		
183	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
184	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
185	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	9,217	m		
186	L605	4,318	0,160	3,998	0,1700	0,0063	0,1574	16,657	m		
187	L605	4,400	0,280	3,840	0,1732	0,0110	0,1512	32,906	m		
188	L605	4,400	0,280	3,840	0,1732	0,0110	0,1512	4,485	m		
189	L605	4,400	0,320	3,760	0,1732	0,0126	0,1480	41,479	m		

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
191	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	3,030	m		
192	L605	6,000	0,200	5,600	0,2362	0,0079	0,2205	4,011	m		
193	L605	6,240	0,120	6,000	0,2457	0,0047	0,2362	5,526	m		
194	L605	10,000	0,100	25,000	0,3937	0,0039	0,9843	797,000	St		
195	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
196	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
197	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
198	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
199	NiTi	0,300	0,085	0,130	0,0118	0,0033	0,0051	7,122	m	ground	Max. 15 °C
200	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	7,270	m	ground	Max. 15 °C
201	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	Max. 15 °C
202	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	55,000	m	ground	Max. 15 °C
203	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	81,374	m	dark oxidized	Max. 15 °C
204	NiTi	0,400	0,080	0,240	0,0157	0,0031	0,0094	2,136	m	ground out-/oxidic inside	Max. 15 °C
205	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	10,388	m	ground	Max. 15 °C
206	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	46,115	m	ground	Max. 15 °C
207	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	31,544	m	dark oxidized	Max. 15 °C
208	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	10,973	m	polished	Max. 15 °C
209	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	16,459	m	polished	Max. 15 °C
210	NiTi	0,480	0,076	0,328	0,0189	0,0030	0,0129	8,070	m	ground	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,480	0,080	0,320	0,0189	0,0031	0,0126	61,141 m			Max. 15 °C
212	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	1010,291 m		dark oxidized	Max. 15 °C
213	NiTi	0,559	0,070	0,419	0,0220	0,0028	0,0165	0,345 m		ground	Max. 15 °C
214	NiTi	0,635	0,102	0,432	0,0250	0,0040	0,0170	107,816 m		ground	Max. 15 °C
215	NiTi	0,640	0,100	0,440	0,0252	0,0039	0,0173	7,243 m		ground	Max. 15 °C
216	NiTi	0,730	0,100	0,530	0,0287	0,0039	0,0209	49,742 m		ground	Max. 15 °C
217	NiTi	0,900	0,190	0,520	0,0354	0,0075	0,0205	1,481 m		dark oxidized	Max. 15 °C
218	NiTi	0,960	0,050	0,860	0,0378	0,0020	0,0339	3,469 m		ground	Max. 15 °C
219	NiTi	1,000	0,050	0,900	0,0394	0,0020	0,0354	23,711 m		ground	Max. 15 °C
220	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	14,904 m		ground	Max. 15 °C
221	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	48,010 m		ground	Max. 15 °C
222	NiTi	1,080	0,040	1,000	0,0425	0,0016	0,0394	1,161 m		ground	Max. 15 °C
223	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	39,395 m		ground	Max. 15 °C
224	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	11,760 m		ground	Max. 15 °C
225	NiTi	1,200	0,125	0,950	0,0472	0,0049	0,0374	28,581 m		ground	Max. 15 °C
226	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	4,995 m		ground out-/oxidic inside	Max. 15 °C
227	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	7,585 m		ground out-/oxidic inside	Max. 15 °C
228	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	239,427 m		ground	Max. 15 °C
229	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	163,995 m		ground	Max. 15 °C
230	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	8,648 m		ground	Max. 15 °C
231	NiTi	1,240	0,230	0,780	0,0488	0,0091	0,0307	24,456 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716 m		ground	Max. 15 °C
233	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	70,418 m		ground	Max. 15 °C
234	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,520 m		ground	Max. 15 °C
235	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	36,539 m		ground	Max. 15 °C
236	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,632 m		ground	Max. 15 °C
237	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	Max. 15 °C
238	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m		ground out-/oxidic inside	Max. 15 °C
239	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	21,797 m		ground out-/oxidic inside	Max. 15 °C
240	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	Max. 15 °C
241	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,030 m		ground	Max. 15 °C
242	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	3,250 m		ground	Max. 15 °C
243	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m		ground	Max. 15 °C
244	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,129 m		ground	Max. 15 °C
245	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,410 m		ground	Max. 15 °C
246	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	Max. 15 °C
247	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	Max. 15 °C
248	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	175,017 m		ground	Max. 15 °C
249	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	Max. 15 °C
250	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	Max. 15 °C
251	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,500 m		ground	Max. 15 °C
252	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	Max. 15 °C
254	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	Max. 15 °C
255	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	Max. 15 °C
256	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,948 m		ground	Max. 15 °C
257	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,943 m		ground	Max. 15 °C
258	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	Max. 15 °C
259	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	Max. 15 °C
260	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	40,650 m		ground	Max. 15 °C
261	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	9,410 m		ground	Max. 15 °C
262	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	15,060 m		ground	Max. 15 °C
263	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	3,374 m		ground	Max. 15 °C
264	NiTi	1,350	0,135	1,080	0,0531	0,0053	0,0425	11,961 m		ground	Max. 15 °C
265	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	10,634 m		ground	Max. 15 °C
266	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	12,215 m		ground	Max. 15 °C
267	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	6,751 m		ground	Max. 15 °C
268	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	10,187 m		ground	Max. 15 °C
269	NiTi	1,390	0,130	1,130	0,0547	0,0051	0,0445	5,670 m		ground	Max. 15 °C
270	NiTi	1,400	0,240	0,920	0,0551	0,0094	0,0362	2,000 m		ground	Max. 15 °C
271	NiTi	1,422	0,051	1,320	0,0560	0,0020	0,0520	6,259 m		ground	Max. 15 °C
272	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	5,939 m		ground	Max. 15 °C
273	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	3,563 m		ground	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,524	0,114	1,296	0,0600	0,0045	0,0510	5,000	St	ground	Max. 15 °C
275	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	19,461	m	ground	Max. 15 °C
276	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	51,181	m	ground	Max. 15 °C
277	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	8,878	m	ground	Max. 15 °C
278	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	1,300	m	ground	Max. 15 °C
279	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080	m	ground out-/oxidic inside	Max. 15 °C
280	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	96,900	m	ground out-/oxidic inside	Max. 15 °C
281	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	16,307	m	ground	Max. 15 °C
282	NiTi	1,560	0,130	1,300	0,0614	0,0051	0,0512	3,882	m	ground	Max. 15 °C
283	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,532	m	ground out-/oxidic inside	Max. 15 °C
284	NiTi	1,600	0,200	1,200	0,0630	0,0079	0,0472	4,874	m		min. 55 °C
285	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	22,144	m	ground	Max. 15 °C
286	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,077	m	ground	Max. 15 °C
287	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	66,396	m	ground	Max. 15 °C
288	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	9,605	m	ground	Max. 15 °C
289	NiTi	1,600	0,474	0,653	0,0630	0,0187	0,0257	8,000	St	ground	Max. 15 °C
290	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	3,490	m	ground	Max. 15 °C
291	NiTi	1,620	0,240	1,140	0,0638	0,0094	0,0449	39,435	m	ground out-/oxidic inside	Max. 15 °C
292	NiTi	1,626	0,140	1,346	0,0640	0,0055	0,0530	9,289	m	ground	Max. 15 °C
293	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	Max. 15 °C
294	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	13,028	m	ground out-/oxidic inside	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737 m		ground out-/oxidic inside	Max. 15 °C
296	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970 m		ground out-/oxidic inside	Max. 15 °C
297	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820 m		ground out-/oxidic inside	Max. 15 °C
298	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,170 m		polished	Max. 15 °C
299	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	4,631 m		ground	Max. 15 °C
300	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609 m		ground	Max. 15 °C
301	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,965 m		ground	Max. 15 °C
302	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,165 m		ground	Max. 15 °C
303	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	181,246 m		ground	Max. 15 °C
304	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279 m		ground	Max. 15 °C
305	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	21,363 m		ground	Max. 15 °C
306	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	3,627 m		ground	Max. 15 °C
307	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	Max. 15 °C
308	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		dark oxidized	Max. 15 °C
309	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	Max. 15 °C
310	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	Max. 15 °C
311	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	Max. 15 °C
312	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	Max. 15 °C
313	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	Max. 15 °C
314	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,980 m		ground	Max. 15 °C
315	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	Max. 15 °C
317	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	Max. 15 °C
318	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	Max. 15 °C
319	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	Max. 15 °C
320	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	Max. 15 °C
321	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	255,144 m		ground	Max. 15 °C
322	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,150 m		ground	Max. 15 °C
323	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	Max. 15 °C
324	NiTi	1,670	0,100	1,470	0,0657	0,0039	0,0579	13,676 m		ground	Max. 15 °C
325	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	24,000 m	St	ground	Max. 15 °C
326	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	215,668 m		ground out-/oxidic inside	Max. 15 °C
327	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	287,701 m		ground out-/oxidic inside	Max. 15 °C
328	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	188,906 m		ground	Max. 15 °C
329	NiTi	1,729	0,210	1,309	0,0681	0,0083	0,0515	7,559 m		ground	Max. 15 °C
330	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	36,100 m		ground	Max. 15 °C
331	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	Max. 15 °C
332	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m		ground	Max. 15 °C
333	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	Max. 15 °C
334	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	Max. 15 °C
335	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,323 m		ground	Max. 15 °C
336	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m		ground	Max. 15 °C



## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	Max. 15 °C
338	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	Max. 15 °C
339	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	Max. 15 °C
340	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,900 m		ground	Max. 15 °C
341	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	Max. 15 °C
342	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	81,630 m		ground	Max. 15 °C
343	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,250 m		ground	Max. 15 °C
344	NiTi	1,778	0,406	0,966	0,0700	0,0160	0,0380	22,252 m		ground	Max. 15 °C
345	NiTi	1,796	0,250	1,296	0,0707	0,0098	0,0510	4,875 m		ground	Max. 15 °C
346	NiTi	1,800	0,070	1,660	0,0709	0,0028	0,0654	17,365 m		ground	Max. 15 °C
347	NiTi	1,800	0,075	1,650	0,0709	0,0030	0,0650	21,481 m		ground	Max. 15 °C
348	NiTi	1,800	0,080	1,640	0,0709	0,0031	0,0646	9,088 m		ground	Max. 15 °C
349	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,273 m		ground	Max. 15 °C
350	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	Max. 15 °C
351	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	64,888 m		ground	Max. 15 °C
352	NiTi	1,800	0,095	1,610	0,0709	0,0037	0,0634	14,995 m		ground	Max. 15 °C
353	NiTi	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,469 m		ground	Max. 15 °C
354	NiTi	1,800	0,220	1,360	0,0709	0,0087	0,0535	1,438 m		ground	Max. 15 °C
355	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	10,263 m		ground	Max. 15 °C
356	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	14,726 m		ground	Max. 15 °C
357	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	21,683 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,238 m		ground	Max. 15 °C
359	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,716 m		ground	Max. 15 °C
360	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	5,537 m		ground	Max. 15 °C
361	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	18,149 m		ground	Max. 15 °C
362	NiTi	1,900	0,370	1,160	0,0748	0,0146	0,0457	8,895 m		ground	Max. 15 °C
363	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	11,009 m		ground	Max. 15 °C
364	NiTi	1,915	0,165	1,585	0,0754	0,0065	0,0624	3,069 m		ground	Max. 15 °C
365	NiTi	1,930	0,305	1,320	0,0760	0,0120	0,0520	113,053 m		ground out-/oxidic inside	Max. 15 °C
366	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	4,795 m		ground	Max. 15 °C
367	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	8,969 m		ground	Max. 15 °C
368	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	7,035 m		ground	Max. 15 °C
369	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	8,934 m		ground	Max. 15 °C
370	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	156,705 m		ground	Max. 15 °C
371	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	278,514 m		ground	Max. 15 °C
372	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990 m		ground	Max. 15 °C
373	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	27,510 m		ground	Max. 15 °C
374	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m		ground	Max. 15 °C
375	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	21,199 m		ground	Max. 15 °C
376	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	38,515 m		ground	Max. 15 °C
377	NiTi	2,019	0,266	1,487	0,0795	0,0105	0,0585	3,728 m		ground	Max. 15 °C
378	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	6,924 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847 m		ground	Max. 15 °C
380	NiTi	2,030	0,280	1,470	0,0799	0,0110	0,0579	12,322 m		ground	Max. 15 °C
381	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	318,700 m		ground	Max. 15 °C
382	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	333,511 m		ground	Max. 15 °C
383	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	411,914 m		ground	Max. 15 °C
384	NiTi	2,050	0,300	1,450	0,0807	0,0118	0,0571	13,025 m		ground	Max. 15 °C
385	NiTi	2,100	0,250	1,600	0,0827	0,0098	0,0630	14,009 m		ground	Max. 15 °C
386	NiTi	2,120	0,320	1,480	0,0835	0,0126	0,0583	12,945 m		ground	Max. 15 °C
387	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	4,950 m		ground	Max. 15 °C
388	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	14,305 m		ground	Max. 15 °C
389	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	16,510 m		ground	Max. 15 °C
390	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	23,347 m		ground	Max. 15 °C
391	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	34,349 m		ground	Max. 15 °C
392	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	7,169 m		ground	Max. 15 °C
393	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	130,730 m		ground	Max. 15 °C
394	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	25,753 m		ground	Max. 15 °C
395	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	3,772 m		ground	Max. 15 °C
396	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	341,218 m		ground	Max. 15 °C
397	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	15,602 m		ground	Max. 15 °C
398	NiTi	2,180	0,370	1,440	0,0858	0,0146	0,0567	12,634 m		ground	Max. 15 °C
399	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	1,840 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	13,550 m		ground	Max. 15 °C
401	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	9,847 m		ground	Max. 15 °C
402	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	8,283 m		ground	Max. 15 °C
403	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,294 m		ground	Max. 15 °C
404	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	33,766 m		ground out-/oxidic inside	Max. 15 °C
405	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	57,200 m		ground out-/oxidic inside	Max. 15 °C
406	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	Max. 15 °C
407	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	25,542 m		ground	Max. 15 °C
408	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	8,472 m		ground	Max. 15 °C
409	NiTi	2,200	0,270	1,660	0,0866	0,0106	0,0654	42,972 m		ground	Max. 15 °C
410	NiTi	2,200	0,325	1,550	0,0866	0,0128	0,0610	2,040 m		ground	Max. 15 °C
411	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	Max. 15 °C
412	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	21,926 m		ground	Max. 15 °C
413	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	44,581 m		ground	Max. 15 °C
414	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,081 m		ground	Max. 15 °C
415	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,936 m		ground	Max. 15 °C
416	NiTi	2,286	0,254	1,778	0,0900	0,0100	0,0700	2,821 m		ground	Max. 15 °C
417	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	Max. 15 °C
418	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,624 m		ground	Max. 15 °C
419	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	Max. 15 °C
420	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	Max. 15 °C
422	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	Max. 15 °C
423	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	Max. 15 °C
424	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,800 m		ground out-/oxidic inside	Max. 15 °C
425	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	Max. 15 °C
426	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	Max. 15 °C
427	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	3,010 m		ground	Max. 15 °C
428	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	42,120 m		ground	Max. 15 °C
429	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	8,866 m		ground	Max. 15 °C
430	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	12,818 m		ground	Max. 15 °C
431	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	Max. 15 °C
432	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	33,572 m		ground	Max. 15 °C
433	NiTi	2,400	0,085	2,230	0,0945	0,0033	0,0878	3,204 m		ground	Max. 15 °C
434	NiTi	2,400	0,090	2,220	0,0945	0,0035	0,0874	6,898 m		ground	Max. 15 °C
435	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	34,413 m		dark oxidized	Max. 15 °C
436	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	8,635 m		ground	Max. 15 °C
437	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	11,313 m		ground	Max. 15 °C
438	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	11,630 m		ground	Max. 15 °C
439	NiTi	2,413	0,229	1,956	0,0950	0,0090	0,0770	3,805 m		ground	Max. 15 °C
440	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	22,067 m		ground	Max. 15 °C
441	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	1,760 m		dark oxidized	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	2,449	0,221	2,007	0,0964	0,0087	0,0790	12,885 m		ground	Max. 15 °C
443	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	2,629 m		ground	Max. 15 °C
444	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	20,344 m		ground	Max. 15 °C
445	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	3,920 m		ground	Max. 15 °C
446	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	28,072 m		ground	Max. 15 °C
447	NiTi	2,550	0,180	2,190	0,1004	0,0071	0,0862	15,614 m		ground	Max. 15 °C
448	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	13,249 m		ground	Max. 15 °C
449	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	3,914 m		ground	Max. 15 °C
450	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,577 m		ground	Max. 15 °C
451	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m		ground	Max. 15 °C
452	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	9,004 m		ground out-/oxidic inside	Max. 15 °C
453	NiTi	2,590	0,076	2,438	0,1020	0,0030	0,0960	2,188 m		ground	Max. 15 °C
454	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	74,601 m		ground	Max. 15 °C
455	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	41,055 m		ground	Max. 15 °C
456	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,811 m		ground	Max. 15 °C
457	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	81,655 m		ground	Max. 15 °C
458	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,617 m		ground	Max. 15 °C
459	NiTi	2,654	0,102	2,450	0,1045	0,0040	0,0965	1,013 m		ground	Max. 15 °C
460	NiTi	2,667	0,241	2,185	0,1050	0,0095	0,0860	5,060 m		ground	Max. 15 °C
461	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	4,405 m		ground	Max. 15 °C
462	NiTi	2,680	0,115	2,450	0,1055	0,0045	0,0965	13,550 m		dark oxidized	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022 m		ground	Max. 15 °C
464	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,177 m		ground	Max. 15 °C
465	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	1,143 m		ground	Max. 15 °C
466	NiTi	2,720	0,170	2,380	0,1071	0,0067	0,0937	1,592 m		ground	Max. 15 °C
467	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	11,520 m		ground	Max. 15 °C
468	NiTi	2,760	0,190	2,380	0,1087	0,0075	0,0937	4,993 m		ground	Max. 15 °C
469	NiTi	2,800	0,230	2,340	0,1102	0,0091	0,0921	5,786 m		ground	Max. 15 °C
470	NiTi	2,800	0,300	2,200	0,1102	0,0118	0,0866	8,406 m		ground	Max. 15 °C
471	NiTi	2,800	0,500	1,800	0,1102	0,0197	0,0709	3,998 m		ground out-/oxidic inside	Max. 15 °C
472	NiTi	2,819	0,371	2,077	0,1110	0,0146	0,0818	7,000 m	St	ground	Max. 15 °C
473	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	13,868 m		ground	Max. 15 °C
474	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	17,847 m		ground out-/oxidic inside	Max. 15 °C
475	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	179,021 m		ground out-/oxidic inside	Max. 15 °C
476	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	21,873 m		ground out-/oxidic inside	Max. 15 °C
477	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	34,802 m		ground out-/oxidic inside	Max. 15 °C
478	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	4,788 m		ground out-/oxidic inside	Max. 15 °C
479	NiTi	2,906	0,191	2,524	0,1144	0,0075	0,0994	22,430 m		ground	Max. 15 °C
480	NiTi	3,000	0,150	2,700	0,1181	0,0059	0,1063	1,801 m		ground	Max. 15 °C
481	NiTi	3,000	0,200	2,600	0,1181	0,0079	0,1024	4,658 m		ground	Max. 15 °C
482	NiTi	3,000	0,300	2,400	0,1181	0,0118	0,0945	6,324 m		ground	Max. 15 °C
483	NiTi	3,030	0,233	2,564	0,1193	0,0092	0,1009	6,086 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	3,048	0,254	2,540	0,1200	0,0100	0,1000	1,000	St	ground	Max. 15 °C
485	NiTi	3,063	0,262	2,539	0,1206	0,0103	0,1000	3,054	m	ground	Max. 15 °C
486	NiTi	3,150	0,203	2,744	0,1240	0,0080	0,1080	49,115	m	ground	Max. 15 °C
487	NiTi	3,160	0,170	2,820	0,1244	0,0067	0,1110	9,239	m	ground	Max. 15 °C
488	NiTi	3,280	0,115	3,050	0,1291	0,0045	0,1201	5,050	m	ground	Max. 15 °C
489	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,471	m	ground out-/oxidic inside	Max. 15 °C
490	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,757	m	ground out-/oxidic inside	Max. 15 °C
491	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	11,977	m	ground	Max. 15 °C
492	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	52,816	m	ground	Max. 15 °C
493	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,471	m	ground	Max. 15 °C
494	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	1,245	m	ground out-/oxidic inside	Max. 15 °C
495	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	4,156	m	ground	Max. 15 °C
496	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	5,377	m	ground	Max. 15 °C
497	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	6,000	St	ground	Max. 15 °C
498	NiTi	3,404	0,458	2,489	0,1340	0,0180	0,0980	8,009	m	ground	Max. 15 °C
499	NiTi	3,500	0,075	3,350	0,1378	0,0030	0,1319	15,571	m	ground	Max. 15 °C
500	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	13,198	m	ground	Max. 15 °C
501	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	8,819	m	ground	Max. 15 °C
502	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610	m	ground	Max. 15 °C
503	NiTi	3,500	0,170	3,160	0,1378	0,0067	0,1244	3,115	m	ground	Max. 15 °C
504	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	3,772	m	ground	Max. 15 °C



## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	2,292 m		ground	Max. 15 °C
506	NiTi	3,810	0,120	3,570	0,1500	0,0047	0,1406	3,570 m		ground	Max. 15 °C
507	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	109,685 m		ground	Max. 15 °C
508	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	3,174 m		ground	Max. 15 °C
509	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	4,613 m		ground	Max. 15 °C
510	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	5,000 m		ground	Max. 15 °C
511	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	18,036 m		ground	Max. 15 °C
512	NiTi	4,242	0,152	3,938	0,1670	0,0060	0,1550	3,705 m		ground	Max. 15 °C
513	NiTi	4,250	0,065	4,120	0,1673	0,0026	0,1622	4,333 m		polished	Max. 15 °C
514	NiTi	4,270	0,079	4,112	0,1681	0,0031	0,1619	4,942 m		ground	Max. 15 °C
515	NiTi	4,370	0,285	3,800	0,1720	0,0112	0,1496	3,412 m		ground	Max. 15 °C
516	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	1,836 m		ground	Max. 15 °C
517	NiTi	4,700	0,150	4,400	0,1850	0,0059	0,1732	11,619 m		ground	Max. 15 °C
518	NiTi	4,750	0,125	4,500	0,1870	0,0049	0,1772	1,784 m		ground	Max. 15 °C
519	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,597 m		ground	Max. 15 °C
520	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	2,905 m		ground	Max. 15 °C
521	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	2,707 m		ground	Max. 15 °C
522	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	5,320 m		polished	Max. 15 °C
523	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	Max. 15 °C
524	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,306 m		ground	Max. 15 °C
525	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	29,886 m		ground out-/oxidic inside	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
526	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	Max. 15 °C
527	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	Max. 15 °C
528	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	Max. 15 °C
529	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	Max. 15 °C
530	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	Max. 15 °C
531	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	64,607 m		ground out-/oxidic inside	Max. 15 °C
532	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,030 m		ground out-/oxidic inside	Max. 15 °C
533	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	Max. 15 °C
534	NiTi	4,980	0,280	4,420	0,1961	0,0110	0,1740	3,032 m		ground	Max. 15 °C
535	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	2,510 m		ground	Max. 15 °C
536	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	4,970 m		ground	Max. 15 °C
537	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	44,759 m		ground	Max. 15 °C
538	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	8,708 m		ground	Max. 15 °C
539	NiTi	5,000	0,250	4,500	0,1969	0,0098	0,1772	5,870 m		ground	Max. 15 °C
540	NiTi	5,004	0,533	3,938	0,1970	0,0210	0,1550	2,263 m		ground out-/oxidic inside	Max. 15 °C
541	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	Max. 15 °C
542	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434 m		ground	Max. 15 °C
543	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	16,798 m		ground	Max. 15 °C
544	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	3,189 m		ground	Max. 15 °C
545	NiTi	5,207	0,279	4,649	0,2050	0,0110	0,1830	1,400 m		ground	Max. 15 °C
546	NiTi	5,500	0,215	5,070	0,2165	0,0085	0,1996	9,046 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
547	NiTi	5,500	0,450	4,600	0,2165	0,0177	0,1811	29,439 m		ground	Max. 15 °C
548	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	3,553 m		ground	Max. 15 °C
549	NiTi	5,944	0,572	4,800	0,2340	0,0225	0,1890	1,250 m		ground out-/oxidic inside	Max. 15 °C
550	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,110 m		ground out-/oxidic inside	Max. 15 °C
551	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	14,190 m		ground out-/oxidic inside	Max. 15 °C
552	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,525 m		ground	Max. 15 °C
553	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	7,512 m		ground	Max. 15 °C
554	NiTi	6,000	0,400	5,200	0,2362	0,0157	0,2047	3,215 m		ground	Max. 15 °C
555	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	18,021 m		ground	Max. 15 °C
556	NiTi	6,200	0,150	5,900	0,2441	0,0059	0,2323	12,837 m		ground	Max. 15 °C
557	NiTi	6,400	0,200	6,000	0,2520	0,0079	0,2362	9,390 m		ground	Max. 15 °C
558	NiTi	6,500	0,220	6,060	0,2559	0,0087	0,2386	2,442 m		ground	Max. 15 °C
559	NiTi	6,510	0,245	6,020	0,2563	0,0096	0,2370	10,408 m		ground	Max. 15 °C
560	NiTi	6,700	0,250	6,200	0,2638	0,0098	0,2441	3,726 m		ground	Max. 15 °C
561	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	2,532 m		ground	Max. 15 °C
562	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	6,967 m		ground	Max. 15 °C
563	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	5,487 m		ground	Max. 15 °C
564	NiTi	7,000	0,470	6,060	0,2756	0,0185	0,2386	1,631 m		ground	Max. 15 °C
565	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	10,725 m		ground out-/oxidic inside	Max. 15 °C
566	NiTi	7,000	0,533	5,934	0,2756	0,0210	0,2336	1,559 m		ground	Max. 15 °C
567	NiTi	7,150	0,100	6,950	0,2815	0,0039	0,2736	11,141 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
568	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	5,777 m		ground	Max. 15 °C
569	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	0,710 m		ground	Max. 15 °C
570	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	1,520 m			Max. 15 °C
571	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,130 m		ground	Max. 15 °C
572	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,570 m		ground	Max. 15 °C
573	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	9,837 m		ground	Max. 15 °C
574	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	14,356 m		ground	Max. 15 °C
575	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	4,550 m		ground	Max. 15 °C
576	NiTi	8,000	0,500	7,000	0,3150	0,0197	0,2756	9,553 m		ground	Max. 15 °C
577	NiTi	8,000	0,650	6,700	0,3150	0,0256	0,2638	1,623 m		polished	Max. 15 °C
578	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,645 m		ground	Max. 15 °C
579	NiTi	8,500	0,220	8,060	0,3346	0,0087	0,3173	3,458 m		ground	Max. 15 °C
580	NiTi	8,800	0,450	7,900	0,3465	0,0177	0,3110	17,179 m		ground	Max. 15 °C
581	NiTi	8,800	0,550	7,700	0,3465	0,0217	0,3031	1,297 m		ground	Max. 15 °C
582	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	20,069 m		ground	Max. 15 °C
583	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	3,470 m		ground	Max. 15 °C
584	NiTi	10,000	0,480	9,040	0,3937	0,0189	0,3559	14,031 m		ground	Max. 15 °C
585	NiTi	10,000	0,625	8,750	0,3937	0,0246	0,3445	7,149 m		ground	Max. 15 °C
586	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	3,410 m		ground	Max. 15 °C
587	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	6,591 m		ground	Max. 15 °C
588	NiTi	10,000	0,720	8,560	0,3937	0,0283	0,3370	1,869 m		ground	Max. 15 °C

## Stock list - Tubes

current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
589	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	1,050 m		ground	Max. 15 °C
590	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	2,854 m		ground	Max. 15 °C
591	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	8,806 m		ground	Max. 15 °C
592	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034 m			
593	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	3,053 m			
594	Tantal	1,800	0,210	1,380	0,0709	0,0083	0,0543	1,016 m			
595	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	5,067 m			
596	Tantal	4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647 m			
597	Tantal	4,900	0,500	3,900	0,1929	0,0197	0,1535	3,529 m			
598	Tantal-Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162 m			
599	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210 m		ground	
600	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480 m		ground	
601	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310 m			
602	Titan Gr. 2	0,820	0,156	0,508	0,0323	0,0061	0,0200	76,750 m			
603	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	664,655 m			
604	Titan Gr. 2	1,225	0,050	1,125	0,0482	0,0020	0,0443	46,511 m			
605	Titan Gr. 2	1,250	0,100	1,050	0,0492	0,0039	0,0413	62,150 m		ground	
606	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,806 m			
607	Titan Gr. 2	2,350	0,500	1,350	0,0925	0,0197	0,0531	2,800 m			
608	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490 m			
609	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670 m			

**Stock list - Tubes**current status: **04.05.2021**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
610	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
611	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
612	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		
613	Titan Gr. 2	7,925	0,889	6,147	0,3120	0,0350	0,2420	6,679	m		