

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	10,000	m		
2	1.4301 (304)	1,702	0,102	1,498	0,0670	0,0040	0,0590	83,000	St		
3	1.4301 (304)	1,956	0,102	1,752	0,0770	0,0040	0,0690	48,000	St		
4	1.4301 (304)	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
5	1.4301 (304)	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
6	1.4301 (304)	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
7	1.4301 (304)	6,700	0,500	5,700	0,2638	0,0197	0,2244	2,490	m		
8	1.4301 (304)	6,900	2,300	2,300	0,2717	0,0906	0,0906	5,250	m		
9	1.4301 (304)	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
10	1.4307	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
11	1.4452 (P 2000)	1,600	0,090	1,420	0,0630	0,0035	0,0559	8,636	m		
12	1.4452 (P 2000)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
13	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
14	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	30,775	m		
15	1.4452 (P 2000)	4,572	0,152	4,268	0,1800	0,0060	0,1680	19,059	m		
16	1.4541	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
17	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	14,722	m		
18	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	24,000	m		
19	1.4568	0,690	0,125	0,440	0,0272	0,0049	0,0173	7,854	m		
20	1.4568	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
21	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	15,956	m		

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	1.4568	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
23	1.4568	9,647	0,342	8,963	0,3798	0,0135	0,3529	9,570	m		
24	1.4568	10,313	0,342	9,629	0,4060	0,0135	0,3791	3,202	m		
25	1.4571	5,600	0,150	5,300	0,2205	0,0059	0,2087	278,000	St		
26	1.4571	5,950	0,150	5,700	0,2343	0,0059	0,2244	219,000	St		
27	1.4571	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
28	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	33,244	m		
29	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
30	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
31	316L	2,400	0,220	1,960	0,0945	0,0087	0,0772	12,129	m		
32	316L	2,610	0,220	2,170	0,1028	0,0087	0,0854	17,889	m		
33	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	8,621	m		
34	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
35	316L	4,290	0,300	3,690	0,1689	0,0118	0,1453	10,767	m		
36	316L	4,670	0,360	3,950	0,1839	0,0142	0,1555	10,300	m		
37	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
38	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	359,805	m		
39	316L	6,400	0,340	5,720	0,2520	0,0134	0,2252	35,044	m		
40	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	88,787	m		
41	316LVM	0,450	0,100	0,250	0,0177	0,0039	0,0098	54,471	m		
42	316LVM	0,518	0,099	0,320	0,0204	0,0039	0,0126	186,374	m		

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	24,093	m		
44	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	14,644	m		
45	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	38,274	m		
46	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	42,246	m		
47	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	35,800	m		
48	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	35,600	m		
49	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	45,981	m		
50	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	66,569	m		
51	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	13,188	m		
52	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	18,107	m		
53	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	46,025	m		
54	316LVM	1,330	0,175	0,980	0,0524	0,0069	0,0386	22,347	m		
55	316LVM	1,400	0,130	1,140	0,0551	0,0051	0,0449	33,968	m		
56	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
57	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
58	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
59	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	2,986	m		
60	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	6,362	m		
61	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	13,058	m		
62	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	9,943	m		
63	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	12,556	m		

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	15,660	m		
65	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	20,731	m		
66	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	19,953	m		
67	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
68	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	56,595	m		
69	316LVM	3,200	0,200	2,800	0,1260	0,0079	0,1102	45,450	m		
70	316LVM	3,230	0,115	3,000	0,1272	0,0045	0,1181	5,679	m		
71	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
72	316LVM	3,600	0,220	3,160	0,1417	0,0087	0,1244	73,248	m		
73	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	31,428	m		
74	316LVM	4,000	0,090	3,820	0,1575	0,0035	0,1504	8,373	m		
75	316LVM	4,572	0,229	4,114	0,1800	0,0090	0,1620	49,659	m		
76	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
77	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	10,683	m		
78	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	19,984	m		
79	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	29,609	m		
80	316LVM	5,000	0,250	4,500	0,1969	0,0098	0,1772	7,199	m		
81	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
82	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
83	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	19,306	m		
84	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	18,200	m		
86	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		
87	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	5,294	m		
88	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
89	316LVM	6,350	2,197	1,956	0,2500	0,0865	0,0770	1,596	m		
90	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	5,126	m		
91	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	6,030	m		
92	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
93	Biodur 108	1,220	0,075	1,070	0,0480	0,0030	0,0421	7,542	m		
94	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	46,797	m		
95	KC35N LT	0,356	0,102	0,152	0,0140	0,0040	0,0060	27,000	St		
96	KC35N LT	0,368	0,083	0,203	0,0145	0,0033	0,0080	29,000	St		
97	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	10,137	m		
98	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2290,000	St		
99	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	897,000	St		
100	KC35N LT	0,580	0,050	0,480	0,0228	0,0020	0,0189	6,063	m		
101	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	42,052	m		
102	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	5,666	m		
103	KC35N LT	0,914	0,038	0,838	0,0360	0,0015	0,0330	7,510	m		
104	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	41,639	m		
105	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	8,091	m		

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	1,240	0,070	1,100	0,0488	0,0028	0,0433	19,985	m		
107	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
108	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	17,178	m		
109	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
110	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	0,426	m		
111	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	0,836	m		
112	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
113	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	25,500	m		
114	KC35N LT	2,350	0,150	2,050	0,0925	0,0059	0,0807	21,407	m		
115	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
116	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
117	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	14,293	m		
118	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
119	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	9,819	m		
120	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,434	m		
121	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	4,047	m		
122	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	32,325	m		
123	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
124	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
125	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
126	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	11,154	m		

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	L605	0,762	0,127	0,508	0,0300	0,0050	0,0200	37,452	m		
128	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	3,792	m		
129	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,699	m		
130	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
131	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	24,138	m		
132	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
133	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	25,816	m		
134	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	108,200	m		
135	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	111,988	m		
136	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	3,300	m		
137	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
138	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		
139	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
140	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
141	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
142	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
143	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
144	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
145	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
146	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	66,151	m		
147	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	20,050	m		
149	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	14,270	m		
150	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	5,794	m		
151	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,504	m		
152	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
153	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	161,399	m		
154	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
155	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	5,555	m		
156	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	92,473	m		
157	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
158	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
159	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,423	m		
160	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
161	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
162	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
163	L605	1,800	0,104	1,592	0,0709	0,0041	0,0627	109,681	m		
164	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	107,761	m		
165	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	18,580	m		
166	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	517,960	m		
167	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	552,000	m		
168	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	67,150	m		

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
170	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	8,711	m		
171	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	9,500	m		
172	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	30,503	m		
173	L605	1,900	0,070	1,760	0,0748	0,0028	0,0693	12,315	m		
174	L605	1,900	0,070	1,760	0,0748	0,0028	0,0693	12,742	m		
175	L605	2,000	0,110	1,780	0,0787	0,0043	0,0701	44,013	m		
176	L605	2,000	0,240	1,520	0,0787	0,0094	0,0598	14,800	m		
177	L605	3,500	0,200	3,100	0,1378	0,0079	0,1220	11,265	m		
178	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
179	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	2,296	m		
180	L605	4,400	0,320	3,760	0,1732	0,0126	0,1480	7,444	m		
181	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
182	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	1,530	m		
183	L605	6,000	0,200	5,600	0,2362	0,0079	0,2205	4,011	m		
184	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
185	Mu-Metal	0,927	0,076	0,775	0,0365	0,0030	0,0305	3,065	m		
186	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
187	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	26,685	m		
188	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
189	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	NiTi	0,310	0,045	0,220	0,0122	0,0018	0,0087	55,250 m		dark oxidized	Max. 15 °C
191	NiTi	0,310	0,045	0,220	0,0122	0,0018	0,0087	6,762 m		dark oxidized	Max. 15 °C
192	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	1,000 m		ground	Max. 15 °C
193	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	40,000 m		ground	Max. 15 °C
194	NiTi	0,360	0,055	0,250	0,0142	0,0022	0,0098	8,199 m		dark oxidized	Max. 15 °C
195	NiTi	0,380	0,070	0,240	0,0150	0,0028	0,0094	65,000 St		ground	Max. 15 °C
196	NiTi	0,400	0,120	0,160	0,0157	0,0047	0,0063	7,090 m		ground	Max. 15 °C
197	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	46,115 m		ground	Max. 15 °C
198	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	7,671 m		ground	Max. 15 °C
199	NiTi	0,432	0,099	0,235	0,0170	0,0039	0,0093	60,317 m		ground	Max. 15 °C
200	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	7,756 m		dark oxidized	Max. 15 °C
201	NiTi	0,480	0,080	0,320	0,0189	0,0031	0,0126	37,973 m			Max. 15 °C
202	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	234,926 m		dark oxidized	Max. 15 °C
203	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	509,409 m		dark oxidized	Max. 15 °C
204	NiTi	0,559	0,090	0,379	0,0220	0,0035	0,0149	31,941 m		ground	Max. 15 °C
205	NiTi	0,570	0,090	0,390	0,0224	0,0035	0,0154	106,876 m		dark oxidized	Max. 15 °C
206	NiTi	0,570	0,100	0,370	0,0224	0,0039	0,0146	29,507 m		ground	Max. 15 °C
207	NiTi	0,635	0,100	0,435	0,0250	0,0039	0,0171	2,099 m		ground	Max. 15 °C
208	NiTi	0,640	0,120	0,400	0,0252	0,0047	0,0157	122,518 m		ground	Max. 15 °C
209	NiTi	0,660	0,102	0,456	0,0260	0,0040	0,0180	8,948 m		ground	Max. 15 °C
210	NiTi	0,690	0,120	0,450	0,0272	0,0047	0,0177	27,951 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,730	0,100	0,530	0,0287	0,0039	0,0209	33,642 m		ground	Max. 15 °C
212	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	530,960 m		dark oxidized	Max. 15 °C
213	NiTi	0,960	0,050	0,860	0,0378	0,0020	0,0339	20,368 m		ground	Max. 15 °C
214	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	133,802 m		ground	Max. 15 °C
215	NiTi	1,200	0,085	1,030	0,0472	0,0033	0,0406	18,787 m		ground	Max. 15 °C
216	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	39,235 m		ground	Max. 15 °C
217	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	210,027 m		ground	Max. 15 °C
218	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	29,212 m		ground	Max. 15 °C
219	NiTi	1,257	0,149	0,959	0,0495	0,0059	0,0378	343,228 m		ground	Max. 15 °C
220	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	26,531 m		ground	Max. 15 °C
221	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716 m		ground	Max. 15 °C
222	NiTi	1,280	0,160	0,960	0,0504	0,0063	0,0378	59,121 m		ground	Max. 15 °C
223	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	15,075 m		ground	Max. 15 °C
224	NiTi	1,300	0,220	0,860	0,0512	0,0087	0,0339	58,805 m		ground	Max. 15 °C
225	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	509,214 m		ground	Max. 15 °C
226	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	Max. 15 °C
227	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m		ground out-/oxidic inside	Max. 15 °C
228	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	20,797 m		ground out-/oxidic inside	Max. 15 °C
229	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	Max. 15 °C
230	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	1,690 m		ground	Max. 15 °C
231	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	8,124 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,096 m		ground	Max. 15 °C
233	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,257 m		ground	Max. 15 °C
234	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,329 m		ground	Max. 15 °C
235	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	Max. 15 °C
236	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	150,980 m		ground	Max. 15 °C
237	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	Max. 15 °C
238	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	Max. 15 °C
239	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	19,333 m		ground	Max. 15 °C
240	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	Max. 15 °C
241	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	Max. 15 °C
242	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	Max. 15 °C
243	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	Max. 15 °C
244	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	Max. 15 °C
245	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,824 m		ground	Max. 15 °C
246	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	39,443 m		ground	Max. 15 °C
247	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	Max. 15 °C
248	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	Max. 15 °C
249	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,300 m		ground	Max. 15 °C
250	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	8,219 m		ground	Max. 15 °C
251	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	10,634 m		ground	Max. 15 °C
252	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	13,197 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	33,700	m	ground	Max. 15 °C
254	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	7,858	m	ground	Max. 15 °C
255	NiTi	1,520	0,280	0,960	0,0598	0,0110	0,0378	15,440	m	ground	Max. 15 °C
256	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	34,602	m	ground out-/oxidic inside	Max. 15 °C
257	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	35,880	m	ground out-/oxidic inside	Max. 15 °C
258	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	26,560	m	ground out-/oxidic inside	Max. 15 °C
259	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	30,677	m	ground	Max. 15 °C
260	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	32,218	m	ground	Max. 15 °C
261	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,238	m	ground	Max. 15 °C
262	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	8,598	m	ground	Max. 15 °C
263	NiTi	1,600	0,340	0,920	0,0630	0,0134	0,0362	20,775	m	ground	Max. 15 °C
264	NiTi	1,600	0,474	0,653	0,0630	0,0187	0,0257	2,000	St	ground	Max. 15 °C
265	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	1,312	m	ground	Max. 15 °C
266	NiTi	1,610	0,230	1,150	0,0634	0,0091	0,0453	6,342	m	ground	Max. 15 °C
267	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	Max. 15 °C
268	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	10,817	m	ground out-/oxidic inside	Max. 15 °C
269	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737	m	ground out-/oxidic inside	Max. 15 °C
270	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970	m	ground out-/oxidic inside	Max. 15 °C
271	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820	m	ground out-/oxidic inside	Max. 15 °C
272	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,092	m	polished	Max. 15 °C
273	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	3,427	m	ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609 m		ground	Max. 15 °C
275	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,745 m		ground	Max. 15 °C
276	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,316 m		ground	Max. 15 °C
277	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	296,480 m		ground	Max. 15 °C
278	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279 m		ground	Max. 15 °C
279	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	21,363 m		ground	Max. 15 °C
280	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	3,671 m		ground	Max. 15 °C
281	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	Max. 15 °C
282	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	Max. 15 °C
283	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,074 m		dark oxidized	Max. 15 °C
284	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	Max. 15 °C
285	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	Max. 15 °C
286	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	Max. 15 °C
287	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	61,033 m		ground	Max. 15 °C
288	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	Max. 15 °C
289	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,920 m		ground	Max. 15 °C
290	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	Max. 15 °C
291	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	Max. 15 °C
292	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	Max. 15 °C
293	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	Max. 15 °C
294	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	Max. 15 °C
296	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,054 m		ground	Max. 15 °C
297	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	Max. 15 °C
298	NiTi	1,670	0,100	1,470	0,0657	0,0039	0,0579	5,546 m		polished	Max. 15 °C
299	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	26,000	St	ground	Max. 15 °C
300	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	204,474 m		ground out-/oxidic inside	Max. 15 °C
301	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	266,994 m		ground out-/oxidic inside	Max. 15 °C
302	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	18,844 m		ground	Max. 15 °C
303	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	35,912 m		ground	Max. 15 °C
304	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	15,720 m		ground	Max. 15 °C
305	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	Max. 15 °C
306	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	Max. 15 °C
307	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	Max. 15 °C
308	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,379 m		ground	Max. 15 °C
309	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m		ground	Max. 15 °C
310	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	Max. 15 °C
311	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,726 m		ground	Max. 15 °C
312	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	Max. 15 °C
313	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	Max. 15 °C
314	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	Max. 15 °C
315	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,150 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,800	0,070	1,660	0,0709	0,0028	0,0654	4,143 m		ground	Max. 15 °C
317	NiTi	1,800	0,075	1,650	0,0709	0,0030	0,0650	15,310 m		ground	Max. 15 °C
318	NiTi	1,800	0,080	1,640	0,0709	0,0031	0,0646	6,594 m		ground	Max. 15 °C
319	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	3,638 m		ground	Max. 15 °C
320	NiTi	1,820	0,280	1,260	0,0717	0,0110	0,0496	18,483 m		ground	Max. 15 °C
321	NiTi	1,921	0,203	1,515	0,0756	0,0080	0,0596	82,160 m		ground	Max. 15 °C
322	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	42,523 m		ground	Max. 15 °C
323	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	240,564 m		ground	Max. 15 °C
324	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	46,724 m		ground	Max. 15 °C
325	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	55,608 m		ground	Max. 15 °C
326	NiTi	2,000	0,085	1,830	0,0787	0,0033	0,0720	7,611 m		dark oxidized	Max. 15 °C
327	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	27,510 m		ground	Max. 15 °C
328	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m		ground	Max. 15 °C
329	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	18,599 m		ground	Max. 15 °C
330	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	209,029 m		ground	Max. 15 °C
331	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	33,730 m		ground	Max. 15 °C
332	NiTi	2,019	0,267	1,486	0,0795	0,0105	0,0585	1,364 m		ground	Max. 15 °C
333	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	1,383 m		ground	Max. 15 °C
334	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	205,106 m		polished	Max. 15 °C
335	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	42,545 m		polished	Max. 15 °C
336	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	8,242 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	45,595 m		ground	Max. 15 °C
338	NiTi	2,118	0,056	2,006	0,0834	0,0022	0,0790	5,666 m		ground	Max. 15 °C
339	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	76,717 m		ground	Max. 15 °C
340	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	11,469 m		ground	Max. 15 °C
341	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	297,031 m		ground	Max. 15 °C
342	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	21,907 m		ground	Max. 15 °C
343	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	6,191 m		ground	Max. 15 °C
344	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	3,179 m		ground	Max. 15 °C
345	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	20,471 m		ground out-/oxidic inside	Max. 15 °C
346	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	56,236 m		ground out-/oxidic inside	Max. 15 °C
347	NiTi	2,200	0,079	2,042	0,0866	0,0031	0,0804	11,315 m		ground	Max. 15 °C
348	NiTi	2,200	0,080	2,040	0,0866	0,0031	0,0803	77,930 m		ground	Max. 15 °C
349	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	Max. 15 °C
350	NiTi	2,300	0,150	2,000	0,0906	0,0059	0,0787	2,238 m		ground	Max. 15 °C
351	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	Max. 15 °C
352	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,441 m		ground	Max. 15 °C
353	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,432 m		ground	Max. 15 °C
354	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	54,223 m		ground	Max. 15 °C
355	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	Max. 15 °C
356	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	11,886 m		ground out-/oxidic inside	Max. 15 °C
357	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	15,466 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	Max. 15 °C
359	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	24,930 m		ground	Max. 15 °C
360	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	Max. 15 °C
361	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,731 m		ground out-/oxidic inside	Max. 15 °C
362	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	Max. 15 °C
363	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,768 m		ground out-/oxidic inside	Max. 15 °C
364	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	Max. 15 °C
365	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	26,056 m		ground	Max. 15 °C
366	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	40,566 m		ground	Max. 15 °C
367	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	2,297 m		ground	Max. 15 °C
368	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	8,280 m		ground	Max. 15 °C
369	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	Max. 15 °C
370	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	7,121 m		ground	Max. 15 °C
371	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	17,933 m		ground	Max. 15 °C
372	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	34,124 m		dark oxidized	Max. 15 °C
373	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	8,114 m		ground	Max. 15 °C
374	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	26,177 m		ground	Max. 15 °C
375	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	14,936 m		ground	Max. 15 °C
376	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	2,291 m		ground	Max. 15 °C
377	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	22,810 m		ground	Max. 15 °C
378	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	39,840 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	7,087 m		ground	Max. 15 °C
380	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	20,752 m		ground	Max. 15 °C
381	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	8,064 m		ground	Max. 15 °C
382	NiTi	2,500	0,085	2,330	0,0984	0,0033	0,0917	8,460 m		dark oxidized	Max. 15 °C
383	NiTi	2,500	0,100	2,300	0,0984	0,0039	0,0906	30,468 m		ground	Max. 15 °C
384	NiTi	2,500	0,550	1,400	0,0984	0,0217	0,0551	4,702 m			Max. 15 °C
385	NiTi	2,520	0,270	1,980	0,0992	0,0106	0,0780	42,000 St		ground	Max. 15 °C
386	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	1,485 m		ground out-/oxidic inside	Max. 15 °C
387	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,501 m		ground	Max. 15 °C
388	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	7,459 m		ground	Max. 15 °C
389	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m		ground	Max. 15 °C
390	NiTi	2,600	0,300	2,000	0,1024	0,0118	0,0787	39,662 m		ground	Max. 15 °C
391	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	29,949 m		ground out-/oxidic inside	Max. 15 °C
392	NiTi	2,600	0,510	1,580	0,1024	0,0201	0,0622	78,567 m		ground	Max. 15 °C
393	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	3,035 m		ground	Max. 15 °C
394	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	41,293 m		ground	Max. 15 °C
395	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	28,588 m		ground	Max. 15 °C
396	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,526 m		ground	Max. 15 °C
397	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	59,319 m		ground	Max. 15 °C
398	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,145 m		ground	Max. 15 °C
399	NiTi	2,640	0,450	1,740	0,1039	0,0177	0,0685	2,990 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	2,309 m		ground	Max. 15 °C
401	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	1,143 m		ground	Max. 15 °C
402	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	3,594 m		ground	Max. 15 °C
403	NiTi	2,800	0,100	2,600	0,1102	0,0039	0,1024	47,645 m		ground	Max. 15 °C
404	NiTi	2,800	0,610	1,580	0,1102	0,0240	0,0622	15,550 m		ground	Max. 15 °C
405	NiTi	2,819	0,371	2,077	0,1110	0,0146	0,0818	7,000 St		ground	Max. 15 °C
406	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	46,479 m		ground	Max. 15 °C
407	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	6,469 m		ground	Max. 15 °C
408	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	9,460 m		ground	Max. 15 °C
409	NiTi	3,000	0,100	2,800	0,1181	0,0039	0,1102	2,785 m		ground	Max. 15 °C
410	NiTi	3,000	0,100	2,800	0,1181	0,0039	0,1102	9,302 m		ground	Max. 15 °C
411	NiTi	3,000	0,500	2,000	0,1181	0,0197	0,0787	7,591 m		ground out-/oxidic inside	Max. 15 °C
412	NiTi	3,048	0,241	2,566	0,1200	0,0095	0,1010	5,477 m		ground	Max. 15 °C
413	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,410 m		ground out-/oxidic inside	Max. 15 °C
414	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,863 m		ground out-/oxidic inside	Max. 15 °C
415	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,371 m		ground out-/oxidic inside	Max. 15 °C
416	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	31,649 m		ground	Max. 15 °C
417	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	6,001 m		ground	Max. 15 °C
418	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	72,327 m		ground	Max. 15 °C
419	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	7,241 m		ground	Max. 15 °C
420	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	6,642 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	1,134 m		ground	Max. 15 °C
422	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	12,560 m		ground	Max. 15 °C
423	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	6,409 m		ground	Max. 15 °C
424	NiTi	3,800	0,265	3,270	0,1496	0,0104	0,1287	1,805 m		ground	Max. 15 °C
425	NiTi	4,000	0,300	3,400	0,1575	0,0118	0,1339	20,747 m		ground	Max. 15 °C
426	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	Max. 15 °C
427	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	143,098 m		ground	Max. 15 °C
428	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	170,966 m		ground out-/oxidic inside	Max. 15 °C
429	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	Max. 15 °C
430	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	Max. 15 °C
431	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	Max. 15 °C
432	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	Max. 15 °C
433	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	Max. 15 °C
434	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	Max. 15 °C
435	NiTi	5,000	0,100	4,800	0,1969	0,0039	0,1890	57,441 m		ground	Max. 15 °C
436	NiTi	5,000	0,500	4,000	0,1969	0,0197	0,1575	2,404 m		ground	Max. 15 °C
437	NiTi	5,000	0,500	4,000	0,1969	0,0197	0,1575	51,108 m		ground	Max. 15 °C
438	NiTi	5,001	0,114	4,773	0,1969	0,0045	0,1879	7,967 m		ground	Max. 15 °C
439	NiTi	5,200	0,200	4,800	0,2047	0,0079	0,1890	8,882 m		ground	Max. 15 °C
440	NiTi	5,840	0,120	5,600	0,2299	0,0047	0,2205	145,072 m		ground	Max. 15 °C
441	NiTi	5,893	0,546	4,801	0,2320	0,0215	0,1890	7,086 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)

west USA: Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	5,980	0,540	4,900	0,2354	0,0213	0,1929	17,717 m		ground	Max. 15 °C
443	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	2,015 m		ground out-/oxidic inside	Max. 15 °C
444	NiTi	6,000	0,080	5,840	0,2362	0,0031	0,2299	12,982 m		ground	Max. 15 °C
445	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	4,353 m		ground	Max. 15 °C
446	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	9,398 m		ground	Max. 15 °C
447	NiTi	6,800	0,430	5,940	0,2677	0,0169	0,2339	0,923 m		ground	Max. 15 °C
448	NiTi	7,000	0,080	6,840	0,2756	0,0031	0,2693	32,421 m		ground	Max. 15 °C
449	NiTi	7,000	0,090	6,820	0,2756	0,0035	0,2685	25,993 m		ground	Max. 15 °C
450	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	13,894 m		ground	Max. 15 °C
451	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	16,395 m		ground	Max. 15 °C
452	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	2,012 m		ground	Max. 15 °C
453	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	24,113 m		ground	Max. 15 °C
454	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	4,539 m		ground	Max. 15 °C
455	NiTi	8,000	0,300	7,400	0,3150	0,0118	0,2913	4,132 m		ground	Max. 15 °C
456	NiTi	8,000	0,370	7,260	0,3150	0,0146	0,2858	38,284 m		ground	Max. 15 °C
457	NiTi	8,000	0,445	7,110	0,3150	0,0175	0,2799	22,797 m		ground	Max. 15 °C
458	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,634 m		ground	Max. 15 °C
459	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	1,825 m		ground	Max. 15 °C
460	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	6,252 m		ground	Max. 15 °C
461	NiTi	9,000	0,500	8,000	0,3543	0,0197	0,3150	8,839 m		ground	Max. 15 °C
462	NiTi	9,900	0,625	8,650	0,3898	0,0246	0,3406	1,114 m		ground	Max. 15 °C

Stock list - Tubes

current status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	10,000	0,300	9,400	0,3937	0,0118	0,3701	2,516 m		ground	Max. 15 °C
464	NiTi	10,000	0,400	9,200	0,3937	0,0157	0,3622	10,772 m		ground	Max. 15 °C
465	NiTi	10,000	0,470	9,060	0,3937	0,0185	0,3567	4,329 m		ground	Max. 15 °C
466	NiTi	10,000	0,600	8,800	0,3937	0,0236	0,3465	4,610 m		ground	Max. 15 °C
467	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	0,701 m		ground	Max. 15 °C
468	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	9,650 m			
469	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	2,207 m			
470	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	3,897 m			
471	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	30,791 m			
472	Tantal	4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647 m			
473	Tantal	4,900	0,500	3,900	0,1929	0,0197	0,1535	1,538 m			
474	Tantal-Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162 m			
475	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210 m		ground	
476	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480 m		ground	
477	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310 m			
478	Titan Gr. 2	0,820	0,156	0,508	0,0323	0,0061	0,0200	67,156 m			
479	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	662,317 m			
480	Titan Gr. 2	1,225	0,050	1,125	0,0482	0,0020	0,0443	44,997 m			
481	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,027 m			
482	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	2,490 m			
483	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670 m			

Stock list - Tubescurrent status: **05.08.2022**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
485	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
486	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		