

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1		1,500	0,178	1,144	0,0591	0,0070	0,0450	8,990	m		
2		1,800	0,210	1,380	0,0709	0,0083	0,0543	1,016	m		
3		4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647	m		
4		4,900	0,500	3,900	0,1929	0,0197	0,1535	3,529	m		
5	(1.4301 (304))	0,356	0,075	0,206	0,0140	0,0030	0,0081	3,000	m		
6	(1.4301 (304))	0,410	0,045	0,320	0,0161	0,0018	0,0126	54,933	m		
7	(1.4301 (304))	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
8	(1.4301 (304))	1,372	0,305	0,762	0,0540	0,0120	0,0300	20,000	m		
9	(1.4301 (304))	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
10	(1.4301 (304))	2,515	0,051	2,413	0,0990	0,0020	0,0950	9,000	St		
11	(1.4301 (304))	3,000	0,300	2,400	0,1181	0,0118	0,0945	4,369	m		
12	(1.4301 (304))	3,600	0,300	3,000	0,1417	0,0118	0,1181	5,328	m		
13	(1.4301 (304))	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
14	(1.4301 (304))	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
15	(1.4301 (304))	6,700	0,500	5,700	0,2638	0,0197	0,2244	12,728	m		
16	(1.4301 (304))	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
17	(1.4301 (304))	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
18	(1.4307)	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
19	(1.4452)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
20	(1.4452)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
21	(1.4452)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	(1.4452)	1,800	0,090	1,620	0,0709	0,0035	0,0638	31,775	m		
23	(1.4452)	2,350	0,150	2,050	0,0925	0,0059	0,0807	4,737	m		
24	(1.4452)	4,500	0,220	4,060	0,1772	0,0087	0,1598	2,393	m		
25	(1.4452)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
26	(1.4541)	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
27	(1.4568)	0,690	0,125	0,440	0,0272	0,0049	0,0173	8,854	m		
28	(1.4568)	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
29	(1.4568)	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
30	(1.4568)	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
31	(1.4568)	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
32	(1.4568)	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
33	(1.4571)	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
34	00Cr18Mn15Mo3	1,800	0,110	1,580	0,0709	0,0043	0,0622	8,000	m		
35	316L	0,457	0,070	0,317	0,0180	0,0028	0,0125	6,939	m		
36	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	45,250	m		
37	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	194,020	m		
38	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
39	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
40	316L	3,000	0,100	2,800	0,1181	0,0039	0,1102	10,732	m		
41	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	13,621	m		
42	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	107,000	St		
44	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
45	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	367,466	m		
46	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	137,167	m		
47	316LVM	0,450	0,075	0,300	0,0177	0,0030	0,0118	9,481	m		
48	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	61,000	m		
49	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	27,113	m		
50	316LVM	0,635	0,076	0,483	0,0250	0,0030	0,0190	13,000	m		
51	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	23,050	m		
52	316LVM	0,724	0,100	0,524	0,0285	0,0039	0,0206	1,462	m		
53	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	37,212	m		
54	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	138,710	m		
55	316LVM	0,960	0,120	0,720	0,0378	0,0047	0,0283	5,727	m		
56	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	48,370	m		
57	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	74,290	m		
58	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	24,981	m		
59	316LVM	1,000	0,200	0,600	0,0394	0,0079	0,0236	51,603	m		
60	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
61	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	62,780	m		
62	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	66,530	m		
63	316LVM	1,169	0,102	0,965	0,0460	0,0040	0,0380	4,104	m		

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
65	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
66	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
67	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	8,953	m		
68	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
69	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		
70	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	19,602	m		
71	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	11,761	m		
72	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	13,998	m		
73	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
74	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	48,700	m		
75	316LVM	2,100	0,100	1,900	0,0827	0,0039	0,0748	18,853	m		
76	316LVM	2,400	0,100	2,200	0,0945	0,0039	0,0866	25,027	m		
77	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	29,849	m		
78	316LVM	2,530	0,100	2,330	0,0996	0,0039	0,0917	5,508	m		
79	316LVM	2,610	0,220	2,170	0,1028	0,0087	0,0854	6,803	m		
80	316LVM	2,730	0,220	2,290	0,1075	0,0087	0,0902	2,882	m		
81	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
82	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	77,395	m		
83	316LVM	3,110	0,105	2,900	0,1224	0,0041	0,1142	29,707	m		
84	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	46,767	m		
86	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
87	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	9,885	m		
88	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
89	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
90	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	22,012	m		
91	316LVM	5,436	0,216	5,003	0,2140	0,0085	0,1970	3,475	m		
92	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
93	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
94	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
95	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	30,982	m		
96	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	21,000	m		
97	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		
98	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	52,701	m		
99	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
100	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	12,404	m		
101	316LVM	7,940	0,510	6,920	0,3126	0,0201	0,2724	4,620	m		
102	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		
103	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
104	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	6,251	m		
105	316LVM	10,000	0,500	9,000	0,3937	0,0197	0,3543	28,295	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	75,001	m		
107	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	41,889	m		
108	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	3,100	m		
109	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2310,000	St		
110	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	935,000	St		
111	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	48,190	m		
112	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	9,886	m		
113	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		
114	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		
115	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
116	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
117	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
118	KC35N LT	1,500	0,130	1,240	0,0591	0,0051	0,0488	23,010	m		
119	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
120	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	1,816	m		
121	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	14,397	m		
122	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
123	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		
124	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
125	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
126	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
128	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	56,410	m		
129	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	12,232	m		
130	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
131	KC35N LT	6,000	0,550	4,900	0,2362	0,0217	0,1929	13,402	m		
132	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		
133	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
134	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	37,340	m		
135	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
136	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
137	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
138	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	16,160	m		
139	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,451	m		
140	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
141	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	45,448	m		
142	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
143	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
144	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	10,764	m		
145	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	26,260	m		
146	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
147	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
149	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
150	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
151	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
152	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
153	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
154	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
155	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		
156	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	10,264	m		
157	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	164,603	m		
158	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	18,890	m		
159	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	9,221	m		
160	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
161	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,532	m		
162	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
163	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
164	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	153,966	m		
165	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	204,174	m		
166	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
167	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
168	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		
170	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	22,750	m		
171	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	374,899	m		
172	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
173	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
174	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
175	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
176	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
177	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		
178	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
179	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
180	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
181	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	111,553	m		
182	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	21,220	m		
183	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	582,780	m		
184	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
185	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	32,710	m		
186	L605	2,997	0,107	2,783	0,1180	0,0042	0,1096	6,457	m		
187	L605	3,000	0,170	2,660	0,1181	0,0067	0,1047	67,387	m		
188	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	16,400	m		
189	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	100,710	m		

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
191	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	16,700	m		
192	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
193	L605	4,400	0,280	3,840	0,1732	0,0110	0,1512	4,485	m		
194	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
195	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	3,030	m		
196	L605	5,000	0,200	4,600	0,1969	0,0079	0,1811	11,146	m		
197	L605	6,000	0,250	5,500	0,2362	0,0098	0,2165	9,199	m		
198	L605	8,200	0,250	7,700	0,3228	0,0098	0,3031	8,967	m		
199	L605	8,890	0,813	7,264	0,3500	0,0320	0,2860	3,962	m		
200	L605	8,890	0,813	7,264	0,3500	0,0320	0,2860	5,283	m		
201	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
202	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
203	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
204	NiTi	0,100	0,040	0,020	0,0039	0,0016	0,0008	18,200	m	ground	max. 15 °C
205	NiTi	0,216	0,038	0,140	0,0085	0,0015	0,0055	13,038	m	ground	max. 15 °C
206	NiTi	0,240	0,090	0,060	0,0094	0,0035	0,0024	3,820	m	ground	max. 15 °C
207	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	10,757	m	ground	max. 15 °C
208	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	max. 15 °C
209	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	56,000	m	ground	max. 15 °C
210	NiTi	0,350	0,125	0,100	0,0138	0,0049	0,0039	3,390	m	ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	133,457 m		dark oxidized	max. 15 °C
212	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	14,421 m		dark oxidized	max. 15 °C
213	NiTi	0,400	0,080	0,240	0,0157	0,0031	0,0094	2,136 m		ground out-/oxidic inside	
214	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	10,388 m		ground	max. 15 °C
215	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	48,598 m		ground	
216	NiTi	0,432	0,090	0,252	0,0170	0,0035	0,0099	24,774 m		ground	max. 15 °C
217	NiTi	0,450	0,050	0,350	0,0177	0,0020	0,0138	10,747 m		ground	max. 15 °C
218	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	31,544 m		dark oxidized	max. 15 °C
219	NiTi	0,460	0,050	0,360	0,0181	0,0020	0,0142	5,903 m		ground	max. 15 °C
220	NiTi	0,480	0,076	0,328	0,0189	0,0030	0,0129	16,197 m		ground	max. 15 °C
221	NiTi	0,570	0,090	0,390	0,0224	0,0035	0,0154	1,899 m		dark oxidized	max. 15 °C
222	NiTi	0,580	0,115	0,350	0,0228	0,0045	0,0138	0,996 m		ground	max. 15 °C
223	NiTi	0,600	0,080	0,440	0,0236	0,0031	0,0173	13,085 m		ground out-/oxidic inside	
224	NiTi	0,635	0,102	0,432	0,0250	0,0040	0,0170	119,397 m		ground	max. 15 °C
225	NiTi	0,640	0,100	0,440	0,0252	0,0039	0,0173	7,243 m		ground	max. 15 °C
226	NiTi	0,660	0,076	0,508	0,0260	0,0030	0,0200	22,000 St		ground	max. 15 °C
227	NiTi	0,730	0,150	0,430	0,0287	0,0059	0,0169	22,485 m		ground out-/oxidic inside	max. 15 °C
228	NiTi	0,792	0,099	0,594	0,0312	0,0039	0,0234	6,447 m		ground	max. 15 °C
229	NiTi	0,880	0,115	0,650	0,0346	0,0045	0,0256	2,853 m		ground	max. 15 °C
230	NiTi	0,900	0,190	0,520	0,0354	0,0075	0,0205	9,275 m		dark oxidized	max. 15 °C
231	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	47,800 m		dark oxidized	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	0,960	0,050	0,860	0,0378	0,0020	0,0339	7,587 m		ground	max. 15 °C
233	NiTi	1,000	0,050	0,900	0,0394	0,0020	0,0354	26,235 m		ground	max. 15 °C
234	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	19,884 m		ground	
235	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	60,170 m		ground	
236	NiTi	1,080	0,040	1,000	0,0425	0,0016	0,0394	1,161 m		ground	max. 15 °C
237	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	44,348 m		ground	max. 15 °C
238	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	40,920 m		ground	max. 15 °C
239	NiTi	1,200	0,125	0,950	0,0472	0,0049	0,0374	4,725 m		ground	max. 15 °C
240	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	3,675 m		ground out-/oxidic inside	
241	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	4,995 m		ground out-/oxidic inside	
242	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	9,088 m		ground out-/oxidic inside	max. 15 °C
243	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	239,427 m		ground	max. 15 °C
244	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	172,269 m		ground	max. 15 °C
245	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	8,648 m		ground	max. 15 °C
246	NiTi	1,240	0,230	0,780	0,0488	0,0091	0,0307	24,456 m		ground	max. 15 °C
247	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716 m		ground	max. 15 °C
248	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	80,843 m		ground	max. 15 °C
249	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,520 m		ground	max. 15 °C
250	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	40,733 m		ground	max. 15 °C
251	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,632 m		ground	max. 15 °C
252	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	12,460 m	ground		max. 15 °C
254	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m	ground	out-/oxidic inside	
255	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	24,000 m	ground	out-/oxidic inside	
256	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m	ground		
257	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,030 m	ground		
258	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	3,250 m	ground		
259	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m	ground		
260	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,129 m	ground		
261	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,410 m	ground		
262	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m	ground		
263	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m	ground		
264	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	175,017 m	ground		
265	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m	ground		
266	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m	ground		
267	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,500 m	ground		
268	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m	ground		
269	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m	ground		max. 15 °C
270	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m	ground		max. 15 °C
271	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m	ground		
272	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,943 m	ground		
273	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	39,400 m	ground		

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	
275	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	
276	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	40,650 m		ground	max. 15 °C
277	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	6,151 m		ground	
278	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	9,410 m		ground	
279	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	19,235 m		ground	max. 15 °C
280	NiTi	1,350	0,135	1,080	0,0531	0,0053	0,0425	11,961 m		ground	max. 15 °C
281	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	12,215 m		ground	max. 15 °C
282	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	12,364 m		ground	max. 15 °C
283	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	10,187 m		ground	max. 15 °C
284	NiTi	1,390	0,130	1,130	0,0547	0,0051	0,0445	15,575 m		ground	max. 15 °C
285	NiTi	1,400	0,240	0,920	0,0551	0,0094	0,0362	2,801 m		ground	max. 15 °C
286	NiTi	1,400	0,240	0,920	0,0551	0,0094	0,0362	3,000 m		ground	max. 15 °C
287	NiTi	1,420	0,160	1,100	0,0559	0,0063	0,0433	2,420 m		ground	max. 15 °C
288	NiTi	1,422	0,051	1,320	0,0560	0,0020	0,0520	12,281 m		ground	
289	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	5,939 m		ground	max. 15 °C
290	NiTi	1,450	0,225	1,000	0,0571	0,0089	0,0394	3,630 m		ground	max. 15 °C
291	NiTi	1,450	0,225	1,000	0,0571	0,0089	0,0394	3,870 m		ground	max. 15 °C
292	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	1,859 m		ground	max. 15 °C
293	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	5,762 m		ground	max. 15 °C
294	NiTi	1,524	0,114	1,296	0,0600	0,0045	0,0510	7,000 St		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,524	0,127	1,270	0,0600	0,0050	0,0500	2,492 m		ground	max. 15 °C
296	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	19,461 m		ground	max. 15 °C
297	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	64,005 m		ground	max. 15 °C
298	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	8,878 m		ground	max. 15 °C
299	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	87,904 m		ground	max. 15 °C
300	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	1,300 m		ground	max. 15 °C
301	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080 m		ground out-/oxidic inside	max. 15 °C
302	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	96,900 m		ground out-/oxidic inside	max. 15 °C
303	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	16,307 m		ground	max. 15 °C
304	NiTi	1,560	0,130	1,300	0,0614	0,0051	0,0512	17,080 m		ground	max. 15 °C
305	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,532 m		ground out-/oxidic inside	max. 15 °C
306	NiTi	1,600	0,200	1,200	0,0630	0,0079	0,0472	14,569 m			70 - 110 °C
307	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	158,940 m		ground	max. 15 °C
308	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	247,196 m		ground	max. 15 °C
309	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	44,811 m		ground	max. 15 °C
310	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	75,072 m		ground	max. 15 °C
311	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	22,144 m		ground	max. 15 °C
312	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,077 m		ground	max. 15 °C
313	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	66,396 m		ground	max. 15 °C
314	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	9,605 m		ground	max. 15 °C
315	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	3,490 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,620	0,240	1,140	0,0638	0,0094	0,0449	39,435 m		ground out-/oxidic inside	max. 15 °C
317	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	max. 15 °C
318	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	13,028 m		ground out-/oxidic inside	max. 15 °C
319	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737 m		ground out-/oxidic inside	
320	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	271,498 m		ground out-/oxidic inside	max. 15 °C
321	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970 m		ground out-/oxidic inside	max. 15 °C
322	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	88,612 m		ground out-/oxidic inside	max. 15 °C
323	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820 m		ground out-/oxidic inside	max. 15 °C
324	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,170 m		polished	max. 15 °C
325	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	4,631 m		ground	max. 15 °C
326	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609 m		ground	max. 15 °C
327	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,965 m		ground	max. 15 °C
328	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,165 m		ground	
329	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	181,246 m		ground	max. 15 °C
330	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279 m		ground	max. 15 °C
331	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	
332	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		dark oxidized	
333	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	
334	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	
335	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,627 m		ground	
336	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	
338	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	61,610 m		ground	max. 15 °C
339	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	
340	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,980 m		ground	
341	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	91,179 m		ground	max. 15 °C
342	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	
343	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	
344	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	
345	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	
346	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	
347	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	
348	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	255,144 m		ground	max. 15 °C
349	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,150 m		ground	max. 15 °C
350	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	max. 15 °C
351	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	126,000 St		ground	max. 15 °C
352	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	215,668 m		ground out-/oxidic inside	max. 15 °C
353	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	289,941 m		ground out-/oxidic inside	max. 15 °C
354	NiTi	1,700	0,210	1,280	0,0669	0,0083	0,0504	1,539 m		ground	max. 15 °C
355	NiTi	1,700	0,300	1,100	0,0669	0,0118	0,0433	2,640 m		ground	max. 15 °C
356	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	193,756 m		ground	max. 15 °C
357	NiTi	1,729	0,210	1,309	0,0681	0,0083	0,0515	9,600 m		ground	

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	36,100 m		ground	
359	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	
360	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m		ground	max. 15 °C
361	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	
362	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	max. 15 °C
363	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,323 m		ground	max. 15 °C
364	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m		ground	max. 15 °C
365	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	max. 15 °C
366	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	
367	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	
368	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,900 m		ground	
369	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	max. 15 °C
370	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,250 m		ground	
371	NiTi	1,778	0,406	0,966	0,0700	0,0160	0,0380	22,252 m		ground	max. 15 °C
372	NiTi	1,796	0,250	1,296	0,0707	0,0098	0,0510	2,181 m		ground	max. 15 °C
373	NiTi	1,796	0,250	1,296	0,0707	0,0098	0,0510	4,875 m		ground	max. 15 °C
374	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	16,992 m		ground	max. 15 °C
375	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	max. 15 °C
376	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	64,888 m		ground	max. 15 °C
377	NiTi	1,800	0,220	1,360	0,0709	0,0087	0,0535	1,438 m		ground	max. 15 °C
378	NiTi	1,803	0,216	1,371	0,0710	0,0085	0,0540	7,750 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,238 m		ground	max. 15 °C
380	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,716 m		ground	max. 15 °C
381	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	5,537 m		ground	max. 15 °C
382	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	11,549 m		ground	max. 15 °C
383	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	5,627 m		ground	max. 15 °C
384	NiTi	1,829	0,267	1,295	0,0720	0,0105	0,0510	1,548 m		ground	max. 15 °C
385	NiTi	1,829	0,292	1,245	0,0720	0,0115	0,0490	5,967 m		ground	max. 15 °C
386	NiTi	1,900	0,370	1,160	0,0748	0,0146	0,0457	8,895 m		ground	max. 15 °C
387	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	11,009 m		ground	max. 15 °C
388	NiTi	1,915	0,165	1,585	0,0754	0,0065	0,0624	15,890 m		ground	max. 15 °C
389	NiTi	1,915	0,165	1,585	0,0754	0,0065	0,0624	5,860 m		ground	max. 15 °C
390	NiTi	1,930	0,305	1,320	0,0760	0,0120	0,0520	145,604 m		ground out-/oxidic inside	max. 15 °C
391	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	12,453 m		ground	max. 15 °C
392	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	14,280 m		ground	max. 15 °C
393	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	156,705 m		ground	max. 15 °C
394	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990 m		ground	max. 15 °C
395	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m		ground	max. 15 °C
396	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	21,199 m		ground	max. 15 °C
397	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	43,678 m		ground	max. 15 °C
398	NiTi	2,019	0,266	1,487	0,0795	0,0105	0,0585	3,728 m		ground	max. 15 °C
399	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	6,924 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847 m		ground	max. 15 °C
401	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	329,792 m		ground	max. 15 °C
402	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	333,511 m		ground	max. 15 °C
403	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	413,795 m		ground	max. 15 °C
404	NiTi	2,050	0,150	1,750	0,0807	0,0059	0,0689	1,672 m		ground	max. 15 °C
405	NiTi	2,050	0,300	1,450	0,0807	0,0118	0,0571	13,025 m		ground	max. 15 °C
406	NiTi	2,100	0,250	1,600	0,0827	0,0098	0,0630	16,462 m		ground	max. 15 °C
407	NiTi	2,120	0,320	1,480	0,0835	0,0126	0,0583	12,945 m		ground	max. 15 °C
408	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	4,950 m		ground	max. 15 °C
409	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	17,172 m		ground	max. 15 °C
410	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	21,817 m		ground	max. 15 °C
411	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	23,347 m		ground	max. 15 °C
412	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	25,863 m		ground	max. 15 °C
413	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	31,296 m		ground	max. 15 °C
414	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	130,730 m		ground	max. 15 °C
415	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	25,753 m		ground	max. 15 °C
416	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	3,772 m		ground	max. 15 °C
417	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	341,218 m		ground	max. 15 °C
418	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	16,710 m		ground	max. 15 °C
419	NiTi	2,180	0,370	1,440	0,0858	0,0146	0,0567	12,634 m		ground	max. 15 °C
420	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	1,840 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	13,550 m		ground	
422	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	9,847 m		ground	
423	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	8,283 m		ground	
424	NiTi	2,184	0,349	1,486	0,0860	0,0137	0,0585	1,046 m		ground	max. 15 °C
425	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,294 m		ground	max. 15 °C
426	NiTi	2,185	0,350	1,485	0,0860	0,0138	0,0585	3,070 m		ground	max. 15 °C
427	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	37,318 m		ground out-/oxidic inside	max. 15 °C
428	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	57,200 m		ground out-/oxidic inside	max. 15 °C
429	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	max. 15 °C
430	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	10,610 m		ground	max. 15 °C
431	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	25,542 m		ground	max. 15 °C
432	NiTi	2,200	0,270	1,660	0,0866	0,0106	0,0654	42,972 m		ground	max. 15 °C
433	NiTi	2,200	0,325	1,550	0,0866	0,0128	0,0610	2,040 m		ground	max. 15 °C
434	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	max. 15 °C
435	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	42,745 m		ground	max. 15 °C
436	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,081 m		ground	max. 15 °C
437	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,936 m		ground	max. 15 °C
438	NiTi	2,286	0,254	1,778	0,0900	0,0100	0,0700	5,700 m		ground	max. 15 °C
439	NiTi	2,300	0,150	2,000	0,0906	0,0059	0,0787	57,130 m		ground	max. 15 °C
440	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	max. 15 °C
441	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	3,794 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	4,246 m		ground	max. 15 °C
443	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	max. 15 °C
444	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	max. 15 °C
445	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	max. 15 °C
446	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	max. 15 °C
447	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	max. 15 °C
448	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,800 m		ground out-/oxidic inside	max. 15 °C
449	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	max. 15 °C
450	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	
451	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	3,010 m		ground	
452	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	43,543 m		ground	max. 15 °C
453	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	13,710 m		ground	max. 15 °C
454	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	13,960 m		ground	
455	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	max. 15 °C
456	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	33,572 m		ground	max. 15 °C
457	NiTi	2,400	0,085	2,230	0,0945	0,0033	0,0878	6,193 m		ground	max. 15 °C
458	NiTi	2,400	0,090	2,220	0,0945	0,0035	0,0874	6,898 m		ground	max. 15 °C
459	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	35,613 m		dark oxidized	max. 15 °C
460	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	12,867 m		ground	max. 15 °C
461	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	11,630 m		ground	
462	NiTi	2,413	0,229	1,956	0,0950	0,0090	0,0770	7,460 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	22,067 m		ground	max. 15 °C
464	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	1,760 m		dark oxidized	
465	NiTi	2,449	0,221	2,007	0,0964	0,0087	0,0790	18,443 m		ground	max. 15 °C
466	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	10,987 m		ground	max. 15 °C
467	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	8,106 m		ground	max. 15 °C
468	NiTi	2,480	0,225	2,030	0,0976	0,0089	0,0799	4,533 m		ground	max. 15 °C
469	NiTi	2,490	0,050	2,390	0,0980	0,0020	0,0941	2,080 m		ground	max. 15 °C
470	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	20,344 m		ground	max. 15 °C
471	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	3,920 m		ground	max. 15 °C
472	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	30,615 m		ground	max. 15 °C
473	NiTi	2,500	0,127	2,246	0,0984	0,0050	0,0884	6,653 m		ground	max. 15 °C
474	NiTi	2,500	0,250	2,000	0,0984	0,0098	0,0787	3,445 m		ground	max. 15 °C
475	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	10,510 m		ground out-/oxidic inside	max. 15 °C
476	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	13,249 m		ground	max. 15 °C
477	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	3,914 m		ground	max. 15 °C
478	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,577 m		ground	max. 15 °C
479	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m		ground	max. 15 °C
480	NiTi	2,590	0,076	2,438	0,1020	0,0030	0,0960	2,188 m		ground	max. 15 °C
481	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	17,785 m		ground	max. 15 °C
482	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	22,439 m		ground out-/oxidic inside	max. 15 °C
483	NiTi	2,604	0,216	2,172	0,1025	0,0085	0,0855	2,818 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	102,958 m		ground	max. 15 °C
485	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	41,055 m		ground	max. 15 °C
486	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,811 m		ground	max. 15 °C
487	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	83,723 m		ground	max. 15 °C
488	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,617 m		ground	max. 15 °C
489	NiTi	2,654	0,102	2,450	0,1045	0,0040	0,0965	10,114 m		ground	max. 15 °C
490	NiTi	2,667	0,241	2,185	0,1050	0,0095	0,0860	5,060 m		ground	max. 15 °C
491	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	4,405 m		ground	max. 15 °C
492	NiTi	2,680	0,115	2,450	0,1055	0,0045	0,0965	13,550 m		dark oxidized	max. 15 °C
493	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022 m		ground	max. 15 °C
494	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,177 m		ground	max. 15 °C
495	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	13,414 m		ground	max. 15 °C
496	NiTi	2,720	0,170	2,380	0,1071	0,0067	0,0937	3,175 m		ground	max. 15 °C
497	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	12,963 m		ground	max. 15 °C
498	NiTi	2,751	0,302	2,147	0,1083	0,0119	0,0845	42,540 m		ground	max. 15 °C
499	NiTi	2,760	0,190	2,380	0,1087	0,0075	0,0937	4,993 m		ground	max. 15 °C
500	NiTi	2,770	0,065	2,640	0,1091	0,0026	0,1039	2,635 m		ground	max. 15 °C
501	NiTi	2,800	0,230	2,340	0,1102	0,0091	0,0921	7,230 m		ground	max. 15 °C
502	NiTi	2,800	0,380	2,040	0,1102	0,0150	0,0803	28,404 m		ground	max. 15 °C
503	NiTi	2,800	0,380	2,040	0,1102	0,0150	0,0803	38,263 m		ground	max. 15 °C
504	NiTi	2,800	0,500	1,800	0,1102	0,0197	0,0709	13,866 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	NiTi	2,800	0,500	1,800	0,1102	0,0197	0,0709	3,998 m		ground out-/oxidic inside	15 °C
506	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	16,129 m		ground	max. 15 °C
507	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	17,847 m		ground out-/oxidic inside	max. 15 °C
508	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	19,462 m		ground out-/oxidic inside	max. 15 °C
509	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	21,873 m		ground out-/oxidic inside	max. 15 °C
510	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	6,082 m		ground out-/oxidic inside	max. 15 °C
511	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	85,326 m		ground out-/oxidic inside	max. 15 °C
512	NiTi	2,906	0,191	2,524	0,1144	0,0075	0,0994	22,430 m		ground	max. 15 °C
513	NiTi	2,980	0,208	2,564	0,1173	0,0082	0,1009	14,173 m		ground	max. 15 °C
514	NiTi	3,000	0,070	2,860	0,1181	0,0028	0,1126	12,510 m		ground	max. 15 °C
515	NiTi	3,030	0,233	2,564	0,1193	0,0092	0,1009	6,086 m		ground	max. 15 °C
516	NiTi	3,048	0,254	2,540	0,1200	0,0100	0,1000	9,000 m	St	ground	max. 15 °C
517	NiTi	3,063	0,262	2,539	0,1206	0,0103	0,1000	5,630 m		ground	
518	NiTi	3,160	0,170	2,820	0,1244	0,0067	0,1110	9,239 m		ground	max. 15 °C
519	NiTi	3,200	0,165	2,870	0,1260	0,0065	0,1130	2,042 m		ground	max. 15 °C
520	NiTi	3,200	0,190	2,820	0,1260	0,0075	0,1110	2,000 m	St	ground	max. 15 °C
521	NiTi	3,200	0,540	2,120	0,1260	0,0213	0,0835	7,690 m		ground	max. 15 °C
522	NiTi	3,200	0,540	2,120	0,1260	0,0213	0,0835	8,597 m		ground	max. 15 °C
523	NiTi	3,260	0,140	2,980	0,1283	0,0055	0,1173	1,257 m		ground	max. 15 °C
524	NiTi	3,260	0,140	2,980	0,1283	0,0055	0,1173	1,464 m		ground	max. 15 °C
525	NiTi	3,280	0,115	3,050	0,1291	0,0045	0,1201	5,050 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
526	NiTi	3,302	0,711	1,880	0,1300	0,0280	0,0740	13,357 m		ground	max. 15 °C
527	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,471 m		ground out-/oxidic inside	max. 15 °C
528	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,757 m		ground out-/oxidic inside	max. 15 °C
529	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	53,865 m		ground	max. 15 °C
530	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,471 m		ground	max. 15 °C
531	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	3,666 m		ground out-/oxidic inside	max. 15 °C
532	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	7,000 m	St	ground	max. 15 °C
533	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	7,872 m		ground	max. 15 °C
534	NiTi	3,500	0,075	3,350	0,1378	0,0030	0,1319	15,571 m		ground	max. 15 °C
535	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	13,198 m		ground	max. 15 °C
536	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	13,147 m		ground	max. 15 °C
537	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610 m		ground	max. 15 °C
538	NiTi	3,500	0,170	3,160	0,1378	0,0067	0,1244	1,425 m		dark oxidized	max. 15 °C
539	NiTi	3,500	0,170	3,160	0,1378	0,0067	0,1244	3,915 m		ground	max. 15 °C
540	NiTi	3,500	0,190	3,120	0,1378	0,0075	0,1228	21,447 m		ground	max. 15 °C
541	NiTi	3,500	0,320	2,860	0,1378	0,0126	0,1126	1,494 m		ground	max. 15 °C
542	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	5,520 m		ground	max. 15 °C
543	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	10,190 m		ground	max. 15 °C
544	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	11,588 m		ground	max. 15 °C
545	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	6,999 m		ground	max. 15 °C
546	NiTi	3,610	0,250	3,110	0,1421	0,0098	0,1224	4,542 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
547	NiTi	3,800	0,100	3,600	0,1496	0,0039	0,1417	3,027 m		ground	max. 15 °C
548	NiTi	3,800	0,265	3,270	0,1496	0,0104	0,1287	4,516 m		ground	
549	NiTi	3,810	0,120	3,570	0,1500	0,0047	0,1406	4,565 m		ground	max. 15 °C
550	NiTi	3,900	0,260	3,380	0,1535	0,0102	0,1331	7,000 m		ground	max. 15 °C
551	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	110,766 m		ground	max. 15 °C
552	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	119,084 m		ground	max. 15 °C
553	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	23,177 m		ground	max. 15 °C
554	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	4,613 m		ground	max. 15 °C
555	NiTi	4,000	0,100	3,800	0,1575	0,0039	0,1496	5,220 m		ground	max. 15 °C
556	NiTi	4,000	0,100	3,800	0,1575	0,0039	0,1496	95,793 m		ground	max. 15 °C
557	NiTi	4,000	0,102	3,796	0,1575	0,0040	0,1494	7,452 m		ground	max. 15 °C
558	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	21,222 m		ground	max. 15 °C
559	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	3,660 m		ground	max. 15 °C
560	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	4,000 m		ground	max. 15 °C
561	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	19,533 m		ground	
562	NiTi	4,242	0,152	3,938	0,1670	0,0060	0,1550	9,208 m		ground	max. 15 °C
563	NiTi	4,270	0,079	4,112	0,1681	0,0031	0,1619	4,942 m		ground	max. 15 °C
564	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	2,653 m		ground	
565	NiTi	4,500	0,080	4,340	0,1772	0,0031	0,1709	0,744 m		ground	max. 15 °C
566	NiTi	4,500	0,127	4,246	0,1772	0,0050	0,1672	2,264 m		ground	max. 15 °C
567	NiTi	4,500	0,700	3,100	0,1772	0,0276	0,1220	7,780 m		ground	max. 15 °C

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
568	NiTi	4,700	0,150	4,400	0,1850	0,0059	0,1732	28,451 m		ground	max. 15 °C
569	NiTi	4,750	0,125	4,500	0,1870	0,0049	0,1772	7,390 m		ground	max. 15 °C
570	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,597 m		ground	max. 15 °C
571	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	2,905 m		ground	max. 15 °C
572	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	2,707 m		ground	max. 15 °C
573	NiTi	4,900	0,200	4,500	0,1929	0,0079	0,1772	37,806 m		ground	max. 15 °C
574	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	5,320 m		polished	max. 15 °C
575	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	max. 15 °C
576	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,306 m		ground	max. 15 °C
577	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,876 m		ground	max. 15 °C
578	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	max. 15 °C
579	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	max. 15 °C
580	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	max. 15 °C
581	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	max. 15 °C
582	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	max. 15 °C
583	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,030 m		ground out-/oxidic inside	max. 15 °C
584	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	max. 15 °C
585	NiTi	4,980	0,280	4,420	0,1961	0,0110	0,1740	3,032 m		ground	max. 15 °C
586	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	2,510 m		ground	max. 15 °C
587	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	8,708 m		ground	max. 15 °C
588	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	9,631 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
589	NiTi	5,000	0,250	4,500	0,1969	0,0098	0,1772	5,870 m		ground	
590	NiTi	5,000	0,400	4,200	0,1969	0,0157	0,1654	3,333 m		ground	max. 15 °C
591	NiTi	5,004	0,533	3,938	0,1970	0,0210	0,1550	4,518 m		ground out-/oxidic inside	max. 15 °C
592	NiTi	5,004	0,546	3,912	0,1970	0,0215	0,1540	23,848 m		ground	max. 15 °C
593	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	max. 15 °C
594	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434 m		ground	max. 15 °C
595	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	16,545 m		ground	max. 15 °C
596	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	35,820 m		ground	max. 15 °C
597	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	25,000 m		ground	max. 15 °C
598	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	3,189 m		ground	max. 15 °C
599	NiTi	5,207	0,279	4,649	0,2050	0,0110	0,1830	1,400 m		ground	max. 15 °C
600	NiTi	5,410	0,483	4,444	0,2130	0,0190	0,1750	3,010 m		ground	max. 15 °C
601	NiTi	5,500	0,065	5,370	0,2165	0,0026	0,2114	0,723 m		polished	max. 15 °C
602	NiTi	5,500	0,100	5,300	0,2165	0,0039	0,2087	3,479 m		ground	max. 15 °C
603	NiTi	5,538	0,203	5,131	0,2180	0,0080	0,2020	3,490 m		ground	max. 15 °C
604	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	3,520 m		ground	max. 15 °C
605	NiTi	5,893	0,546	4,801	0,2320	0,0215	0,1890	6,471 m		ground	max. 15 °C
606	NiTi	5,944	0,572	4,800	0,2340	0,0225	0,1890	1,250 m		ground out-/oxidic inside	max. 15 °C
607	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,110 m		ground out-/oxidic inside	max. 15 °C
608	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	14,190 m		ground out-/oxidic inside	max. 15 °C
609	NiTi	5,994	0,254	5,486	0,2360	0,0100	0,2160	4,450 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
610	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,525 m		ground	max. 15 °C
611	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	7,512 m		ground	max. 15 °C
612	NiTi	6,000	0,064	5,872	0,2362	0,0025	0,2312	4,910 m		ground	max. 15 °C
613	NiTi	6,000	0,400	5,200	0,2362	0,0157	0,2047	3,215 m		ground	max. 15 °C
614	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	1,840 m		ground	max. 15 °C
615	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	15,390 m		ground	max. 15 °C
616	NiTi	6,150	0,100	5,950	0,2421	0,0039	0,2343	7,196 m		ground	max. 15 °C
617	NiTi	6,200	0,150	5,900	0,2441	0,0059	0,2323	1,386 m		ground	max. 15 °C
618	NiTi	6,200	0,150	5,900	0,2441	0,0059	0,2323	12,837 m		ground	max. 15 °C
619	NiTi	6,700	0,250	6,200	0,2638	0,0098	0,2441	4,936 m		ground	max. 15 °C
620	NiTi	6,820	0,160	6,500	0,2685	0,0063	0,2559	5,515 m		ground	max. 15 °C
621	NiTi	6,830	0,245	6,340	0,2689	0,0096	0,2496	11,020 m		ground	max. 15 °C
622	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	6,967 m		ground	max. 15 °C
623	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	1,800 m		ground	max. 15 °C
624	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	1,967 m		ground	max. 15 °C
625	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	2,399 m		ground	max. 15 °C
626	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	3,772 m		ground	max. 15 °C
627	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	5,167 m		ground out-/oxidic inside	max. 15 °C
628	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	7,472 m		ground	max. 15 °C
629	NiTi	7,000	0,508	5,984	0,2756	0,0200	0,2356	3,885 m		ground	max. 15 °C
630	NiTi	7,000	0,533	5,934	0,2756	0,0210	0,2336	5,412 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
631	NiTi	7,150	0,100	6,950	0,2815	0,0039	0,2736	11,141 m		ground	max. 15 °C
632	NiTi	7,350	0,310	6,730	0,2894	0,0122	0,2650	2,460 m		ground	max. 15 °C
633	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	5,777 m		ground	max. 15 °C
634	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	0,710 m		ground	
635	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	1,520 m			
636	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	18,020 m		ground	
637	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,130 m		ground	
638	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,570 m		ground	
639	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	16,660 m		ground	
640	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	4,550 m		ground	
641	NiTi	8,000	0,720	6,560	0,3150	0,0283	0,2583	1,186 m		ground	max. 15 °C
642	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,645 m		ground	max. 15 °C
643	NiTi	8,300	0,310	7,680	0,3268	0,0122	0,3024	4,460 m		ground	max. 15 °C
644	NiTi	8,800	0,550	7,700	0,3465	0,0217	0,3031	1,297 m		ground	max. 15 °C
645	NiTi	9,000	0,400	8,200	0,3543	0,0157	0,3228	4,000 m	St	ground	max. 15 °C
646	NiTi	10,000	0,200	9,600	0,3937	0,0079	0,3780	3,220 m		ground	max. 15 °C
647	NiTi	10,000	0,250	9,500	0,3937	0,0098	0,3740	1,080 m		ground	max. 15 °C
648	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	20,069 m		ground	max. 15 °C
649	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	3,470 m		ground	max. 15 °C
650	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	4,220 m		ground	max. 15 °C
651	NiTi	10,000	0,480	9,040	0,3937	0,0189	0,3559	14,031 m		ground	max. 15 °C

Stock list - Tubes

current status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
652	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	9,166 m		ground	max. 15 °C
653	NiTi	10,000	0,625	8,750	0,3937	0,0246	0,3445	7,149 m		ground	max. 15 °C
654	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	3,410 m		ground	
655	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	6,591 m		ground	max. 15 °C
656	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	8,806 m		ground	
657	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034 m			
658	section	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
659	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	3,053 m			
660	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	5,067 m			
661	Tantal/Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162 m			
662	Tantalum	1,600	0,200	1,200	0,0630	0,0079	0,0472	0,951 m		polished	
663	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210 m		ground	
664	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480 m		ground	
665	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310 m			
666	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	661,087 m			
667	Titan Gr. 2	1,250	0,100	1,050	0,0492	0,0039	0,0413	62,150 m		ground	
668	Titan Gr. 2	1,650	0,150	1,350	0,0650	0,0059	0,0531	80,674 m			
669	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,806 m			
670	Titan Gr. 2	2,350	0,500	1,350	0,0925	0,0197	0,0531	2,800 m			
671	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490 m			
672	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670 m			

Stock list - Tubescurrent status: **07.01.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
673	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
674	Titan Gr. 2	5,000	0,550	3,900	0,1969	0,0217	0,1535	8,761	m		
675	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
676	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		
677	Titan Gr. 2	7,925	0,889	6,147	0,3120	0,0350	0,2420	6,679	m		
678	Titan Gr. 2	10,000	4,450	1,100	0,3937	0,1752	0,0433	24,000	St		
679	Titan Gr. 2	10,000	4,450	1,100	0,3937	0,1752	0,0433	24,000	St		