

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
2	1.4301 (304)	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
3	1.4301 (304)	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
4	1.4301 (304)	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
5	1.4301 (304)	6,700	0,500	5,700	0,2638	0,0197	0,2244	11,650	m		
6	1.4301 (304)	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
7	1.4301 (304)	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
8	1.4307	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
9	1.4452 (P 2000)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
10	1.4452 (P 2000)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
11	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
12	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	30,775	m		
13	1.4452 (P 2000)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
14	1.4541	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
15	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	14,722	m		
16	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	24,000	m		
17	1.4568	0,690	0,125	0,440	0,0272	0,0049	0,0173	7,854	m		
18	1.4568	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
19	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
20	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
21	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	23,560	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	1.4568	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
23	1.4568	9,647	0,342	8,963	0,3798	0,0135	0,3529	9,570	m		
24	1.4568	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
25	1.4568	10,313	0,342	9,629	0,4060	0,0135	0,3791	3,202	m		
26	1.4571	5,600	0,150	5,300	0,2205	0,0059	0,2087	278,000	St		
27	1.4571	5,950	0,150	5,700	0,2343	0,0059	0,2244	222,000	St		
28	1.4571	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
29	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	33,244	m		
30	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	185,000	m		
31	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
32	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
33	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	8,621	m		
34	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
35	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
36	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	359,805	m		
37	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	108,816	m		
38	316LVM	0,450	0,100	0,250	0,0177	0,0039	0,0098	57,644	m		
39	316LVM	0,518	0,099	0,320	0,0204	0,0039	0,0126	186,374	m		
40	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	6,000	m		
41	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	26,093	m		
42	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	14,644	m		

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	42,246	m		
44	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	35,800	m		
45	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	38,024	m		
46	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	45,981	m		
47	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	72,562	m		
48	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	13,188	m		
49	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
50	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	62,256	m		
51	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	67,374	m		
52	316LVM	1,400	0,130	1,140	0,0551	0,0051	0,0449	37,369	m		
53	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
54	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
55	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
56	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	2,986	m		
57	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
58	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		
59	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	13,058	m		
60	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	9,943	m		
61	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	12,556	m		
62	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
63	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	39,185	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	19,953	m		
65	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
66	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	59,721	m		
67	316LVM	3,200	0,200	2,800	0,1260	0,0079	0,1102	47,209	m		
68	316LVM	3,230	0,115	3,000	0,1272	0,0045	0,1181	8,248	m		
69	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
70	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	39,148	m		
71	316LVM	4,000	0,090	3,820	0,1575	0,0035	0,1504	8,373	m		
72	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
73	316LVM	4,572	0,229	4,114	0,1800	0,0090	0,1620	63,638	m		
74	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
75	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
76	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	19,984	m		
77	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	35,822	m		
78	316LVM	5,000	0,250	4,500	0,1969	0,0098	0,1772	7,199	m		
79	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
80	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
81	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	19,306	m		
82	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
83	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	18,200	m		
84	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
86	316LVM	6,350	2,197	1,956	0,2500	0,0865	0,0770	1,596	m		
87	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	7,287	m		
88	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		
89	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
90	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	5,251	m		
91	316LVM	8,960	0,425	8,110	0,3528	0,0167	0,3193	30,605	m		
92	Biodur 108	1,220	0,075	1,070	0,0480	0,0030	0,0421	7,542	m		
93	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	46,797	m		
94	KC35N LT	0,356	0,102	0,152	0,0140	0,0040	0,0060	27,000	St		
95	KC35N LT	0,368	0,083	0,203	0,0145	0,0033	0,0080	29,000	St		
96	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	13,137	m		
97	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	2,100	m		
98	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2290,000	St		
99	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	915,000	St		
100	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	47,100	m		
101	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	5,666	m		
102	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		
103	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		
104	KC35N LT	1,240	0,070	1,100	0,0488	0,0028	0,0433	19,985	m		
105	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
107	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
108	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
109	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	0,836	m		
110	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
111	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		
112	KC35N LT	2,350	0,150	2,050	0,0925	0,0059	0,0807	22,407	m		
113	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
114	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
115	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		
116	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
117	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	50,256	m		
118	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	9,819	m		
119	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
120	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		
121	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
122	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	32,325	m		
123	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
124	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
125	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
126	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	11,154	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	L605	0,762	0,127	0,508	0,0300	0,0050	0,0200	37,452	m		
128	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,451	m		
129	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
130	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	35,338	m		
131	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
132	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
133	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	120,328	m		
134	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	6,131	m		
135	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	7,686	m		
136	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
137	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		
138	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
139	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
140	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
141	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
142	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
143	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
144	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
145	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		
146	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	261,700	m		
147	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	24,460	m		

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
149	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,504	m		
150	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
151	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
152	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	161,399	m		
153	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
154	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
155	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	64,623	m		
156	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		
157	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		
158	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
159	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
160	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
161	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
162	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,423	m		
163	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
164	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		
165	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
166	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
167	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
168	L605	1,800	0,104	1,592	0,0709	0,0041	0,0627	109,681	m		



**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	107,761	m		
170	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	18,580	m		
171	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	35,192	m		
172	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	431,611	m		
173	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	531,472	m		
174	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	560,000	m		
175	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
176	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	8,711	m		
177	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	9,500	m		
178	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	30,503	m		
179	L605	2,000	0,110	1,780	0,0787	0,0043	0,0701	44,013	m		
180	L605	2,200	0,120	1,960	0,0866	0,0047	0,0772	10,230	m		
181	L605	3,000	0,160	2,680	0,1181	0,0063	0,1055	14,842	m		
182	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	9,629	m		
183	L605	3,500	0,200	3,100	0,1378	0,0079	0,1220	16,353	m		
184	L605	3,800	0,150	3,500	0,1496	0,0059	0,1378	85,315	m		
185	L605	3,850	0,170	3,510	0,1516	0,0067	0,1382	8,721	m		
186	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
187	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
188	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	2,296	m		
189	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	90,001	m		

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	4,400	0,320	3,760	0,1732	0,0126	0,1480	34,116	m		
191	L605	4,550	0,180	4,190	0,1791	0,0071	0,1650	3,919	m		
192	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
193	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	1,530	m		
194	L605	6,000	0,200	5,600	0,2362	0,0079	0,2205	4,011	m		
195	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
196	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
197	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	20,000	m		
198	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
199	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
200	NiTi	0,254	0,051	0,152	0,0100	0,0020	0,0060	12,208	m	ground	Max. 15 °C
201	NiTi	0,310	0,045	0,220	0,0122	0,0018	0,0087	12,171	m	dark oxidized	Max. 15 °C
202	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	7,602	m	ground	Max. 15 °C
203	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	Max. 15 °C
204	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	52,000	m	ground	Max. 15 °C
205	NiTi	0,400	0,100	0,200	0,0157	0,0039	0,0079	31,571	m	ground	Max. 15 °C
206	NiTi	0,400	0,120	0,160	0,0157	0,0047	0,0063	7,090	m	ground	Max. 15 °C
207	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	46,115	m	ground	Max. 15 °C
208	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	7,671	m	ground	Max. 15 °C
209	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	9,144	m	polished	Max. 15 °C
210	NiTi	0,480	0,080	0,320	0,0189	0,0031	0,0126	77,036	m		Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	634,805 m		dark oxidized	Max. 15 °C
212	NiTi	0,570	0,090	0,390	0,0224	0,0035	0,0154	106,876 m		dark oxidized	Max. 15 °C
213	NiTi	0,570	0,100	0,370	0,0224	0,0039	0,0146	33,132 m		ground	Max. 15 °C
214	NiTi	0,580	0,115	0,350	0,0228	0,0045	0,0138	105,911 m		ground	Max. 15 °C
215	NiTi	0,640	0,120	0,400	0,0252	0,0047	0,0157	94,920 m		ground	Max. 15 °C
216	NiTi	0,730	0,100	0,530	0,0287	0,0039	0,0209	49,742 m		ground	Max. 15 °C
217	NiTi	0,856	0,043	0,770	0,0337	0,0017	0,0303	3,000 St		ground	Max. 15 °C
218	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	615,200 m		dark oxidized	Max. 15 °C
219	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	146,547 m		ground	Max. 15 °C
220	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	15,439 m		ground	Max. 15 °C
221	NiTi	1,200	0,060	1,080	0,0472	0,0024	0,0425	2,348 m		ground	Max. 15 °C
222	NiTi	1,200	0,085	1,030	0,0472	0,0033	0,0406	49,168 m		ground	Max. 15 °C
223	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	235,084 m		ground	Max. 15 °C
224	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	2,379 m		ground	Max. 15 °C
225	NiTi	1,257	0,149	0,959	0,0495	0,0059	0,0378	343,228 m		ground	Max. 15 °C
226	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	28,076 m		ground	Max. 15 °C
227	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716 m		ground	Max. 15 °C
228	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,444 m		ground	Max. 15 °C
229	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	16,443 m		ground	Max. 15 °C
230	NiTi	1,300	0,220	0,860	0,0512	0,0087	0,0339	83,395 m		ground	Max. 15 °C
231	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,146 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	Max. 15 °C
233	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m		ground out-/oxidic inside	Max. 15 °C
234	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	21,797 m		ground out-/oxidic inside	Max. 15 °C
235	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	Max. 15 °C
236	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	1,690 m		ground	Max. 15 °C
237	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,168 m		ground	Max. 15 °C
238	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m		ground	Max. 15 °C
239	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,257 m		ground	Max. 15 °C
240	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,329 m		ground	Max. 15 °C
241	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	Max. 15 °C
242	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	Max. 15 °C
243	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	173,217 m		ground	Max. 15 °C
244	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	Max. 15 °C
245	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	Max. 15 °C
246	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,341 m		ground	Max. 15 °C
247	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	Max. 15 °C
248	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	Max. 15 °C
249	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	Max. 15 °C
250	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	Max. 15 °C
251	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,824 m		ground	Max. 15 °C
252	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	39,443 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	Max. 15 °C
254	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	Max. 15 °C
255	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,300 m		ground	Max. 15 °C
256	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	2,709 m		ground	Max. 15 °C
257	NiTi	1,350	0,150	1,050	0,0531	0,0059	0,0413	10,794 m		ground	Max. 15 °C
258	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	10,634 m		ground	Max. 15 °C
259	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	13,197 m		ground	Max. 15 °C
260	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	34,776 m		ground	Max. 15 °C
261	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	7,858 m		ground	Max. 15 °C
262	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	2,989 m		ground	Max. 15 °C
263	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	3,701 m		ground	Max. 15 °C
264	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	4,382 m		ground	Max. 15 °C
265	NiTi	1,550	0,150	1,250	0,0610	0,0059	0,0492	7,122 m		ground	Max. 15 °C
266	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	43,059 m		ground out-/oxidic inside	Max. 15 °C
267	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080 m		ground out-/oxidic inside	Max. 15 °C
268	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	14,007 m		ground	Max. 15 °C
269	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,447 m		ground out-/oxidic inside	Max. 15 °C
270	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	44,811 m		ground	Max. 15 °C
271	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	22,231 m		ground	Max. 15 °C
272	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,077 m		ground	Max. 15 °C
273	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	64,301 m		ground	Max. 15 °C

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	8,598 m		ground	Max. 15 °C
275	NiTi	1,600	0,340	0,920	0,0630	0,0134	0,0362	12,286 m		ground	Max. 15 °C
276	NiTi	1,600	0,474	0,653	0,0630	0,0187	0,0257	5,000	St	ground	Max. 15 °C
277	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	1,312	m	ground	Max. 15 °C
278	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	Max. 15 °C
279	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	10,817	m	ground out-/oxidic inside	Max. 15 °C
280	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737	m	ground out-/oxidic inside	Max. 15 °C
281	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970	m	ground out-/oxidic inside	Max. 15 °C
282	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820	m	ground out-/oxidic inside	Max. 15 °C
283	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,092	m	polished	Max. 15 °C
284	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	3,427	m	ground	Max. 15 °C
285	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609	m	ground	Max. 15 °C
286	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,745	m	ground	Max. 15 °C
287	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,316	m	ground	Max. 15 °C
288	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279	m	ground	Max. 15 °C
289	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	21,363	m	ground	Max. 15 °C
290	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	3,671	m	ground	Max. 15 °C
291	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430	m	ground	Max. 15 °C
292	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000	m	ground	Max. 15 °C
293	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,074	m	dark oxidized	Max. 15 °C
294	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390	m	ground	Max. 15 °C

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	Max. 15 °C
296	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	Max. 15 °C
297	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	Max. 15 °C
298	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,920 m		ground	Max. 15 °C
299	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	86,681 m		ground	Max. 15 °C
300	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	Max. 15 °C
301	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	Max. 15 °C
302	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	Max. 15 °C
303	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	Max. 15 °C
304	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	Max. 15 °C
305	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	Max. 15 °C
306	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,054 m		ground	Max. 15 °C
307	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	Max. 15 °C
308	NiTi	1,670	0,100	1,470	0,0657	0,0039	0,0579	10,963 m		ground	Max. 15 °C
309	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	204,474 m		ground out-/oxidic inside	Max. 15 °C
310	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	287,701 m		ground out-/oxidic inside	Max. 15 °C
311	NiTi	1,700	0,250	1,200	0,0669	0,0098	0,0472	143,649 m		ground	Max. 15 °C
312	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	67,823 m		ground	Max. 15 °C
313	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	35,912 m		ground	Max. 15 °C
314	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	Max. 15 °C
315	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	258,962 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m		ground	Max. 15 °C
317	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	Max. 15 °C
318	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	Max. 15 °C
319	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,379 m		ground	Max. 15 °C
320	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m		ground	Max. 15 °C
321	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	Max. 15 °C
322	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	Max. 15 °C
323	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	Max. 15 °C
324	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,766 m		ground	Max. 15 °C
325	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	Max. 15 °C
326	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	81,630 m		ground	Max. 15 °C
327	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,150 m		ground	Max. 15 °C
328	NiTi	1,800	0,060	1,680	0,0709	0,0024	0,0661	3,428 m		ground	Max. 15 °C
329	NiTi	1,800	0,060	1,680	0,0709	0,0024	0,0661	5,293 m		ground	Max. 15 °C
330	NiTi	1,800	0,070	1,660	0,0709	0,0028	0,0654	16,883 m		ground	Max. 15 °C
331	NiTi	1,800	0,075	1,650	0,0709	0,0030	0,0650	21,369 m		ground	Max. 15 °C
332	NiTi	1,800	0,080	1,640	0,0709	0,0031	0,0646	6,594 m		ground	Max. 15 °C
333	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	Max. 15 °C
334	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	10,460 m		ground	Max. 15 °C
335	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	14,726 m		ground	Max. 15 °C
336	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	21,683 m		ground	Max. 15 °C



## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	9,111 m		ground	Max. 15 °C
338	NiTi	1,850	0,240	1,370	0,0728	0,0094	0,0539	2,446 m		ground	Max. 15 °C
339	NiTi	1,900	0,370	1,160	0,0748	0,0146	0,0457	3,832 m		ground	Max. 15 °C
340	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	11,009 m		ground	Max. 15 °C
341	NiTi	1,921	0,203	1,515	0,0756	0,0080	0,0596	96,643 m		ground	Max. 15 °C
342	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	240,564 m		ground	Max. 15 °C
343	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	68,415 m		ground	Max. 15 °C
344	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990 m		ground	Max. 15 °C
345	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	27,510 m		ground	Max. 15 °C
346	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m		ground	Max. 15 °C
347	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	18,599 m		ground	Max. 15 °C
348	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	36,134 m		ground	Max. 15 °C
349	NiTi	2,000	0,330	1,340	0,0787	0,0130	0,0528	5,061 m		ground	Max. 15 °C
350	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	1,383 m		ground	Max. 15 °C
351	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847 m		ground	Max. 15 °C
352	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	12,985 m		ground out-/oxidic inside	Max. 15 °C
353	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	11,128 m		ground	Max. 15 °C
354	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	28,537 m		ground	Max. 15 °C
355	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	4,626 m		ground	Max. 15 °C
356	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	6,506 m		ground	Max. 15 °C
357	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	1,908 m		ground	Max. 15 °C

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	25,753 m		ground	Max. 15 °C
359	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	330,416 m		ground	Max. 15 °C
360	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	21,907 m		ground	Max. 15 °C
361	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	8,283 m		ground	Max. 15 °C
362	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,386 m		ground	Max. 15 °C
363	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	22,967 m		ground out-/oxidic inside	Max. 15 °C
364	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	40,443 m		ground out-/oxidic inside	Max. 15 °C
365	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	Max. 15 °C
366	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	24,268 m		ground	Max. 15 °C
367	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	6,356 m		ground	Max. 15 °C
368	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	Max. 15 °C
369	NiTi	2,250	0,320	1,610	0,0886	0,0126	0,0634	4,360 m		ground	Max. 15 °C
370	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	1,361 m		ground	Max. 15 °C
371	NiTi	2,300	0,150	2,000	0,0906	0,0059	0,0787	2,238 m		ground	Max. 15 °C
372	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	Max. 15 °C
373	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,432 m		ground	Max. 15 °C
374	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,624 m		ground	Max. 15 °C
375	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	Max. 15 °C
376	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	15,466 m		ground	Max. 15 °C
377	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	Max. 15 °C
378	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	Max. 15 °C

## Stock list - Tubes

current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	Max. 15 °C
380	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	Max. 15 °C
381	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,768 m		ground out-/oxidic inside	Max. 15 °C
382	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	Max. 15 °C
383	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	Max. 15 °C
384	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	29,031 m		ground	Max. 15 °C
385	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	40,566 m		ground	Max. 15 °C
386	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	8,866 m		ground	Max. 15 °C
387	NiTi	2,362	0,076	2,210	0,0930	0,0030	0,0870	55,707 m		ground	Max. 15 °C
388	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	8,280 m		ground	Max. 15 °C
389	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	Max. 15 °C
390	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	8,136 m		ground	Max. 15 °C
391	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	34,124 m		dark oxidized	Max. 15 °C
392	NiTi	2,400	0,300	1,800	0,0945	0,0118	0,0709	8,173 m		ground	Max. 15 °C
393	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	11,313 m		ground	Max. 15 °C
394	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	21,039 m		ground	Max. 15 °C
395	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	1,819 m		dark oxidized	Max. 15 °C
396	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	2,652 m		ground	Max. 15 °C
397	NiTi	2,500	0,127	2,246	0,0984	0,0050	0,0884	13,723 m		ground	Max. 15 °C
398	NiTi	2,500	0,550	1,400	0,0984	0,0217	0,0551	6,995 m			Max. 15 °C
399	NiTi	2,550	0,180	2,190	0,1004	0,0071	0,0862	8,096 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	2,976 m	ground	out-/oxidic inside	Max. 15 °C
401	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,501 m	ground		Max. 15 °C
402	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	7,459 m	ground		Max. 15 °C
403	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m	ground		Max. 15 °C
404	NiTi	2,600	0,510	1,580	0,1024	0,0201	0,0622	112,604 m	ground		Max. 15 °C
405	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	58,230 m	ground		Max. 15 °C
406	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	39,314 m	ground		Max. 15 °C
407	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,526 m	ground		Max. 15 °C
408	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	59,319 m	ground		Max. 15 °C
409	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,145 m	ground		Max. 15 °C
410	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	1,116 m	ground		Max. 15 °C
411	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022 m	ground		Max. 15 °C
412	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,114 m	ground		Max. 15 °C
413	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	1,143 m	ground		Max. 15 °C
414	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	3,594 m	ground		Max. 15 °C
415	NiTi	2,800	0,610	1,580	0,1102	0,0240	0,0622	12,989 m	ground		Max. 15 °C
416	NiTi	2,819	0,371	2,077	0,1110	0,0146	0,0818	7,000 m	St ground		Max. 15 °C
417	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	10,330 m	ground		Max. 15 °C
418	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	15,109 m	ground		Max. 15 °C
419	NiTi	2,832	0,386	2,060	0,1115	0,0152	0,0811	46,479 m	ground		max. 10 °C
420	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	10,448 m	ground		Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	3,000	0,150	2,700	0,1181	0,0059	0,1063	35,145 m		ground	Max. 15 °C
422	NiTi	3,150	0,203	2,744	0,1240	0,0080	0,1080	21,903 m		ground	Max. 15 °C
423	NiTi	3,200	0,540	2,120	0,1260	0,0213	0,0835	4,663 m		ground	Max. 15 °C
424	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,410 m		ground out-/oxidic inside	Max. 15 °C
425	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,863 m		ground out-/oxidic inside	Max. 15 °C
426	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	10,931 m		ground out-/oxidic inside	Max. 15 °C
427	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,955 m		ground	Max. 15 °C
428	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	48,544 m		ground	Max. 15 °C
429	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	6,001 m		ground	Max. 15 °C
430	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,057 m		ground	Max. 15 °C
431	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	2,797 m		ground	Max. 15 °C
432	NiTi	3,500	0,075	3,350	0,1378	0,0030	0,1319	13,285 m		ground	Max. 15 °C
433	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	9,569 m		ground	Max. 15 °C
434	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	22,275 m		ground	Max. 15 °C
435	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	8,819 m		ground	Max. 15 °C
436	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610 m		ground	Max. 15 °C
437	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	13,785 m		ground	Max. 15 °C
438	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	4,240 m		ground	Max. 15 °C
439	NiTi	3,505	0,280	2,945	0,1380	0,0110	0,1159	3,312 m		ground	Max. 15 °C
440	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	1,134 m		ground	Max. 15 °C
441	NiTi	3,600	0,200	3,200	0,1417	0,0079	0,1260	3,784 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	11,470 m		ground	Max. 15 °C
443	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	1,828 m		ground	Max. 15 °C
444	NiTi	4,250	0,065	4,120	0,1673	0,0026	0,1622	4,268 m		polished	Max. 15 °C
445	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	1,836 m		ground	Max. 15 °C
446	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,595 m		ground	Max. 15 °C
447	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	2,927 m		ground	Max. 15 °C
448	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	1,355 m		ground	Max. 15 °C
449	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	3,271 m		polished	Max. 15 °C
450	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	Max. 15 °C
451	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	143,098 m		ground	Max. 15 °C
452	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	29,886 m		ground out-/oxidic inside	Max. 15 °C
453	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	Max. 15 °C
454	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	Max. 15 °C
455	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,210 m		ground	Max. 15 °C
456	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	Max. 15 °C
457	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	54,498 m		ground out-/oxidic inside	Max. 15 °C
458	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	Max. 15 °C
459	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	Max. 15 °C
460	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	93,614 m		ground out-/oxidic inside	Max. 15 °C
461	NiTi	5,000	0,500	4,000	0,1969	0,0197	0,1575	3,607 m		ground	Max. 15 °C
462	NiTi	5,001	0,114	4,773	0,1969	0,0045	0,1879	2,381 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	Max. 15 °C
464	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434 m		ground	Max. 15 °C
465	NiTi	5,200	0,200	4,800	0,2047	0,0079	0,1890	15,625 m		ground	Max. 15 °C
466	NiTi	5,500	0,100	5,300	0,2165	0,0039	0,2087	2,737 m		ground	Max. 15 °C
467	NiTi	5,500	0,530	4,440	0,2165	0,0209	0,1748	16,895 m		ground	Max. 15 °C
468	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	67,878 m		ground	Max. 15 °C
469	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,087 m		ground out-/oxidic inside	Max. 15 °C
470	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	8,875 m		ground out-/oxidic inside	Max. 15 °C
471	NiTi	5,994	0,537	4,920	0,2360	0,0211	0,1937	6,102 m		ground	Max. 15 °C
472	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,492 m		ground	Max. 15 °C
473	NiTi	6,000	0,300	5,400	0,2362	0,0118	0,2126	4,631 m		ground	Max. 15 °C
474	NiTi	6,000	0,480	5,040	0,2362	0,0189	0,1984	16,304 m		ground	Max. 15 °C
475	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	11,061 m		ground	Max. 15 °C
476	NiTi	6,000	0,580	4,840	0,2362	0,0228	0,1906	12,201 m		ground	Max. 15 °C
477	NiTi	6,200	0,150	5,900	0,2441	0,0059	0,2323	27,882 m		ground	Max. 15 °C
478	NiTi	6,700	0,135	6,430	0,2638	0,0053	0,2531	18,215 m		ground	Max. 15 °C
479	NiTi	7,000	0,090	6,820	0,2756	0,0035	0,2685	32,785 m		ground	Max. 15 °C
480	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	4,539 m		ground	Max. 15 °C
481	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	1,557 m		ground	Max. 15 °C
482	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	5,564 m		ground	Max. 15 °C
483	NiTi	8,000	0,520	6,960	0,3150	0,0205	0,2740	12,911 m		ground	Max. 15 °C

**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)  
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)  
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)  
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,634 m		ground	Max. 15 °C
485	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	6,252 m		ground	Max. 15 °C
486	NiTi	8,800	0,450	7,900	0,3465	0,0177	0,3110	6,785 m		ground	Max. 15 °C
487	NiTi	9,900	0,625	8,650	0,3898	0,0246	0,3406	1,114 m		ground	Max. 15 °C
488	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	9,766 m		ground	Max. 15 °C
489	NiTi	10,000	0,450	9,100	0,3937	0,0177	0,3583	1,410 m		ground	Max. 15 °C
490	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	8,514 m		ground	Max. 15 °C
491	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	2,374 m		ground	Max. 15 °C
492	NiTi	10,000	0,600	8,800	0,3937	0,0236	0,3465	4,610 m		ground	Max. 15 °C
493	NiTi	10,000	0,720	8,560	0,3937	0,0283	0,3370	0,874 m		ground	Max. 15 °C
494	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	0,851 m		ground	Max. 15 °C
495	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	10,558 m		ground	Max. 15 °C
496	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	2,851 m		ground	Max. 15 °C
497	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	6,601 m		ground	Max. 15 °C
498	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	8,793 m		ground	Max. 15 °C
499	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034 m			
500	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	2,207 m			
501	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	3,897 m			
502	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	30,791 m			
503	Tantal	4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647 m			
504	Tantal	4,900	0,500	3,900	0,1929	0,0197	0,1535	1,538 m			



**Stock list - Tubes**current status: **14.01.2022**

To receive a quote, please contact  
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, [nicole.odenwald@euroflex.de](mailto:nicole.odenwald@euroflex.de))  
or Michaela Müller (Phone +49(0)7231.208.249, [michaela.mueller@euroflex.de](mailto:michaela.mueller@euroflex.de))  
or Valerie Stumpf (Phone +49(0)7231.208.560, [valerie.stumpf@euroflex.de](mailto:valerie.stumpf@euroflex.de))

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, [alec.niedermaier@euroflex.de](mailto:alec.niedermaier@euroflex.de))  
west USA: or Keyur Amin (Phone +1 714-317-0971, [keyur.amin@euroflex.de](mailto:keyur.amin@euroflex.de))

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	Tantal-Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162 m			
506	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210 m		ground	
507	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480 m		ground	
508	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310 m			
509	Titan Gr. 2	0,820	0,156	0,508	0,0323	0,0061	0,0200	74,736 m			
510	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	662,317 m			
511	Titan Gr. 2	1,225	0,050	1,125	0,0482	0,0020	0,0443	44,997 m			
512	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,027 m			
513	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490 m			
514	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670 m			
515	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120 m			
516	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990 m			
517	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050 m			