

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1		1,500	0,178	1,144	0,0591	0,0070	0,0450	8,990	m		
2		1,800	0,210	1,380	0,0709	0,0083	0,0543	1,016	m		
3		4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647	m		
4		4,900	0,500	3,900	0,1929	0,0197	0,1535	3,529	m		
5	(1.4301 (304))	0,356	0,075	0,206	0,0140	0,0030	0,0081	4,000	m		
6	(1.4301 (304))	0,410	0,045	0,320	0,0161	0,0018	0,0126	54,933	m		
7	(1.4301 (304))	0,790	0,035	0,720	0,0311	0,0014	0,0283	30,500	m		
8	(1.4301 (304))	0,790	0,035	0,720	0,0311	0,0014	0,0283	8,436	m		
9	(1.4301 (304))	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
10	(1.4301 (304))	1,372	0,305	0,762	0,0540	0,0120	0,0300	168,000	m		
11	(1.4301 (304))	1,372	0,305	0,762	0,0540	0,0120	0,0300	20,000	m		
12	(1.4301 (304))	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
13	(1.4301 (304))	2,515	0,051	2,413	0,0990	0,0020	0,0950	9,000	St		
14	(1.4301 (304))	3,000	0,300	2,400	0,1181	0,0118	0,0945	4,369	m		
15	(1.4301 (304))	3,600	0,300	3,000	0,1417	0,0118	0,1181	5,328	m		
16	(1.4301 (304))	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
17	(1.4301 (304))	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
18	(1.4301 (304))	6,700	0,500	5,700	0,2638	0,0197	0,2244	12,728	m		
19	(1.4301 (304))	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
20	(1.4301 (304))	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
21	(1.4307)	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	(1.4452)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
23	(1.4452)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
24	(1.4452)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
25	(1.4452)	1,800	0,090	1,620	0,0709	0,0035	0,0638	31,775	m		
26	(1.4452)	2,350	0,150	2,050	0,0925	0,0059	0,0807	4,737	m		
27	(1.4452)	4,500	0,220	4,060	0,1772	0,0087	0,1598	2,393	m		
28	(1.4452)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
29	(1.4541)	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
30	(1.4568)	0,690	0,125	0,440	0,0272	0,0049	0,0173	8,854	m		
31	(1.4568)	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
32	(1.4568)	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
33	(1.4568)	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
34	(1.4568)	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
35	(1.4568)	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
36	(1.4571)	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
37	00Cr18Mn15Mo	1,800	0,110	1,580	0,0709	0,0043	0,0622	8,000	m		
38	316L	0,457	0,070	0,317	0,0180	0,0028	0,0125	6,939	m		
39	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	45,250	m		
40	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	194,020	m		
41	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	23,136	m		
42	316L	3,000	0,100	2,800	0,1181	0,0039	0,1102	10,732	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	13,621	m		
44	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
45	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	107,000	St		
46	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
47	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	367,466	m		
48	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	137,167	m		
49	316LVM	0,450	0,075	0,300	0,0177	0,0030	0,0118	9,481	m		
50	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	61,000	m		
51	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	27,113	m		
52	316LVM	0,635	0,076	0,483	0,0250	0,0030	0,0190	17,000	m		
53	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	23,050	m		
54	316LVM	0,724	0,100	0,524	0,0285	0,0039	0,0206	3,735	m		
55	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	37,212	m		
56	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	138,710	m		
57	316LVM	0,960	0,120	0,720	0,0378	0,0047	0,0283	9,277	m		
58	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	48,370	m		
59	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	74,290	m		
60	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	24,981	m		
61	316LVM	1,000	0,200	0,600	0,0394	0,0079	0,0236	51,603	m		
62	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
63	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	62,780	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	66,530	m		
65	316LVM	1,169	0,102	0,965	0,0460	0,0040	0,0380	6,900	m		
66	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
67	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
68	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
69	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	8,953	m		
70	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
71	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		
72	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	19,602	m		
73	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	11,761	m		
74	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	29,813	m		
75	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
76	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	48,700	m		
77	316LVM	2,100	0,100	1,900	0,0827	0,0039	0,0748	18,853	m		
78	316LVM	2,400	0,100	2,200	0,0945	0,0039	0,0866	29,165	m		
79	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	29,849	m		
80	316LVM	2,530	0,100	2,330	0,0996	0,0039	0,0917	5,508	m		
81	316LVM	2,610	0,220	2,170	0,1028	0,0087	0,0854	6,803	m		
82	316LVM	2,730	0,220	2,290	0,1075	0,0087	0,0902	2,882	m		
83	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
84	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	77,395	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	3,110	0,105	2,900	0,1224	0,0041	0,1142	29,707	m		
86	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
87	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	48,250	m		
88	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
89	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	9,885	m		
90	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
91	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
92	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	22,012	m		
93	316LVM	5,436	0,216	5,003	0,2140	0,0085	0,1970	3,475	m		
94	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
95	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
96	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
97	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	30,982	m		
98	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	21,000	m		
99	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		
100	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	52,701	m		
101	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
102	316LVM	6,350	0,254	5,842	0,2500	0,0100	0,2300	5,020	m		
103	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	12,404	m		
104	316LVM	7,940	0,510	6,920	0,3126	0,0201	0,2724	4,620	m		
105	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
107	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	6,251	m		
108	316LVM	9,525	0,513	8,500	0,3750	0,0202	0,3346	7,162	m		
109	316LVM	10,000	0,500	9,000	0,3937	0,0197	0,3543	28,295	m		
110	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	76,000	m		
111	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	43,087	m		
112	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	3,100	m		
113	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2310,000	St		
114	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	935,000	St		
115	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	9,886	m		
116	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		
117	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		
118	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
119	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
120	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
121	KC35N LT	1,500	0,130	1,240	0,0591	0,0051	0,0488	23,010	m		
122	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
123	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	2,013	m		
124	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	14,397	m		
125	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
126	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
128	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
129	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		
130	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,710	m		
131	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	56,410	m		
132	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	12,232	m		
133	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
134	KC35N LT	6,000	0,550	4,900	0,2362	0,0217	0,1929	13,402	m		
135	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		
136	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
137	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
138	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
139	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
140	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
141	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	45,448	m		
142	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
143	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
144	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	10,764	m		
145	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	26,260	m		
146	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
147	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
149	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
150	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
151	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
152	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
153	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
154	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
155	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		
156	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	10,264	m		
157	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	166,877	m		
158	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	18,890	m		
159	L605	1,600	0,120	1,360	0,0630	0,0047	0,0535	9,221	m		
160	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
161	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	21,532	m		
162	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
163	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
164	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	153,966	m		
165	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
166	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
167	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		
168	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	22,750	m		
170	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	374,899	m		
171	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
172	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
173	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
174	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
175	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
176	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		
177	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
178	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
179	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
180	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	10,552	m		
181	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	111,553	m		
182	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	21,220	m		
183	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	582,780	m		
184	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
185	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	32,710	m		
186	L605	2,540	0,178	2,184	0,1000	0,0070	0,0860	19,710	m		
187	L605	2,997	0,107	2,783	0,1180	0,0042	0,1096	6,457	m		
188	L605	3,000	0,170	2,660	0,1181	0,0067	0,1047	67,387	m		
189	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	16,400	m		

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	100,710	m		
191	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
192	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	16,700	m		
193	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
194	L605	4,400	0,280	3,840	0,1732	0,0110	0,1512	4,485	m		
195	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
196	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	3,030	m		
197	L605	5,000	0,200	4,600	0,1969	0,0079	0,1811	11,403	m		
198	L605	6,000	0,250	5,500	0,2362	0,0098	0,2165	9,199	m		
199	L605	8,200	0,250	7,700	0,3228	0,0098	0,3031	8,967	m		
200	L605	8,890	0,813	7,264	0,3500	0,0320	0,2860	3,962	m		
201	L605	8,890	0,813	7,264	0,3500	0,0320	0,2860	5,944	m		
202	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
203	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
204	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
205	NiTi	0,100	0,040	0,020	0,0039	0,0016	0,0008	18,200	m	ground	max. 15 °C
206	NiTi	0,216	0,038	0,140	0,0085	0,0015	0,0055	14,376	m	ground	max. 15 °C
207	NiTi	0,240	0,080	0,080	0,0094	0,0031	0,0031	210,138	m	ground	max. 15 °C
208	NiTi	0,240	0,090	0,060	0,0094	0,0035	0,0024	3,820	m	ground	max. 15 °C
209	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	10,757	m	ground	max. 15 °C
210	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	57,750 m		ground	max. 15 °C
212	NiTi	0,350	0,125	0,100	0,0138	0,0049	0,0039	3,390 m		ground	max. 15 °C
213	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	133,457 m		dark oxidized	max. 15 °C
214	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	23,812 m		dark oxidized	max. 15 °C
215	NiTi	0,400	0,080	0,240	0,0157	0,0031	0,0094	5,087 m		ground out-/oxidic inside	
216	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	51,080 m		ground	
217	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	8,790 m		ground	max. 15 °C
218	NiTi	0,432	0,090	0,252	0,0170	0,0035	0,0099	86,490 m		ground	max. 15 °C
219	NiTi	0,450	0,050	0,350	0,0177	0,0020	0,0138	10,747 m		ground	max. 15 °C
220	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	31,544 m		dark oxidized	max. 15 °C
221	NiTi	0,480	0,076	0,328	0,0189	0,0030	0,0129	16,197 m		ground	max. 15 °C
222	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	162,718 m		dark oxidized	max. 15 °C
223	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	180,236 m		dark oxidized	max. 15 °C
224	NiTi	0,570	0,090	0,390	0,0224	0,0035	0,0154	1,899 m		dark oxidized	max. 15 °C
225	NiTi	0,600	0,080	0,440	0,0236	0,0031	0,0173	14,716 m		ground out-/oxidic inside	
226	NiTi	0,635	0,102	0,432	0,0250	0,0040	0,0170	201,788 m		ground	max. 15 °C
227	NiTi	0,660	0,076	0,508	0,0260	0,0030	0,0200	1,800 m		ground out-/oxidic inside	max. 15 °C
228	NiTi	0,730	0,150	0,430	0,0287	0,0059	0,0169	22,485 m		ground out-/oxidic inside	max. 15 °C
229	NiTi	0,730	0,150	0,430	0,0287	0,0059	0,0169	4,800 m		ground	max. 15 °C
230	NiTi	0,790	0,099	0,592	0,0311	0,0039	0,0233	9,353 m		ground	max. 15 °C
231	NiTi	0,792	0,099	0,594	0,0312	0,0039	0,0234	8,209 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	0,880	0,115	0,650	0,0346	0,0045	0,0256	7,058 m		ground	max. 15 °C
233	NiTi	0,900	0,190	0,520	0,0354	0,0075	0,0205	10,810 m		dark oxidized	max. 15 °C
234	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	48,800 m		dark oxidized	max. 15 °C
235	NiTi	0,960	0,050	0,860	0,0378	0,0020	0,0339	10,639 m		ground	max. 15 °C
236	NiTi	1,000	0,080	0,840	0,0394	0,0031	0,0331	19,884 m		ground	
237	NiTi	1,000	0,090	0,820	0,0394	0,0035	0,0323	1,497 m		ground	
238	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	48,077 m		ground	max. 15 °C
239	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	43,440 m		ground	max. 15 °C
240	NiTi	1,200	0,125	0,950	0,0472	0,0049	0,0374	6,355 m		ground	max. 15 °C
241	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	4,995 m		ground out-/oxidic inside	
242	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	7,330 m		ground out-/oxidic inside	
243	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	9,088 m		ground out-/oxidic inside	max. 15 °C
244	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	240,456 m		ground	max. 15 °C
245	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	213,338 m		ground	max. 15 °C
246	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	8,648 m		ground	max. 15 °C
247	NiTi	1,240	0,230	0,780	0,0488	0,0091	0,0307	29,339 m		ground	max. 15 °C
248	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	6,267 m		ground	max. 15 °C
249	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	80,843 m		ground	max. 15 °C
250	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,520 m		ground	max. 15 °C
251	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	49,682 m		ground	max. 15 °C
252	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,632 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	max. 15 °C
254	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	14,990 m		ground	max. 15 °C
255	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m		ground out-/oxidic inside	
256	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	24,000 m		ground out-/oxidic inside	
257	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	
258	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,030 m		ground	
259	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	3,250 m		ground	
260	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m		ground	
261	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,129 m		ground	
262	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,410 m		ground	
263	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	
264	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	
265	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	
266	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	187,348 m		ground	
267	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	
268	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,500 m		ground	
269	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	
270	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	max. 15 °C
271	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	max. 15 °C
272	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	
273	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,943 m		ground	

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	39,400 m		ground	
275	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	
276	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	
277	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	40,650 m		ground	max. 15 °C
278	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	6,151 m		ground	
279	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	9,410 m		ground	
280	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	19,235 m		ground	max. 15 °C
281	NiTi	1,350	0,135	1,080	0,0531	0,0053	0,0425	15,445 m		ground	max. 15 °C
282	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	12,364 m		ground	max. 15 °C
283	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	13,991 m		ground	max. 15 °C
284	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	10,187 m		ground	max. 15 °C
285	NiTi	1,390	0,130	1,130	0,0547	0,0051	0,0445	15,575 m		ground	max. 15 °C
286	NiTi	1,400	0,240	0,920	0,0551	0,0094	0,0362	2,801 m		ground	max. 15 °C
287	NiTi	1,400	0,240	0,920	0,0551	0,0094	0,0362	3,000 m		ground	max. 15 °C
288	NiTi	1,420	0,160	1,100	0,0559	0,0063	0,0433	2,420 m		ground	max. 15 °C
289	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	5,939 m		ground	max. 15 °C
290	NiTi	1,450	0,225	1,000	0,0571	0,0089	0,0394	3,630 m		ground	max. 15 °C
291	NiTi	1,450	0,225	1,000	0,0571	0,0089	0,0394	3,870 m		ground	max. 15 °C
292	NiTi	1,500	0,220	1,060	0,0591	0,0087	0,0417	1,220 m		ground	max. 15 °C
293	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	1,859 m		ground	max. 15 °C
294	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	5,762 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,524	0,114	1,296	0,0600	0,0045	0,0510	7,000	St	ground	max. 15 °C
296	NiTi	1,524	0,127	1,270	0,0600	0,0050	0,0500	2,492	m	ground	max. 15 °C
297	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	19,461	m	ground	max. 15 °C
298	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	64,005	m	ground	max. 15 °C
299	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	8,878	m	ground	max. 15 °C
300	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	87,904	m	ground	max. 15 °C
301	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	1,300	m	ground	max. 15 °C
302	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080	m	ground out-/oxidic inside	max. 15 °C
303	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	96,900	m	ground out-/oxidic inside	max. 15 °C
304	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	16,307	m	ground	max. 15 °C
305	NiTi	1,560	0,130	1,300	0,0614	0,0051	0,0512	17,080	m	ground	max. 15 °C
306	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,532	m	ground out-/oxidic inside	max. 15 °C
307	NiTi	1,600	0,200	1,200	0,0630	0,0079	0,0472	14,569	m		70 - 110 °C
308	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	158,940	m	ground	max. 15 °C
309	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	247,196	m	ground	max. 15 °C
310	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	44,811	m	ground	max. 15 °C
311	NiTi	1,600	0,240	1,120	0,0630	0,0094	0,0441	75,072	m	ground	max. 15 °C
312	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	2,760	m	ground	max. 15 °C
313	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	25,640	m	ground	max. 15 °C
314	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	66,396	m	ground	max. 15 °C
315	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	9,605	m	ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,600	0,270	1,060	0,0630	0,0106	0,0417	72,769 m		ground	max. 15 °C
317	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	3,490 m		ground	max. 15 °C
318	NiTi	1,620	0,240	1,140	0,0638	0,0094	0,0449	39,435 m		ground out-/oxidic inside	max. 15 °C
319	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	max. 15 °C
320	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	13,028 m		ground out-/oxidic inside	max. 15 °C
321	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737 m		ground out-/oxidic inside	
322	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	271,498 m		ground out-/oxidic inside	max. 15 °C
323	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970 m		ground out-/oxidic inside	max. 15 °C
324	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	88,612 m		ground out-/oxidic inside	max. 15 °C
325	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820 m		ground out-/oxidic inside	max. 15 °C
326	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,170 m		polished	max. 15 °C
327	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	4,631 m		ground	max. 15 °C
328	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609 m		ground	max. 15 °C
329	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,354 m		ground	max. 15 °C
330	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,965 m		ground	max. 15 °C
331	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,165 m		ground	
332	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	181,246 m		ground	max. 15 °C
333	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279 m		ground	max. 15 °C
334	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	
335	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		dark oxidized	
336	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	
338	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,627 m		ground	
339	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	
340	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	
341	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	61,610 m		ground	max. 15 °C
342	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	
343	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,980 m		ground	
344	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	91,179 m		ground	max. 15 °C
345	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	
346	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	
347	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	
348	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	
349	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	
350	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	
351	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	255,144 m		ground	max. 15 °C
352	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,150 m		ground	max. 15 °C
353	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	max. 15 °C
354	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	126,000 St		ground	max. 15 °C
355	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	215,668 m		ground out-/oxidic inside	max. 15 °C
356	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	292,100 m		ground out-/oxidic inside	max. 15 °C
357	NiTi	1,700	0,210	1,280	0,0669	0,0083	0,0504	1,539 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	1,700	0,300	1,100	0,0669	0,0118	0,0433	2,640 m		ground	max. 15 °C
359	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	193,756 m		ground	max. 15 °C
360	NiTi	1,729	0,210	1,309	0,0681	0,0083	0,0515	9,600 m		ground	
361	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	36,100 m		ground	
362	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	
363	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m		ground	max. 15 °C
364	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	
365	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	max. 15 °C
366	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	max. 15 °C
367	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,607 m		ground	max. 15 °C
368	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	
369	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	
370	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,900 m		ground	
371	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	max. 15 °C
372	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	9,247 m		ground	max. 15 °C
373	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,250 m		ground	
374	NiTi	1,778	0,406	0,966	0,0700	0,0160	0,0380	22,252 m		ground	max. 15 °C
375	NiTi	1,796	0,250	1,296	0,0707	0,0098	0,0510	2,181 m		ground	max. 15 °C
376	NiTi	1,796	0,250	1,296	0,0707	0,0098	0,0510	7,313 m		ground	max. 15 °C
377	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	16,992 m		ground	max. 15 °C
378	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	64,888 m		ground	max. 15 °C
380	NiTi	1,800	0,220	1,360	0,0709	0,0087	0,0535	1,438 m		ground	max. 15 °C
381	NiTi	1,803	0,216	1,371	0,0710	0,0085	0,0540	7,750 m		ground	max. 15 °C
382	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,238 m		ground	max. 15 °C
383	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,716 m		ground	max. 15 °C
384	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	5,537 m		ground	max. 15 °C
385	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	11,049 m		ground	max. 15 °C
386	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	11,705 m		ground	max. 15 °C
387	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	5,627 m		ground	max. 15 °C
388	NiTi	1,829	0,267	1,295	0,0720	0,0105	0,0510	1,548 m		ground	max. 15 °C
389	NiTi	1,829	0,292	1,245	0,0720	0,0115	0,0490	5,967 m		ground	max. 15 °C
390	NiTi	1,900	0,270	1,360	0,0748	0,0106	0,0535	68,327 m		ground	max. 15 °C
391	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	15,486 m		ground	max. 15 °C
392	NiTi	1,915	0,165	1,585	0,0754	0,0065	0,0624	15,890 m		ground	max. 15 °C
393	NiTi	1,915	0,165	1,585	0,0754	0,0065	0,0624	5,860 m		ground	max. 15 °C
394	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	162,848 m		ground	max. 15 °C
395	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990 m		ground	max. 15 °C
396	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m		ground	max. 15 °C
397	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	21,199 m		ground	max. 15 °C
398	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	43,678 m		ground	max. 15 °C
399	NiTi	2,019	0,266	1,487	0,0795	0,0105	0,0585	3,728 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	6,924 m		ground	max. 15 °C
401	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847 m		ground	max. 15 °C
402	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	413,795 m		ground	max. 15 °C
403	NiTi	2,050	0,150	1,750	0,0807	0,0059	0,0689	9,180 m		ground	max. 15 °C
404	NiTi	2,050	0,300	1,450	0,0807	0,0118	0,0571	13,025 m		ground	max. 15 °C
405	NiTi	2,120	0,320	1,480	0,0835	0,0126	0,0583	12,945 m		ground	max. 15 °C
406	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	4,950 m		ground	max. 15 °C
407	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	17,172 m		ground	max. 15 °C
408	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	21,817 m		ground	max. 15 °C
409	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	23,347 m		ground	max. 15 °C
410	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	25,863 m		ground	max. 15 °C
411	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	31,296 m		ground	max. 15 °C
412	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	130,730 m		ground	max. 15 °C
413	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	27,266 m		ground	max. 15 °C
414	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	3,772 m		ground	max. 15 °C
415	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	341,218 m		ground	max. 15 °C
416	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	16,710 m		ground	max. 15 °C
417	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	1,840 m		ground	max. 15 °C
418	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	13,550 m		ground	
419	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	9,847 m		ground	
420	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	9,850 m		ground	

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	2,184	0,349	1,486	0,0860	0,0137	0,0585	1,046 m		ground	max. 15 °C
422	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,294 m		ground	max. 15 °C
423	NiTi	2,185	0,350	1,485	0,0860	0,0138	0,0585	3,070 m		ground	max. 15 °C
424	NiTi	2,186	0,086	2,014	0,0861	0,0034	0,0793	8,466 m		ground	max. 15 °C
425	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	37,318 m		ground out-/oxidic inside	max. 15 °C
426	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	57,200 m		ground out-/oxidic inside	max. 15 °C
427	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	max. 15 °C
428	NiTi	2,200	0,230	1,740	0,0866	0,0091	0,0685	6,047 m		ground	max. 15 °C
429	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	10,610 m		ground	max. 15 °C
430	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	25,542 m		ground	max. 15 °C
431	NiTi	2,200	0,325	1,550	0,0866	0,0128	0,0610	2,040 m		ground	max. 15 °C
432	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	max. 15 °C
433	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,936 m		ground	max. 15 °C
434	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	8,747 m		ground	max. 15 °C
435	NiTi	2,286	0,254	1,778	0,0900	0,0100	0,0700	5,700 m		ground	max. 15 °C
436	NiTi	2,300	0,150	2,000	0,0906	0,0059	0,0787	15,023 m		ground	max. 15 °C
437	NiTi	2,300	0,150	2,000	0,0906	0,0059	0,0787	57,130 m		ground	max. 15 °C
438	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	max. 15 °C
439	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	3,794 m		ground	max. 15 °C
440	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	4,246 m		ground	max. 15 °C
441	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	max. 15 °C
443	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	max. 15 °C
444	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	max. 15 °C
445	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	max. 15 °C
446	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,800 m		ground out-/oxidic inside	max. 15 °C
447	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	max. 15 °C
448	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	
449	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	3,010 m		ground	
450	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	15,588 m		ground	max. 15 °C
451	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	43,543 m		ground	max. 15 °C
452	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	13,710 m		ground	max. 15 °C
453	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	13,960 m		ground	
454	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	max. 15 °C
455	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	33,572 m		ground	max. 15 °C
456	NiTi	2,400	0,085	2,230	0,0945	0,0033	0,0878	6,193 m		ground	max. 15 °C
457	NiTi	2,400	0,090	2,220	0,0945	0,0035	0,0874	9,902 m		ground	max. 15 °C
458	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	13,270 m		ground	max. 15 °C
459	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	37,005 m		dark oxidized	max. 15 °C
460	NiTi	2,400	0,300	1,800	0,0945	0,0118	0,0709	1,612 m		ground	max. 15 °C
461	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	12,867 m		ground	max. 15 °C
462	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	11,630 m		ground	

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	2,413	0,229	1,956	0,0950	0,0090	0,0770	7,460 m		ground	max. 15 °C
464	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	22,067 m		ground	max. 15 °C
465	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	3,580 m		dark oxidized	
466	NiTi	2,449	0,221	2,007	0,0964	0,0087	0,0790	19,997 m		ground	max. 15 °C
467	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	10,987 m		ground	max. 15 °C
468	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	8,106 m		ground	max. 15 °C
469	NiTi	2,480	0,225	2,030	0,0976	0,0089	0,0799	6,350 m		ground	max. 15 °C
470	NiTi	2,490	0,050	2,390	0,0980	0,0020	0,0941	2,080 m		ground	max. 15 °C
471	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	3,920 m		ground	max. 15 °C
472	NiTi	2,500	0,127	2,246	0,0984	0,0050	0,0884	6,653 m		ground	max. 15 °C
473	NiTi	2,500	0,180	2,140	0,0984	0,0071	0,0843	8,770 m			max. 15 °C
474	NiTi	2,500	0,250	2,000	0,0984	0,0098	0,0787	3,445 m		ground	max. 15 °C
475	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	10,510 m		ground out-/oxidic inside	max. 15 °C
476	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	13,249 m		ground	max. 15 °C
477	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	3,914 m		ground	max. 15 °C
478	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,577 m		ground	max. 15 °C
479	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m		ground	max. 15 °C
480	NiTi	2,590	0,076	2,438	0,1020	0,0030	0,0960	2,188 m		ground	max. 15 °C
481	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	17,785 m		ground	max. 15 °C
482	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	22,439 m		ground out-/oxidic inside	max. 15 °C
483	NiTi	2,600	0,500	1,600	0,1024	0,0197	0,0630	85,086 m		ground out-/oxidic inside	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	2,604	0,216	2,172	0,1025	0,0085	0,0855	5,040 m		ground	max. 15 °C
485	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	102,958 m		ground	max. 15 °C
486	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	11,355 m		ground	max. 15 °C
487	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	41,055 m		ground	max. 15 °C
488	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,811 m		ground	max. 15 °C
489	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	83,723 m		ground	max. 15 °C
490	NiTi	2,654	0,102	2,450	0,1045	0,0040	0,0965	12,891 m		ground	max. 15 °C
491	NiTi	2,667	0,241	2,185	0,1050	0,0095	0,0860	5,060 m		ground	max. 15 °C
492	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	4,405 m		ground	max. 15 °C
493	NiTi	2,680	0,115	2,450	0,1055	0,0045	0,0965	13,550 m		dark oxidized	max. 15 °C
494	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022 m		ground	max. 15 °C
495	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,177 m		ground	max. 15 °C
496	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	13,414 m		ground	max. 15 °C
497	NiTi	2,720	0,170	2,380	0,1071	0,0067	0,0937	3,175 m		ground	max. 15 °C
498	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	12,963 m		ground	max. 15 °C
499	NiTi	2,751	0,302	2,147	0,1083	0,0119	0,0845	42,540 m		ground	max. 15 °C
500	NiTi	2,760	0,190	2,380	0,1087	0,0075	0,0937	4,993 m		ground	max. 15 °C
501	NiTi	2,770	0,065	2,640	0,1091	0,0026	0,1039	2,635 m		ground	max. 15 °C
502	NiTi	2,795	0,100	2,595	0,1100	0,0039	0,1022	0,326 m		ground	
503	NiTi	2,800	0,230	2,340	0,1102	0,0091	0,0921	7,230 m		ground	max. 15 °C
504	NiTi	2,800	0,500	1,800	0,1102	0,0197	0,0709	13,866 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	NiTi	2,800	0,500	1,800	0,1102	0,0197	0,0709	3,998 m		ground out-/oxidic inside	15 °C
506	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	16,129 m		ground	max. 15 °C
507	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	17,847 m		ground out-/oxidic inside	max. 15 °C
508	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	18,776 m		ground out-/oxidic inside	max. 15 °C
509	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	21,873 m		ground out-/oxidic inside	max. 15 °C
510	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	41,024 m		ground out-/oxidic inside	max. 15 °C
511	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	6,082 m		ground out-/oxidic inside	max. 15 °C
512	NiTi	2,895	0,114	2,667	0,1140	0,0045	0,1050	71,752 m		ground out-/oxidic inside	max. 15 °C
513	NiTi	2,906	0,191	2,524	0,1144	0,0075	0,0994	22,430 m		ground	max. 15 °C
514	NiTi	2,980	0,208	2,564	0,1173	0,0082	0,1009	17,501 m		ground	max. 15 °C
515	NiTi	3,000	0,110	2,780	0,1181	0,0043	0,1094	2,545 m		ground	max. 15 °C
516	NiTi	3,030	0,233	2,564	0,1193	0,0092	0,1009	6,086 m		ground	max. 15 °C
517	NiTi	3,048	0,254	2,540	0,1200	0,0100	0,1000	13,000 m	St	ground	max. 15 °C
518	NiTi	3,063	0,262	2,539	0,1206	0,0103	0,1000	5,630 m		ground	
519	NiTi	3,100	1,075	0,950	0,1220	0,0423	0,0374	1,150 m		ground	
520	NiTi	3,160	0,170	2,820	0,1244	0,0067	0,1110	9,239 m		ground	max. 15 °C
521	NiTi	3,200	0,165	2,870	0,1260	0,0065	0,1130	2,042 m		ground	max. 15 °C
522	NiTi	3,200	0,190	2,820	0,1260	0,0075	0,1110	2,000 m	St	ground	max. 15 °C
523	NiTi	3,200	0,540	2,120	0,1260	0,0213	0,0835	7,690 m		ground	max. 15 °C
524	NiTi	3,200	0,540	2,120	0,1260	0,0213	0,0835	8,597 m		ground	max. 15 °C
525	NiTi	3,260	0,140	2,980	0,1283	0,0055	0,1173	3,843 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
526	NiTi	3,260	0,140	2,980	0,1283	0,0055	0,1173	6,604 m		ground	max. 15 °C
527	NiTi	3,280	0,115	3,050	0,1291	0,0045	0,1201	5,050 m		ground	max. 15 °C
528	NiTi	3,302	0,711	1,880	0,1300	0,0280	0,0740	13,357 m		ground	max. 15 °C
529	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,471 m		ground out-/oxidic inside	max. 15 °C
530	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,757 m		ground out-/oxidic inside	max. 15 °C
531	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	53,865 m		ground	max. 15 °C
532	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,471 m		ground	max. 15 °C
533	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	3,666 m		ground out-/oxidic inside	max. 15 °C
534	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	7,000 m	St	ground	max. 15 °C
535	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	7,872 m		ground	max. 15 °C
536	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	14,571 m		ground	max. 15 °C
537	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610 m		ground	max. 15 °C
538	NiTi	3,500	0,170	3,160	0,1378	0,0067	0,1244	1,425 m		dark oxidized	max. 15 °C
539	NiTi	3,500	0,170	3,160	0,1378	0,0067	0,1244	3,915 m		ground	max. 15 °C
540	NiTi	3,500	0,320	2,860	0,1378	0,0126	0,1126	4,118 m		ground	max. 15 °C
541	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	5,520 m		ground	max. 15 °C
542	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	10,190 m		ground	max. 15 °C
543	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	11,588 m		ground	max. 15 °C
544	NiTi	3,600	0,250	3,100	0,1417	0,0098	0,1220	6,999 m		ground	max. 15 °C
545	NiTi	3,610	0,250	3,110	0,1421	0,0098	0,1224	4,542 m		ground	max. 15 °C
546	NiTi	3,800	0,100	3,600	0,1496	0,0039	0,1417	5,070 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
547	NiTi	3,800	0,265	3,270	0,1496	0,0104	0,1287	4,516 m		ground	
548	NiTi	3,810	0,120	3,570	0,1500	0,0047	0,1406	4,565 m		ground	max. 15 °C
549	NiTi	3,900	0,260	3,380	0,1535	0,0102	0,1331	7,000 m		ground	max. 15 °C
550	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	110,766 m		ground	max. 15 °C
551	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	119,084 m		ground	max. 15 °C
552	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	23,177 m		ground	max. 15 °C
553	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	4,613 m		ground	max. 15 °C
554	NiTi	4,000	0,100	3,800	0,1575	0,0039	0,1496	104,449 m		ground	max. 15 °C
555	NiTi	4,000	0,100	3,800	0,1575	0,0039	0,1496	5,220 m		ground	max. 15 °C
556	NiTi	4,000	0,102	3,796	0,1575	0,0040	0,1494	7,452 m		ground	max. 15 °C
557	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	21,222 m		ground	max. 15 °C
558	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	4,000 m		ground	max. 15 °C
559	NiTi	4,150	0,100	3,950	0,1634	0,0039	0,1555	6,566 m		ground	max. 15 °C
560	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	19,533 m		ground	
561	NiTi	4,242	0,152	3,938	0,1670	0,0060	0,1550	14,331 m		ground	max. 15 °C
562	NiTi	4,270	0,079	4,112	0,1681	0,0031	0,1619	4,942 m		ground	max. 15 °C
563	NiTi	4,300	0,400	3,500	0,1693	0,0157	0,1378	7,315 m		ground	max. 15 °C
564	NiTi	4,500	0,080	4,340	0,1772	0,0031	0,1709	0,744 m		ground	max. 15 °C
565	NiTi	4,500	0,127	4,246	0,1772	0,0050	0,1672	2,264 m		ground	max. 15 °C
566	NiTi	4,500	0,700	3,100	0,1772	0,0276	0,1220	7,780 m		ground	max. 15 °C
567	NiTi	4,700	0,150	4,400	0,1850	0,0059	0,1732	28,451 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
568	NiTi	4,750	0,125	4,500	0,1870	0,0049	0,1772	7,390 m		ground	max. 15 °C
569	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,597 m		ground	max. 15 °C
570	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	5,645 m		ground	max. 15 °C
571	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	2,707 m		ground	max. 15 °C
572	NiTi	4,900	0,200	4,500	0,1929	0,0079	0,1772	37,806 m		ground	max. 15 °C
573	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	5,320 m		polished	max. 15 °C
574	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	max. 15 °C
575	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,306 m		ground	max. 15 °C
576	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,876 m		ground	max. 15 °C
577	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	max. 15 °C
578	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	max. 15 °C
579	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	max. 15 °C
580	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	max. 15 °C
581	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	max. 15 °C
582	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,030 m		ground out-/oxidic inside	max. 15 °C
583	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	max. 15 °C
584	NiTi	4,980	0,280	4,420	0,1961	0,0110	0,1740	3,032 m		ground	max. 15 °C
585	NiTi	5,000	0,100	4,800	0,1969	0,0039	0,1890	3,710 m		ground	max. 15 °C
586	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	2,510 m		ground	max. 15 °C
587	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	8,708 m		ground	max. 15 °C
588	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	9,631 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
589	NiTi	5,000	0,250	4,500	0,1969	0,0098	0,1772	5,870 m		ground	
590	NiTi	5,000	0,400	4,200	0,1969	0,0157	0,1654	8,316 m		ground	max. 15 °C
591	NiTi	5,000	0,450	4,100	0,1969	0,0177	0,1614	2,754 m		ground	max. 15 °C
592	NiTi	5,000	0,560	3,880	0,1969	0,0220	0,1528	1,650 m		ground	
593	NiTi	5,004	0,533	3,938	0,1970	0,0210	0,1550	4,518 m		ground out-/oxidic inside	max. 15 °C
594	NiTi	5,004	0,546	3,912	0,1970	0,0215	0,1540	23,848 m		ground	max. 15 °C
595	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	max. 15 °C
596	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434 m		ground	max. 15 °C
597	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	35,820 m		ground	max. 15 °C
598	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	6,000 m		ground	max. 15 °C
599	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	25,000 m		ground	max. 15 °C
600	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	3,189 m		ground	max. 15 °C
601	NiTi	5,207	0,279	4,649	0,2050	0,0110	0,1830	3,940 m		ground	max. 15 °C
602	NiTi	5,410	0,483	4,444	0,2130	0,0190	0,1750	3,010 m		ground	max. 15 °C
603	NiTi	5,500	0,065	5,370	0,2165	0,0026	0,2114	0,723 m		polished	max. 15 °C
604	NiTi	5,500	0,100	5,300	0,2165	0,0039	0,2087	2,710 m		ground	max. 15 °C
605	NiTi	5,538	0,203	5,131	0,2180	0,0080	0,2020	3,490 m		ground	max. 15 °C
606	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	3,520 m		ground	max. 15 °C
607	NiTi	5,600	0,150	5,300	0,2205	0,0059	0,2087	1,220 m		ground	
608	NiTi	5,700	0,200	5,300	0,2244	0,0079	0,2087	3,075 m		ground	max. 15 °C
609	NiTi	5,893	0,546	4,801	0,2320	0,0215	0,1890	6,471 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
610	NiTi	5,944	0,572	4,800	0,2340	0,0225	0,1890	1,250 m		ground out-/oxidic inside	max. 15 °C
611	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,110 m		ground out-/oxidic inside	max. 15 °C
612	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	14,190 m		ground out-/oxidic inside	max. 15 °C
613	NiTi	5,994	0,254	5,486	0,2360	0,0100	0,2160	4,450 m		ground	max. 15 °C
614	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,525 m		ground	max. 15 °C
615	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	7,512 m		ground	max. 15 °C
616	NiTi	6,000	0,064	5,872	0,2362	0,0025	0,2312	4,910 m		ground	max. 15 °C
617	NiTi	6,000	0,100	5,800	0,2362	0,0039	0,2283	3,228 m		ground	max. 15 °C
618	NiTi	6,000	0,400	5,200	0,2362	0,0157	0,2047	3,215 m		ground	max. 15 °C
619	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	15,390 m		ground	max. 15 °C
620	NiTi	6,150	0,100	5,950	0,2421	0,0039	0,2343	7,196 m		ground	max. 15 °C
621	NiTi	6,200	0,150	5,900	0,2441	0,0059	0,2323	1,386 m		ground	max. 15 °C
622	NiTi	6,400	0,200	6,000	0,2520	0,0079	0,2362	2,011 m		ground	max. 15 °C
623	NiTi	6,700	0,250	6,200	0,2638	0,0098	0,2441	4,936 m		ground	max. 15 °C
624	NiTi	6,820	0,160	6,500	0,2685	0,0063	0,2559	5,515 m		ground	max. 15 °C
625	NiTi	6,830	0,245	6,340	0,2689	0,0096	0,2496	11,020 m		ground	max. 15 °C
626	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	6,967 m		ground	max. 15 °C
627	NiTi	7,000	0,440	6,120	0,2756	0,0173	0,2409	5,641 m		ground	max. 15 °C
628	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	1,967 m		ground	max. 15 °C
629	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	2,399 m		ground	max. 15 °C
630	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	3,772 m		ground	max. 15 °C

Stock list - Tubes

current status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
631	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	5,167 m		ground out-/oxidic inside	max. 15 °C
632	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	7,472 m		ground	max. 15 °C
633	NiTi	7,000	0,508	5,984	0,2756	0,0200	0,2356	3,885 m		ground	max. 15 °C
634	NiTi	7,000	0,533	5,934	0,2756	0,0210	0,2336	5,412 m		ground	max. 15 °C
635	NiTi	7,150	0,100	6,950	0,2815	0,0039	0,2736	11,141 m		ground	max. 15 °C
636	NiTi	7,350	0,310	6,730	0,2894	0,0122	0,2650	2,460 m		ground	max. 15 °C
637	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	5,777 m		ground	max. 15 °C
638	NiTi	8,000	0,160	7,680	0,3150	0,0063	0,3024	4,400 m		ground	max. 15 °C
639	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	0,710 m		ground	
640	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	1,520 m			
641	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	18,020 m		ground	
642	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,130 m		ground	
643	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,570 m		ground	
644	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	16,660 m		ground	
645	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	4,550 m		ground	
646	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	7,310 m		ground	
647	NiTi	8,000	0,520	6,960	0,3150	0,0205	0,2740	2,015 m		ground	max. 15 °C
648	NiTi	8,000	0,720	6,560	0,3150	0,0283	0,2583	1,186 m		ground	max. 15 °C
649	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,645 m		ground	max. 15 °C
650	NiTi	8,300	0,310	7,680	0,3268	0,0122	0,3024	4,460 m		ground	max. 15 °C
651	NiTi	8,800	0,550	7,700	0,3465	0,0217	0,3031	1,297 m		ground	max. 15 °C

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
652	NiTi	9,000	0,400	8,200	0,3543	0,0157	0,3228	4,000	St	ground	max. 15 °C
653	NiTi	9,000	0,500	8,000	0,3543	0,0197	0,3150	2,170	m	ground	max. 15 °C
654	NiTi	10,000	0,200	9,600	0,3937	0,0079	0,3780	3,220	m	ground	max. 15 °C
655	NiTi	10,000	0,250	9,500	0,3937	0,0098	0,3740	1,080	m	ground	max. 15 °C
656	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	20,069	m	ground	max. 15 °C
657	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	3,470	m	ground	max. 15 °C
658	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	4,220	m	ground	max. 15 °C
659	NiTi	10,000	0,480	9,040	0,3937	0,0189	0,3559	14,031	m	ground	max. 15 °C
660	NiTi	10,000	0,625	8,750	0,3937	0,0246	0,3445	7,149	m	ground	max. 15 °C
661	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	3,410	m	ground	
662	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	6,591	m	ground	max. 15 °C
663	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	9,963	m	ground	
664	Phynox / 2.471	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034	m		
665	section	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
666	segment	0,180	0,050	0,080	0,0071	0,0020	0,0031	2,400	g		
667	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	3,053	m		
668	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	5,067	m		
669	Tantal/Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162	m		
670	Tantalum	1,600	0,200	1,200	0,0630	0,0079	0,0472	0,951	m	polished	
671	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210	m	ground	
672	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480	m	ground	

Stock list - Tubescurrent status: **19.11.2020**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
673	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310	m		
674	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	666,882	m		
675	Titan Gr. 2	1,250	0,100	1,050	0,0492	0,0039	0,0413	62,150	m	ground	
676	Titan Gr. 2	1,650	0,150	1,350	0,0650	0,0059	0,0531	80,674	m		
677	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,806	m		
678	Titan Gr. 2	2,350	0,500	1,350	0,0925	0,0197	0,0531	2,800	m		
679	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490	m		
680	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670	m		
681	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
682	Titan Gr. 2	5,000	0,550	3,900	0,1969	0,0217	0,1535	8,761	m		
683	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
684	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		
685	Titan Gr. 2	7,925	0,889	6,147	0,3120	0,0350	0,2420	6,679	m		
686	Titan Gr. 2	10,000	4,450	1,100	0,3937	0,1752	0,0433	24,000	St		
687	Titan Gr. 2	10,000	4,450	1,100	0,3937	0,1752	0,0433	24,000	St		