

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1	1.4301 (304)	0,356	0,075	0,206	0,0140	0,0030	0,0081	2,000	m		
2	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
3	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	20,000	m		
4	1.4301 (304)	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
5	1.4301 (304)	2,515	0,051	2,413	0,0990	0,0020	0,0950	9,000	St		
6	1.4301 (304)	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
7	1.4301 (304)	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
8	1.4301 (304)	6,700	0,500	5,700	0,2638	0,0197	0,2244	11,650	m		
9	1.4301 (304)	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
10	1.4301 (304)	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
11	1.4307	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
12	1.4452 (P 2000)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
13	1.4452 (P 2000)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
14	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
15	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	31,775	m		
16	1.4452 (P 2000)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
17	1.4541	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
18	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	14,722	m		
19	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	24,000	m		
20	1.4550	10,140	0,220	9,700	0,3992	0,0087	0,3819	16,000	St		
21	1.4568	0,690	0,125	0,440	0,0272	0,0049	0,0173	7,854	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	1.4568	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		
23	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
24	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
25	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	23,560	m		
26	1.4568	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
27	1.4568	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
28	1.4571	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
29	316L	0,457	0,070	0,317	0,0180	0,0028	0,0125	5,533	m		
30	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	33,244	m		
31	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	188,000	m		
32	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
33	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
34	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	13,621	m		
35	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
36	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
37	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	359,805	m		
38	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	130,860	m		
39	316LVM	0,450	0,075	0,300	0,0177	0,0030	0,0118	6,646	m		
40	316LVM	0,450	0,100	0,250	0,0177	0,0039	0,0098	66,520	m		
41	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	37,000	m		
42	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	26,114	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	16,587	m		
44	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	37,170	m		
45	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	5,076	m		
46	316LVM	0,800	0,150	0,500	0,0315	0,0059	0,0197	84,820	m		
47	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	35,800	m		
48	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	38,024	m		
49	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	45,981	m		
50	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	72,562	m		
51	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	15,254	m		
52	316LVM	1,000	0,200	0,600	0,0394	0,0079	0,0236	47,383	m		
53	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
54	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	64,256	m		
55	316LVM	1,169	0,102	0,965	0,0460	0,0040	0,0380	2,740	m		
56	316LVM	1,300	0,075	1,150	0,0512	0,0030	0,0453	20,605	m		
57	316LVM	1,400	0,130	1,140	0,0551	0,0051	0,0449	45,402	m		
58	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
59	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
60	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
61	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	2,986	m		
62	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
63	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	19,602	m		
65	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	11,761	m		
66	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	13,998	m		
67	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
68	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	48,700	m		
69	316LVM	2,100	0,100	1,900	0,0827	0,0039	0,0748	18,853	m		
70	316LVM	2,400	0,100	2,200	0,0945	0,0039	0,0866	25,027	m		
71	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	19,953	m		
72	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
73	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	59,721	m		
74	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
75	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	46,767	m		
76	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
77	316LVM	4,572	0,229	4,114	0,1800	0,0090	0,1620	63,638	m		
78	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
79	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
80	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	22,012	m		
81	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	62,513	m		
82	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
83	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
84	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	19,306	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
86	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	21,000	m		
87	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		
88	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	32,702	m		
89	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
90	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	8,287	m		
91	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		
92	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
93	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	6,251	m		
94	316LVM	9,525	0,513	8,500	0,3750	0,0202	0,3346	13,590	m		
95	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	52,377	m		
96	KC35N LT	0,356	0,102	0,152	0,0140	0,0040	0,0060	27,000	St		
97	KC35N LT	0,368	0,083	0,203	0,0145	0,0033	0,0080	29,000	St		
98	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	39,137	m		
99	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	2,100	m		
100	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2290,000	St		
101	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	915,000	St		
102	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	47,100	m		
103	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	5,666	m		
104	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		
105	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	1,240	0,070	1,100	0,0488	0,0028	0,0433	19,985	m		
107	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
108	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
109	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
110	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
111	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	1,816	m		
112	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	14,397	m		
113	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
114	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		
115	KC35N LT	2,350	0,150	2,050	0,0925	0,0059	0,0807	25,567	m		
116	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
117	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
118	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		
119	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
120	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	50,256	m		
121	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	9,819	m		
122	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
123	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		
124	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
125	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	37,340	m		
126	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
128	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		
129	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	16,160	m		
130	L605	0,762	0,127	0,508	0,0300	0,0050	0,0200	38,452	m		
131	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,451	m		
132	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
133	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	45,448	m		
134	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
135	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
136	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	10,764	m		
137	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	26,260	m		
138	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
139	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		
140	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
141	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
142	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
143	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
144	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
145	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
146	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
147	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	189,788	m		
149	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	24,460	m		
150	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
151	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,532	m		
152	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
153	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
154	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	175,576	m		
155	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
156	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
157	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	66,860	m		
158	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		
159	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		
160	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	16,651	m		
161	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
162	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
163	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
164	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
165	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
166	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		
167	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
168	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
170	L605	1,800	0,104	1,592	0,0709	0,0041	0,0627	128,291	m		
171	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	107,761	m		
172	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	21,220	m		
173	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	322,131	m		
174	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	431,611	m		
175	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	561,306	m		
176	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
177	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	8,711	m		
178	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	32,710	m		
179	L605	2,000	0,110	1,780	0,0787	0,0043	0,0701	46,013	m		
180	L605	3,000	0,170	2,660	0,1181	0,0067	0,1047	61,836	m		
181	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	9,721	m		
182	L605	3,800	0,150	3,500	0,1496	0,0059	0,1378	97,397	m		
183	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
184	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
185	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	3,629	m		
186	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	99,880	m		
187	L605	4,318	0,160	3,998	0,1700	0,0063	0,1574	16,657	m		
188	L605	4,400	0,320	3,760	0,1732	0,0126	0,1480	41,479	m		
189	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	3,030	m		
191	L605	6,000	0,200	5,600	0,2362	0,0079	0,2205	4,011	m		
192	L605	6,240	0,120	6,000	0,2457	0,0047	0,2362	5,526	m		
193	L605	10,000	0,100	25,000	0,3937	0,0039	0,9843	597,000	St		
194	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
195	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
196	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	20,000	m		
197	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
198	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
199	NiTi	0,300	0,085	0,130	0,0118	0,0033	0,0051	7,122	m	ground	Max. 15 °C
200	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	7,270	m	ground	Max. 15 °C
201	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	Max. 15 °C
202	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	53,000	m	ground	Max. 15 °C
203	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	20,754	m	dark oxidized	Max. 15 °C
204	NiTi	0,400	0,060	0,280	0,0157	0,0024	0,0110	97,977	m	dark oxidized	Max. 15 °C
205	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	10,388	m	ground	Max. 15 °C
206	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	46,115	m	ground	Max. 15 °C
207	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	29,574	m	dark oxidized	Max. 15 °C
208	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	16,459	m	polished	Max. 15 °C
209	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	7,315	m	polished	Max. 15 °C
210	NiTi	0,480	0,076	0,328	0,0189	0,0030	0,0129	8,070	m	ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	995,299 m		dark oxidized	Max. 15 °C
212	NiTi	0,559	0,070	0,419	0,0220	0,0028	0,0165	0,345 m		ground	Max. 15 °C
213	NiTi	0,580	0,115	0,350	0,0228	0,0045	0,0138	113,074 m		ground	Max. 15 °C
214	NiTi	0,600	0,080	0,440	0,0236	0,0031	0,0173	0,845 m		ground out-/oxidic inside	Max. 15 °C
215	NiTi	0,635	0,102	0,432	0,0250	0,0040	0,0170	104,188 m		ground	Max. 15 °C
216	NiTi	0,640	0,100	0,440	0,0252	0,0039	0,0173	3,714 m		ground	Max. 15 °C
217	NiTi	0,730	0,100	0,530	0,0287	0,0039	0,0209	49,742 m		ground	Max. 15 °C
218	NiTi	0,900	0,190	0,520	0,0354	0,0075	0,0205	1,481 m		dark oxidized	Max. 15 °C
219	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	620,400 m		dark oxidized	Max. 15 °C
220	NiTi	1,000	0,050	0,900	0,0394	0,0020	0,0354	22,640 m		ground	Max. 15 °C
221	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	26,501 m		ground	Max. 15 °C
222	NiTi	1,200	0,085	1,030	0,0472	0,0033	0,0406	51,000 m		ground	Max. 15 °C
223	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	6,960 m		ground	Max. 15 °C
224	NiTi	1,200	0,125	0,950	0,0472	0,0049	0,0374	1,681 m		ground	Max. 15 °C
225	NiTi	1,200	0,160	0,880	0,0472	0,0063	0,0346	7,585 m		ground out-/oxidic inside	Max. 15 °C
226	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	239,427 m		ground	Max. 15 °C
227	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	163,995 m		ground	Max. 15 °C
228	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	8,648 m		ground	Max. 15 °C
229	NiTi	1,240	0,230	0,780	0,0488	0,0091	0,0307	24,456 m		ground	Max. 15 °C
230	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	31,570 m		ground	Max. 15 °C
231	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,520 m		ground	Max. 15 °C
233	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	36,539 m		ground	Max. 15 °C
234	NiTi	1,300	0,220	0,860	0,0512	0,0087	0,0339	100,153 m		ground	Max. 15 °C
235	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,632 m		ground	Max. 15 °C
236	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898 m		ground	Max. 15 °C
237	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570 m		ground out-/oxidic inside	Max. 15 °C
238	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	21,797 m		ground out-/oxidic inside	Max. 15 °C
239	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	Max. 15 °C
240	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,030 m		ground	Max. 15 °C
241	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	3,250 m		ground	Max. 15 °C
242	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m		ground	Max. 15 °C
243	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,129 m		ground	Max. 15 °C
244	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,410 m		ground	Max. 15 °C
245	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	Max. 15 °C
246	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	Max. 15 °C
247	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	173,217 m		ground	Max. 15 °C
248	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	Max. 15 °C
249	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	Max. 15 °C
250	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,500 m		ground	Max. 15 °C
251	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	Max. 15 °C
252	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	Max. 15 °C
254	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	Max. 15 °C
255	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,948 m		ground	Max. 15 °C
256	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,943 m		ground	Max. 15 °C
257	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	Max. 15 °C
258	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	Max. 15 °C
259	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	40,650 m		ground	Max. 15 °C
260	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	9,410 m		ground	Max. 15 °C
261	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	13,081 m		ground	Max. 15 °C
262	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	3,374 m		ground	Max. 15 °C
263	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	5,157 m		ground	Max. 15 °C
264	NiTi	1,350	0,135	1,080	0,0531	0,0053	0,0425	3,524 m		ground	Max. 15 °C
265	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	10,634 m		ground	Max. 15 °C
266	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	3,394 m		ground	Max. 15 °C
267	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	10,187 m		ground	Max. 15 °C
268	NiTi	1,390	0,130	1,130	0,0547	0,0051	0,0445	5,670 m		ground	Max. 15 °C
269	NiTi	1,422	0,051	1,320	0,0560	0,0020	0,0520	6,259 m		ground	Max. 15 °C
270	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	3,701 m		ground	Max. 15 °C
271	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	1,373 m		ground	Max. 15 °C
272	NiTi	1,524	0,114	1,296	0,0600	0,0045	0,0510	1,000 St		ground	Max. 15 °C
273	NiTi	1,524	0,127	1,270	0,0600	0,0050	0,0500	28,410 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	8,878 m		ground	Max. 15 °C
275	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	1,300 m		ground	Max. 15 °C
276	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080 m		ground out-/oxidic inside	Max. 15 °C
277	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	96,900 m		ground out-/oxidic inside	Max. 15 °C
278	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	14,007 m		ground	Max. 15 °C
279	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,532 m		ground out-/oxidic inside	Max. 15 °C
280	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	22,144 m		ground	Max. 15 °C
281	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	270,135 m		ground out-/oxidic inside	Max. 15 °C
282	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,077 m		ground	Max. 15 °C
283	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	64,425 m		ground	Max. 15 °C
284	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	9,605 m		ground	Max. 15 °C
285	NiTi	1,600	0,474	0,653	0,0630	0,0187	0,0257	7,000 St		ground	Max. 15 °C
286	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	3,490 m		ground	Max. 15 °C
287	NiTi	1,620	0,240	1,140	0,0638	0,0094	0,0449	39,435 m		ground out-/oxidic inside	Max. 15 °C
288	NiTi	1,626	0,140	1,346	0,0640	0,0055	0,0530	9,289 m		ground	Max. 15 °C
289	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000 St		ground	Max. 15 °C
290	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	13,028 m		ground out-/oxidic inside	Max. 15 °C
291	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737 m		ground out-/oxidic inside	Max. 15 °C
292	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970 m		ground out-/oxidic inside	Max. 15 °C
293	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820 m		ground out-/oxidic inside	Max. 15 °C
294	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,170 m		polished	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	3,478 m		ground	Max. 15 °C
296	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609 m		ground	Max. 15 °C
297	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,965 m		ground	Max. 15 °C
298	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,165 m		ground	Max. 15 °C
299	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	181,246 m		ground	Max. 15 °C
300	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279 m		ground	Max. 15 °C
301	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	21,363 m		ground	Max. 15 °C
302	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	3,627 m		ground	Max. 15 °C
303	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	Max. 15 °C
304	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		dark oxidized	Max. 15 °C
305	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	Max. 15 °C
306	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	Max. 15 °C
307	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	Max. 15 °C
308	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	Max. 15 °C
309	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	Max. 15 °C
310	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,980 m		ground	Max. 15 °C
311	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	Max. 15 °C
312	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	Max. 15 °C
313	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	Max. 15 °C
314	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	Max. 15 °C
315	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m	ground	out-/oxidic inside	Max. 15 °C
317	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	255,144 m	ground		Max. 15 °C
318	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,150 m	ground		Max. 15 °C
319	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m	ground		Max. 15 °C
320	NiTi	1,670	0,100	1,470	0,0657	0,0039	0,0579	13,676 m	ground		Max. 15 °C
321	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	24,000 St	ground		Max. 15 °C
322	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	215,668 m	ground	out-/oxidic inside	Max. 15 °C
323	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	287,701 m	ground	out-/oxidic inside	Max. 15 °C
324	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	148,168 m	ground		Max. 15 °C
325	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	36,100 m	ground		Max. 15 °C
326	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m	ground		Max. 15 °C
327	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m	ground		Max. 15 °C
328	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m	ground		Max. 15 °C
329	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m	ground		Max. 15 °C
330	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,323 m	ground		Max. 15 °C
331	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m	ground		Max. 15 °C
332	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m	ground		Max. 15 °C
333	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m	ground		Max. 15 °C
334	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m	ground		Max. 15 °C
335	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,900 m	ground		Max. 15 °C
336	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m	ground		Max. 15 °C

Stock list - Tubescurrent status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	81,630 m		ground	Max. 15 °C
338	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,250 m		ground	Max. 15 °C
339	NiTi	1,778	0,406	0,966	0,0700	0,0160	0,0380	22,252 m		ground	Max. 15 °C
340	NiTi	1,800	0,060	1,680	0,0709	0,0024	0,0661	6,545 m		ground	Max. 15 °C
341	NiTi	1,800	0,070	1,660	0,0709	0,0028	0,0654	17,365 m		ground	Max. 15 °C
342	NiTi	1,800	0,075	1,650	0,0709	0,0030	0,0650	21,481 m		ground	Max. 15 °C
343	NiTi	1,800	0,080	1,640	0,0709	0,0031	0,0646	6,594 m		ground	Max. 15 °C
344	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,273 m		ground	Max. 15 °C
345	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	Max. 15 °C
346	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	62,705 m		ground	Max. 15 °C
347	NiTi	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,779 m		ground	Max. 15 °C
348	NiTi	1,800	0,220	1,360	0,0709	0,0087	0,0535	1,438 m		ground	Max. 15 °C
349	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	10,263 m		ground	Max. 15 °C
350	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	14,726 m		ground	Max. 15 °C
351	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	21,683 m		ground	Max. 15 °C
352	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,716 m		ground	Max. 15 °C
353	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	5,537 m		ground	Max. 15 °C
354	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	9,070 m		ground	Max. 15 °C
355	NiTi	1,900	0,370	1,160	0,0748	0,0146	0,0457	3,832 m		ground	Max. 15 °C
356	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	11,009 m		ground	Max. 15 °C
357	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	113,195 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	1,930	0,305	1,320	0,0760	0,0120	0,0520	113,053 m	ground	out-/oxidic inside	Max. 15 °C
359	NiTi	1,930	0,305	1,320	0,0760	0,0120	0,0520	139,767 m	ground	out-/oxidic inside	Max. 15 °C
360	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	8,969 m	ground		Max. 15 °C
361	NiTi	2,000	0,080	1,840	0,0787	0,0031	0,0724	8,934 m	ground		Max. 15 °C
362	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	156,705 m	ground		Max. 15 °C
363	NiTi	2,000	0,220	1,560	0,0787	0,0087	0,0614	278,514 m	ground		Max. 15 °C
364	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990 m	ground		Max. 15 °C
365	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	27,510 m	ground		Max. 15 °C
366	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467 m	ground		Max. 15 °C
367	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	21,199 m	ground		Max. 15 °C
368	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	36,134 m	ground		Max. 15 °C
369	NiTi	2,019	0,266	1,487	0,0795	0,0105	0,0585	3,728 m	ground		Max. 15 °C
370	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	4,124 m	ground		Max. 15 °C
371	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847 m	ground		Max. 15 °C
372	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	318,700 m	ground		Max. 15 °C
373	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	333,511 m	ground		Max. 15 °C
374	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	411,914 m	ground		Max. 15 °C
375	NiTi	2,032	0,286	1,461	0,0800	0,0113	0,0575	248,800 m	ground		Max. 15 °C
376	NiTi	2,050	0,300	1,450	0,0807	0,0118	0,0571	10,691 m	ground		Max. 15 °C
377	NiTi	2,100	0,250	1,600	0,0827	0,0098	0,0630	14,009 m	ground		Max. 15 °C
378	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	1,089 m	ground		Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	14,305 m		ground	Max. 15 °C
380	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	23,347 m		ground	Max. 15 °C
381	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	34,349 m		ground	Max. 15 °C
382	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	6,506 m		ground	Max. 15 °C
383	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	7,169 m		ground	Max. 15 °C
384	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	130,730 m		ground	Max. 15 °C
385	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	25,753 m		ground	Max. 15 °C
386	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	3,772 m		ground	Max. 15 °C
387	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	341,218 m		ground	Max. 15 °C
388	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	15,602 m		ground	Max. 15 °C
389	NiTi	2,180	0,370	1,440	0,0858	0,0146	0,0567	12,634 m		ground	Max. 15 °C
390	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	1,840 m		ground	Max. 15 °C
391	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	13,550 m		ground	Max. 15 °C
392	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	9,847 m		ground	Max. 15 °C
393	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	8,283 m		ground	Max. 15 °C
394	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,294 m		ground	Max. 15 °C
395	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	33,766 m		ground out-/oxidic inside	Max. 15 °C
396	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	57,200 m		ground out-/oxidic inside	Max. 15 °C
397	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	Max. 15 °C
398	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	25,542 m		ground	Max. 15 °C
399	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	8,472 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,200	0,270	1,660	0,0866	0,0106	0,0654	42,972 m		ground	Max. 15 °C
401	NiTi	2,200	0,325	1,550	0,0866	0,0128	0,0610	2,040 m		ground	Max. 15 °C
402	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	Max. 15 °C
403	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,936 m		ground	Max. 15 °C
404	NiTi	2,286	0,254	1,778	0,0900	0,0100	0,0700	2,821 m		ground	Max. 15 °C
405	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	Max. 15 °C
406	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,624 m		ground	Max. 15 °C
407	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	4,584 m		ground	Max. 15 °C
408	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	Max. 15 °C
409	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	Max. 15 °C
410	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	250,174 m		ground out-/oxidic inside	Max. 15 °C
411	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	Max. 15 °C
412	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	Max. 15 °C
413	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	Max. 15 °C
414	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,800 m		ground out-/oxidic inside	Max. 15 °C
415	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	Max. 15 °C
416	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	Max. 15 °C
417	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	3,010 m		ground	Max. 15 °C
418	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	40,566 m		ground	Max. 15 °C
419	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	8,866 m		ground	Max. 15 °C
420	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	12,818 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	Max. 15 °C
422	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	13,315 m		ground	Max. 15 °C
423	NiTi	2,400	0,085	2,230	0,0945	0,0033	0,0878	3,204 m		ground	Max. 15 °C
424	NiTi	2,400	0,090	2,220	0,0945	0,0035	0,0874	1,894 m		ground	Max. 15 °C
425	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	34,413 m		dark oxidized	Max. 15 °C
426	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	8,635 m		ground	Max. 15 °C
427	NiTi	2,400	0,300	1,800	0,0945	0,0118	0,0709	8,126 m		ground	Max. 15 °C
428	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	11,313 m		ground	Max. 15 °C
429	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	4,644 m		ground	Max. 15 °C
430	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	20,940 m		ground	Max. 15 °C
431	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	1,760 m		dark oxidized	Max. 15 °C
432	NiTi	2,449	0,221	2,007	0,0964	0,0087	0,0790	10,725 m		ground	Max. 15 °C
433	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	2,629 m		ground	Max. 15 °C
434	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	3,920 m		ground	Max. 15 °C
435	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	2,622 m		ground	Max. 15 °C
436	NiTi	2,550	0,180	2,190	0,1004	0,0071	0,0862	12,734 m		ground	Max. 15 °C
437	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	13,249 m		ground	Max. 15 °C
438	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	2,999 m		ground out-/oxidic inside	Max. 15 °C
439	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,577 m		ground	Max. 15 °C
440	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526 m		ground	Max. 15 °C
441	NiTi	2,590	0,076	2,438	0,1020	0,0030	0,0960	2,188 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	2,600	0,510	1,580	0,1024	0,0201	0,0622	112,705 m		ground	Max. 15 °C
443	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	74,601 m		ground	Max. 15 °C
444	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	41,055 m		ground	Max. 15 °C
445	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,811 m		ground	Max. 15 °C
446	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	59,796 m		ground	Max. 15 °C
447	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,617 m		ground	Max. 15 °C
448	NiTi	2,667	0,241	2,185	0,1050	0,0095	0,0860	1,780 m		ground	Max. 15 °C
449	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	4,405 m		ground	Max. 15 °C
450	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022 m		ground	Max. 15 °C
451	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,177 m		ground	Max. 15 °C
452	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	1,143 m		ground	Max. 15 °C
453	NiTi	2,720	0,170	2,380	0,1071	0,0067	0,0937	1,592 m		ground	Max. 15 °C
454	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	10,281 m		ground	Max. 15 °C
455	NiTi	2,760	0,190	2,380	0,1087	0,0075	0,0937	4,993 m		ground	Max. 15 °C
456	NiTi	2,800	0,230	2,340	0,1102	0,0091	0,0921	5,786 m		ground	Max. 15 °C
457	NiTi	2,800	0,300	2,200	0,1102	0,0118	0,0866	8,406 m		ground	Max. 15 °C
458	NiTi	2,819	0,371	2,077	0,1110	0,0146	0,0818	7,000 m	St	ground	Max. 15 °C
459	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	13,868 m		ground	Max. 15 °C
460	NiTi	3,000	0,250	2,500	0,1181	0,0098	0,0984	7,777 m		ground	Max. 15 °C
461	NiTi	3,030	0,233	2,564	0,1193	0,0092	0,1009	3,028 m		ground	Max. 15 °C
462	NiTi	3,048	0,241	2,566	0,1200	0,0095	0,1010	14,362 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	3,160	0,170	2,820	0,1244	0,0067	0,1110	9,239 m		ground	Max. 15 °C
464	NiTi	3,200	0,150	2,900	0,1260	0,0059	0,1142	5,731 m		ground	Max. 15 °C
465	NiTi	3,200	0,300	2,600	0,1260	0,0118	0,1024	5,967 m		ground	Max. 15 °C
466	NiTi	3,280	0,115	3,050	0,1291	0,0045	0,1201	5,050 m		ground	Max. 15 °C
467	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,471 m		ground out-/oxidic inside	Max. 15 °C
468	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,757 m		ground out-/oxidic inside	Max. 15 °C
469	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	11,977 m		ground	Max. 15 °C
470	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	52,816 m		ground	Max. 15 °C
471	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,471 m		ground	Max. 15 °C
472	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	1,583 m		ground	Max. 15 °C
473	NiTi	3,400	0,250	2,900	0,1339	0,0098	0,1142	6,000	St	ground	Max. 15 °C
474	NiTi	3,404	0,458	2,489	0,1340	0,0180	0,0980	8,009 m		ground	Max. 15 °C
475	NiTi	3,500	0,075	3,350	0,1378	0,0030	0,1319	15,571 m		ground	Max. 15 °C
476	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	11,028 m		ground	Max. 15 °C
477	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	24,325 m		ground	Max. 15 °C
478	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	8,819 m		ground	Max. 15 °C
479	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610 m		ground	Max. 15 °C
480	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	1,722 m		ground	Max. 15 °C
481	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	4,241 m		ground	Max. 15 °C
482	NiTi	3,500	0,440	2,620	0,1378	0,0173	0,1031	5,308 m		ground	Max. 15 °C
483	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	1,152 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	4,613 m		ground	Max. 15 °C
485	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	5,000 m		ground	Max. 15 °C
486	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	86,426 m		ground	Max. 15 °C
487	NiTi	4,000	0,250	3,500	0,1575	0,0098	0,1378	1,343 m			min. 55 °C
488	NiTi	4,000	0,640	2,720	0,1575	0,0252	0,1071	7,618 m		ground	Max. 15 °C
489	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	3,628 m		ground	Max. 15 °C
490	NiTi	4,250	0,065	4,120	0,1673	0,0026	0,1622	4,333 m		polished	Max. 15 °C
491	NiTi	4,270	0,079	4,112	0,1681	0,0031	0,1619	4,942 m		ground	Max. 15 °C
492	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	1,836 m		ground	Max. 15 °C
493	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	9,987 m		ground	Max. 15 °C
494	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,597 m		ground	Max. 15 °C
495	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	2,905 m		ground	Max. 15 °C
496	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	2,707 m		ground	Max. 15 °C
497	NiTi	4,910	0,213	4,484	0,1933	0,0084	0,1765	13,000 m		ground	Max. 15 °C
498	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	5,320 m		polished	Max. 15 °C
499	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	Max. 15 °C
500	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,306 m		ground	Max. 15 °C
501	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	29,886 m		ground out-/oxidic inside	Max. 15 °C
502	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	Max. 15 °C
503	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	Max. 15 °C
504	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	Max. 15 °C
506	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	54,498 m		ground out-/oxidic inside	Max. 15 °C
507	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	Max. 15 °C
508	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	Max. 15 °C
509	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	93,614 m		ground out-/oxidic inside	Max. 15 °C
510	NiTi	4,980	0,280	4,420	0,1961	0,0110	0,1740	3,032 m		ground	Max. 15 °C
511	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	2,510 m		ground	Max. 15 °C
512	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	4,970 m		ground	Max. 15 °C
513	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	6,919 m		ground	Max. 15 °C
514	NiTi	5,000	0,240	4,520	0,1969	0,0094	0,1780	8,708 m		ground	Max. 15 °C
515	NiTi	5,000	0,250	4,500	0,1969	0,0098	0,1772	5,870 m		ground	Max. 15 °C
516	NiTi	5,000	0,500	4,000	0,1969	0,0197	0,1575	4,140 m		ground	Max. 15 °C
517	NiTi	5,004	0,533	3,938	0,1970	0,0210	0,1550	2,263 m		ground out-/oxidic inside	Max. 15 °C
518	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	Max. 15 °C
519	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434 m		ground	Max. 15 °C
520	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	13,368 m		ground	Max. 15 °C
521	NiTi	5,150	0,100	4,950	0,2028	0,0039	0,1949	3,189 m		ground	Max. 15 °C
522	NiTi	5,207	0,279	4,649	0,2050	0,0110	0,1830	1,400 m		ground	Max. 15 °C
523	NiTi	5,500	0,215	5,070	0,2165	0,0085	0,1996	9,046 m		ground	Max. 15 °C
524	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	3,553 m		ground	Max. 15 °C
525	NiTi	5,944	0,572	4,800	0,2340	0,0225	0,1890	1,250 m		ground out-/oxidic inside	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
526	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,110 m		ground out-/oxidic inside	Max. 15 °C
527	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	14,190 m		ground out-/oxidic inside	Max. 15 °C
528	NiTi	5,994	0,537	4,920	0,2360	0,0211	0,1937	22,649 m		ground	Max. 15 °C
529	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,525 m		ground	Max. 15 °C
530	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	7,512 m		ground	Max. 15 °C
531	NiTi	6,000	0,064	5,872	0,2362	0,0025	0,2312	4,982 m		ground	Max. 15 °C
532	NiTi	6,000	0,400	5,200	0,2362	0,0157	0,2047	2,214 m		ground	Max. 15 °C
533	NiTi	6,000	0,500	5,000	0,2362	0,0197	0,1969	5,585 m		ground	Max. 15 °C
534	NiTi	6,300	0,200	5,900	0,2480	0,0079	0,2323	20,245 m		ground	Max. 15 °C
535	NiTi	6,700	0,250	6,200	0,2638	0,0098	0,2441	3,726 m		ground	Max. 15 °C
536	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	1,287 m		ground	Max. 15 °C
537	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	6,967 m		ground	Max. 15 °C
538	NiTi	7,000	0,470	6,060	0,2756	0,0185	0,2386	1,631 m		ground	Max. 15 °C
539	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	3,517 m		ground	Max. 15 °C
540	NiTi	7,000	0,500	6,000	0,2756	0,0197	0,2362	8,803 m		ground	Max. 15 °C
541	NiTi	7,000	0,533	5,934	0,2756	0,0210	0,2336	4,091 m		ground	Max. 15 °C
542	NiTi	7,150	0,100	6,950	0,2815	0,0039	0,2736	11,141 m		ground	Max. 15 °C
543	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	5,777 m		ground	Max. 15 °C
544	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,130 m		ground	Max. 15 °C
545	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,570 m		ground	Max. 15 °C
546	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	9,837 m		ground	Max. 15 °C

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
547	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	10,851 m		ground	Max. 15 °C
548	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	4,550 m		ground	Max. 15 °C
549	NiTi	8,000	0,650	6,700	0,3150	0,0256	0,2638	1,623 m		polished	Max. 15 °C
550	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,645 m		ground	Max. 15 °C
551	NiTi	8,500	0,220	8,060	0,3346	0,0087	0,3173	3,458 m		ground	Max. 15 °C
552	NiTi	8,800	0,550	7,700	0,3465	0,0217	0,3031	1,297 m		ground	Max. 15 °C
553	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	20,069 m		ground	Max. 15 °C
554	NiTi	10,000	0,460	9,080	0,3937	0,0181	0,3575	3,470 m		ground	Max. 15 °C
555	NiTi	10,000	0,480	9,040	0,3937	0,0189	0,3559	10,436 m		ground	Max. 15 °C
556	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	4,497 m		ground	Max. 15 °C
557	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	5,514 m		ground	Max. 15 °C
558	NiTi	10,000	0,520	8,960	0,3937	0,0205	0,3528	1,217 m		ground	Max. 15 °C
559	NiTi	10,000	0,550	8,900	0,3937	0,0217	0,3504	5,891 m		ground	Max. 15 °C
560	NiTi	10,000	0,670	8,660	0,3937	0,0264	0,3409	3,410 m		ground	Max. 15 °C
561	NiTi	10,000	0,720	8,560	0,3937	0,0283	0,3370	1,869 m		ground	Max. 15 °C
562	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	1,050 m		ground	Max. 15 °C
563	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	13,864 m		ground	Max. 15 °C
564	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	2,854 m		ground	Max. 15 °C
565	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	6,601 m		ground	Max. 15 °C
566	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	8,806 m		ground	Max. 15 °C
567	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034 m			

Stock list - Tubes

current status: **21.07.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east USA: Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA: or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
568	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	2,207	m		
569	Tantal	1,800	0,210	1,380	0,0709	0,0083	0,0543	1,016	m		
570	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	4,677	m		
571	Tantal	4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647	m		
572	Tantal	4,900	0,500	3,900	0,1929	0,0197	0,1535	3,529	m		
573	Tantal-Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162	m		
574	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210	m	ground	
575	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480	m	ground	
576	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310	m		
577	Titan Gr. 2	0,820	0,156	0,508	0,0323	0,0061	0,0200	75,749	m		
578	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	664,655	m		
579	Titan Gr. 2	1,225	0,050	1,125	0,0482	0,0020	0,0443	46,511	m		
580	Titan Gr. 2	1,250	0,100	1,050	0,0492	0,0039	0,0413	62,150	m	ground	
581	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,806	m		
582	Titan Gr. 2	2,350	0,500	1,350	0,0925	0,0197	0,0531	2,800	m		
583	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490	m		
584	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670	m		
585	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
586	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
587	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		
588	Titan Gr. 2	7,925	0,889	6,147	0,3120	0,0350	0,2420	5,980	m		