

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
1	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	12,000	m		
2	1.4301 (304)	1,372	0,305	0,762	0,0540	0,0120	0,0300	20,000	m		
3	1.4301 (304)	2,000	0,400	1,200	0,0787	0,0157	0,0472	41,199	m		
4	1.4301 (304)	2,515	0,051	2,413	0,0990	0,0020	0,0950	9,000	St		
5	1.4301 (304)	4,470	0,435	3,600	0,1760	0,0171	0,1417	4,000	St		
6	1.4301 (304)	5,700	0,500	4,700	0,2244	0,0197	0,1850	7,503	m		
7	1.4301 (304)	6,700	0,500	5,700	0,2638	0,0197	0,2244	11,650	m		
8	1.4301 (304)	6,900	2,300	2,300	0,2717	0,0906	0,0906	6,300	m		
9	1.4301 (304)	9,700	0,500	8,700	0,3819	0,0197	0,3425	8,710	m		
10	1.4307	6,300	0,275	5,750	0,2480	0,0108	0,2264	9,149	m		
11	1.4452 (P 2000)	1,600	0,090	1,420	0,0630	0,0035	0,0559	9,650	m		
12	1.4452 (P 2000)	1,600	0,150	1,300	0,0630	0,0059	0,0512	7,884	m		
13	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	13,102	m		
14	1.4452 (P 2000)	1,800	0,090	1,620	0,0709	0,0035	0,0638	31,775	m		
15	1.4452 (P 2000)	4,572	0,152	4,268	0,1800	0,0060	0,1680	20,530	m		
16	1.4541	9,576	0,114	9,348	0,3770	0,0045	0,3680	17,005	m		
17	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	14,722	m		
18	1.4541	9,750	0,100	9,550	0,3839	0,0039	0,3760	24,000	m		
19	1.4550	10,140	0,220	9,700	0,3992	0,0087	0,3819	14,000	St		
20	1.4568	0,690	0,125	0,440	0,0272	0,0049	0,0173	7,854	m		
21	1.4568	2,108	0,203	1,702	0,0830	0,0080	0,0670	21,630	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
22	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	14,610	m		
23	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	18,335	m		
24	1.4568	7,214	0,381	6,452	0,2840	0,0150	0,2540	23,560	m		
25	1.4568	9,500	0,254	8,992	0,3740	0,0100	0,3540	6,304	m		
26	1.4568	9,647	0,342	8,963	0,3798	0,0135	0,3529	9,570	m		
27	1.4568	9,667	0,249	9,169	0,3806	0,0098	0,3610	2,009	m		
28	1.4568	10,313	0,342	9,629	0,4060	0,0135	0,3791	3,202	m		
29	1.4571	5,600	0,150	5,300	0,2205	0,0059	0,2087	278,000	St		
30	1.4571	5,950	0,150	5,700	0,2343	0,0059	0,2244	222,000	St		
31	1.4571	9,000	0,400	8,200	0,3543	0,0157	0,3228	19,500	m		
32	316L	0,550	0,100	0,350	0,0217	0,0039	0,0138	33,244	m		
33	316L	0,640	0,095	0,450	0,0252	0,0037	0,0177	185,000	m		
34	316L	1,540	0,090	1,360	0,0606	0,0035	0,0535	13,152	m		
35	316L	1,800	0,125	1,550	0,0709	0,0049	0,0610	15,422	m		
36	316L	3,200	0,300	2,600	0,1260	0,0118	0,1024	13,621	m		
37	316L	4,217	0,140	3,937	0,1660	0,0055	0,1550	3,140	m		
38	316L	5,300	0,300	4,700	0,2087	0,0118	0,1850	159,000	St		
39	316L	5,550	0,175	5,200	0,2185	0,0069	0,2047	359,805	m		
40	316LVM	0,292	0,050	0,192	0,0115	0,0020	0,0076	112,836	m		
41	316LVM	0,450	0,100	0,250	0,0177	0,0039	0,0098	66,520	m		
42	316LVM	0,521	0,038	0,445	0,0205	0,0015	0,0175	37,000	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
43	316LVM	0,550	0,075	0,400	0,0217	0,0030	0,0157	26,114	m		
44	316LVM	0,650	0,175	0,300	0,0256	0,0069	0,0118	14,644	m		
45	316LVM	0,700	0,100	0,500	0,0276	0,0039	0,0197	42,246	m		
46	316LVM	0,889	0,140	0,610	0,0350	0,0055	0,0240	35,800	m		
47	316LVM	0,950	0,200	0,550	0,0374	0,0079	0,0217	38,024	m		
48	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	45,981	m		
49	316LVM	0,975	0,078	0,820	0,0384	0,0031	0,0323	72,562	m		
50	316LVM	0,990	0,075	0,840	0,0390	0,0030	0,0331	13,188	m		
51	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	20,960	m		
52	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	64,256	m		
53	316LVM	1,100	0,150	0,800	0,0433	0,0059	0,0315	67,374	m		
54	316LVM	1,400	0,130	1,140	0,0551	0,0051	0,0449	45,402	m		
55	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	18,550	m		
56	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	22,130	m		
57	316LVM	1,700	0,100	1,500	0,0669	0,0039	0,0591	3,450	m		
58	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	2,986	m		
59	316LVM	1,700	0,450	0,800	0,0669	0,0177	0,0315	9,464	m		
60	316LVM	1,753	0,039	1,675	0,0690	0,0015	0,0659	14,026	m		
61	316LVM	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,544	m		
62	316LVM	1,800	0,125	1,550	0,0709	0,0049	0,0610	11,761	m		
63	316LVM	1,800	0,150	1,500	0,0709	0,0059	0,0591	13,998	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
64	316LVM	1,800	0,200	1,400	0,0709	0,0079	0,0551	19,724	m		
65	316LVM	1,930	0,196	1,538	0,0760	0,0077	0,0606	47,700	m		
66	316LVM	2,100	0,100	1,900	0,0827	0,0039	0,0748	18,853	m		
67	316LVM	2,515	0,058	2,400	0,0990	0,0023	0,0945	19,953	m		
68	316LVM	3,000	0,400	2,200	0,1181	0,0157	0,0866	6,230	m		
69	316LVM	3,100	0,100	2,900	0,1220	0,0039	0,1142	59,721	m		
70	316LVM	3,500	0,500	2,500	0,1378	0,0197	0,0984	7,490	m		
71	316LVM	3,759	0,254	3,251	0,1480	0,0100	0,1280	39,148	m		
72	316LVM	4,000	0,090	3,820	0,1575	0,0035	0,1504	8,373	m		
73	316LVM	4,551	0,218	4,115	0,1792	0,0086	0,1620	6,483	m		
74	316LVM	4,572	0,229	4,114	0,1800	0,0090	0,1620	63,638	m		
75	316LVM	4,650	0,090	4,470	0,1831	0,0035	0,1760	16,278	m		
76	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	11,683	m		
77	316LVM	4,763	0,229	4,305	0,1875	0,0090	0,1695	19,984	m		
78	316LVM	5,000	0,250	4,500	0,1969	0,0098	0,1772	10,890	m		
79	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	10,340	m		
80	316LVM	5,840	0,140	5,560	0,2299	0,0055	0,2189	45,880	m		
81	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	19,306	m		
82	316LVM	5,860	0,150	5,560	0,2307	0,0059	0,2189	21,650	m		
83	316LVM	5,960	0,200	5,560	0,2346	0,0079	0,2189	21,000	m		
84	316LVM	6,000	0,279	5,442	0,2362	0,0110	0,2143	0,648	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
85	316LVM	6,000	0,300	5,400	0,2362	0,0118	0,2126	32,702	m		
86	316LVM	6,198	0,229	5,740	0,2440	0,0090	0,2260	9,680	m		
87	316LVM	6,350	2,197	1,956	0,2500	0,0865	0,0770	1,596	m		
88	316LVM	7,938	0,261	7,417	0,3125	0,0103	0,2920	8,287	m		
89	316LVM	7,940	0,710	6,520	0,3126	0,0280	0,2567	11,030	m		
90	316LVM	8,000	0,150	7,700	0,3150	0,0059	0,3031	4,290	m		
91	316LVM	8,000	0,216	7,568	0,3150	0,0085	0,2980	6,251	m		
92	316LVM	9,525	0,513	8,500	0,3750	0,0202	0,3346	7,608	m		
93	Biodur 108	1,220	0,075	1,070	0,0480	0,0030	0,0421	7,542	m		
94	KC35N LT	0,270	0,025	0,220	0,0106	0,0010	0,0087	52,377	m		
95	KC35N LT	0,356	0,102	0,152	0,0140	0,0040	0,0060	27,000	St		
96	KC35N LT	0,368	0,083	0,203	0,0145	0,0033	0,0080	29,000	St		
97	KC35N LT	0,450	0,125	0,200	0,0177	0,0049	0,0079	39,137	m		
98	KC35N LT	0,510	0,050	0,410	0,0201	0,0020	0,0161	2,100	m		
99	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	2290,000	St		
100	KC35N LT	0,520	0,050	0,420	0,0205	0,0020	0,0165	915,000	St		
101	KC35N LT	0,600	0,100	0,400	0,0236	0,0039	0,0157	47,100	m		
102	KC35N LT	0,730	0,115	0,500	0,0287	0,0045	0,0197	5,666	m		
103	KC35N LT	0,960	0,050	0,860	0,0378	0,0020	0,0339	63,482	m		
104	KC35N LT	1,107	0,086	0,935	0,0436	0,0034	0,0368	28,602	m		
105	KC35N LT	1,240	0,070	1,100	0,0488	0,0028	0,0433	19,985	m		

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
106	KC35N LT	1,350	0,075	1,200	0,0531	0,0030	0,0472	57,510	m		
107	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	19,350	m		
108	KC35N LT	1,400	0,100	1,200	0,0551	0,0039	0,0472	55,750	m		
109	KC35N LT	1,600	0,105	1,390	0,0630	0,0041	0,0547	6,685	m		
110	KC35N LT	1,800	0,115	1,570	0,0709	0,0045	0,0618	0,836	m		
111	KC35N LT	2,134	0,102	1,930	0,0840	0,0040	0,0760	20,870	m		
112	KC35N LT	2,311	0,102	2,107	0,0910	0,0040	0,0830	28,500	m		
113	KC35N LT	2,350	0,150	2,050	0,0925	0,0059	0,0807	22,407	m		
114	KC35N LT	2,375	0,089	2,197	0,0935	0,0035	0,0865	1,492	m		
115	KC35N LT	2,400	0,114	2,172	0,0945	0,0045	0,0855	11,820	m		
116	KC35N LT	3,500	0,090	3,320	0,1378	0,0035	0,1307	17,303	m		
117	KC35N LT	4,200	0,100	4,000	0,1654	0,0039	0,1575	4,210	m		
118	KC35N LT	4,720	0,304	4,112	0,1858	0,0120	0,1619	50,256	m		
119	KC35N LT	5,588	0,229	5,130	0,2200	0,0090	0,2020	9,819	m		
120	KC35N LT	6,000	0,500	5,000	0,2362	0,0197	0,1969	12,940	m		
121	KC35N LT	6,400	0,075	6,250	0,2520	0,0030	0,2461	6,038	m		
122	KC35N LT	7,214	0,381	6,452	0,2840	0,0150	0,2540	3,910	m		
123	L605	0,510	0,105	0,300	0,0201	0,0041	0,0118	37,340	m		
124	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	30,988	m		
125	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	354,000	St		
126	L605	0,630	0,100	0,430	0,0248	0,0039	0,0169	42,956	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
127	L605	0,720	0,130	0,460	0,0283	0,0051	0,0181	16,160	m		
128	L605	0,762	0,127	0,508	0,0300	0,0050	0,0200	38,452	m		
129	L605	1,070	0,140	0,790	0,0421	0,0055	0,0311	7,451	m		
130	L605	1,169	0,102	0,965	0,0460	0,0040	0,0380	15,914	m		
131	L605	1,219	0,127	0,965	0,0480	0,0050	0,0380	45,448	m		
132	L605	1,320	0,081	1,158	0,0520	0,0032	0,0456	3,444	m		
133	L605	1,321	0,127	1,067	0,0520	0,0050	0,0420	28,800	m		
134	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	6,131	m		
135	L605	1,400	0,110	1,180	0,0551	0,0043	0,0465	7,686	m		
136	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	16,570	m		
137	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	23,280	m		
138	L605	1,470	0,110	1,250	0,0579	0,0043	0,0492	28,770	m		
139	L605	1,470	0,130	1,210	0,0579	0,0051	0,0476	36,860	m		
140	L605	1,473	0,127	1,219	0,0580	0,0050	0,0480	26,210	m		
141	L605	1,550	0,100	1,350	0,0610	0,0039	0,0531	144,000	m		
142	L605	1,600	0,065	1,470	0,0630	0,0026	0,0579	1,377	m		
143	L605	1,600	0,080	1,440	0,0630	0,0031	0,0567	16,816	m		
144	L605	1,600	0,090	1,420	0,0630	0,0035	0,0559	5,355	m		
145	L605	1,600	0,100	1,400	0,0630	0,0039	0,0551	1,510	m		
146	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	189,788	m		
147	L605	1,600	0,110	1,380	0,0630	0,0043	0,0543	24,460	m		

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
148	L605	1,600	0,140	1,320	0,0630	0,0055	0,0520	16,140	m		
149	L605	1,650	0,230	1,190	0,0650	0,0091	0,0469	19,532	m		
150	L605	1,800	0,065	1,670	0,0709	0,0026	0,0657	23,271	m		
151	L605	1,800	0,085	1,630	0,0709	0,0033	0,0642	12,490	m		
152	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	174,000	m		
153	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	21,400	m		
154	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	27,300	m		
155	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	66,860	m		
156	L605	1,800	0,090	1,620	0,0709	0,0035	0,0638	9,339	m		
157	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	14,921	m		
158	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	46,200	m		
159	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,080	m		
160	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,175	m		
161	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	5,870	m		
162	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	67,000	St		
163	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,550	m		
164	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	7,798	m		
165	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	8,700	m		
166	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	85,255	m		
167	L605	1,800	0,100	1,600	0,0709	0,0039	0,0630	9,474	m		
168	L605	1,800	0,104	1,592	0,0709	0,0041	0,0627	128,291	m		

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
169	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	107,761	m		
170	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	18,580	m		
171	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	431,611	m		
172	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	531,472	m		
173	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	560,000	m		
174	L605	1,800	0,110	1,580	0,0709	0,0043	0,0622	96,116	m		
175	L605	1,800	0,190	1,420	0,0709	0,0075	0,0559	8,711	m		
176	L605	1,880	0,127	1,626	0,0740	0,0050	0,0640	32,710	m		
177	L605	2,000	0,110	1,780	0,0787	0,0043	0,0701	46,013	m		
178	L605	3,000	0,500	2,000	0,1181	0,0197	0,0787	9,721	m		
179	L605	3,800	0,150	3,500	0,1496	0,0059	0,1378	97,397	m		
180	L605	3,850	0,170	3,510	0,1516	0,0067	0,1382	15,284	m		
181	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	106,600	m		
182	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	19,472	m		
183	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	2,296	m		
184	L605	4,000	0,400	3,200	0,1575	0,0157	0,1260	99,880	m		
185	L605	4,318	0,160	3,998	0,1700	0,0063	0,1574	16,657	m		
186	L605	4,400	0,320	3,760	0,1732	0,0126	0,1480	41,479	m		
187	L605	4,550	0,180	4,190	0,1791	0,0071	0,1650	3,919	m		
188	L605	4,700	0,180	4,340	0,1850	0,0071	0,1709	1,040	m		
189	L605	5,000	0,100	4,800	0,1969	0,0039	0,1890	1,530	m		

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
190	L605	5,500	0,210	5,080	0,2165	0,0083	0,2000	11,914	m		
191	L605	6,000	0,200	5,600	0,2362	0,0079	0,2205	4,011	m		
192	L605	6,240	0,120	6,000	0,2457	0,0047	0,2362	5,526	m		
193	L605	9,647	0,342	8,963	0,3798	0,0135	0,3529	4,630	m		
194	L605	10,000	0,100	25,000	0,3937	0,0039	0,9843	385,000	St		
195	Mu-Metal	0,680	0,100	0,480	0,0268	0,0039	0,0189	34,020	m		
196	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	1650,000	St		
197	Mu-Metal	1,422	0,076	1,270	0,0560	0,0030	0,0500	20,000	m		
198	Mu-Metal	3,226	0,051	3,124	0,1270	0,0020	0,1230	18,660	m		
199	Mu-Metal	3,277	0,076	3,124	0,1290	0,0030	0,1230	54,360	m		
200	NiTi	0,330	0,115	0,100	0,0130	0,0045	0,0039	7,270	m	ground	Max. 15 °C
201	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	11,000	m	ground	Max. 15 °C
202	NiTi	0,345	0,110	0,125	0,0136	0,0043	0,0049	53,000	m	ground	Max. 15 °C
203	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	10,388	m	ground	Max. 15 °C
204	NiTi	0,400	0,150	0,100	0,0157	0,0059	0,0039	46,115	m	ground	Max. 15 °C
205	NiTi	0,450	0,070	0,310	0,0177	0,0028	0,0122	28,074	m	dark oxidized	Max. 15 °C
206	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	16,459	m	polished	Max. 15 °C
207	NiTi	0,457	0,076	0,305	0,0180	0,0030	0,0120	3,658	m	polished	Max. 15 °C
208	NiTi	0,480	0,076	0,328	0,0189	0,0030	0,0129	8,070	m	ground	Max. 15 °C
209	NiTi	0,500	0,075	0,350	0,0197	0,0030	0,0138	664,696	m	dark oxidized	Max. 15 °C
210	NiTi	0,580	0,115	0,350	0,0228	0,0045	0,0138	113,074	m	ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
211	NiTi	0,635	0,102	0,432	0,0250	0,0040	0,0170	100,903	m	ground	Max. 15 °C
212	NiTi	0,660	0,076	0,508	0,0260	0,0030	0,0200	16,000	St	ground	Max. 15 °C
213	NiTi	0,730	0,100	0,530	0,0287	0,0039	0,0209	49,742	m	ground	Max. 15 °C
214	NiTi	0,940	0,080	0,780	0,0370	0,0031	0,0307	620,400	m	dark oxidized	Max. 15 °C
215	NiTi	1,000	0,050	0,900	0,0394	0,0020	0,0354	20,640	m	ground	Max. 15 °C
216	NiTi	1,180	0,146	0,889	0,0465	0,0057	0,0350	26,501	m	ground	Max. 15 °C
217	NiTi	1,200	0,085	1,030	0,0472	0,0033	0,0406	49,800	m	ground	Max. 15 °C
218	NiTi	1,200	0,100	1,000	0,0472	0,0039	0,0394	4,920	m	ground	Max. 15 °C
219	NiTi	1,220	0,133	0,954	0,0480	0,0052	0,0376	239,427	m	ground	Max. 15 °C
220	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	158,813	m	ground	Max. 15 °C
221	NiTi	1,230	0,220	0,790	0,0484	0,0087	0,0311	8,648	m	ground	Max. 15 °C
222	NiTi	1,240	0,230	0,780	0,0488	0,0091	0,0307	21,245	m	ground	Max. 15 °C
223	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	31,570	m	ground	Max. 15 °C
224	NiTi	1,269	0,152	0,965	0,0500	0,0060	0,0380	4,716	m	ground	Max. 15 °C
225	NiTi	1,300	0,168	0,964	0,0512	0,0066	0,0380	2,520	m	ground	Max. 15 °C
226	NiTi	1,300	0,170	0,960	0,0512	0,0067	0,0378	36,539	m	ground	Max. 15 °C
227	NiTi	1,300	0,220	0,860	0,0512	0,0087	0,0339	86,088	m	ground	Max. 15 °C
228	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	516,632	m	ground	Max. 15 °C
229	NiTi	1,320	0,180	0,960	0,0520	0,0071	0,0378	63,898	m	ground	Max. 15 °C
230	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	19,570	m	ground out-/oxidic inside	Max. 15 °C
231	NiTi	1,320	0,200	0,920	0,0520	0,0079	0,0362	21,797	m	ground out-/oxidic inside	Max. 15 °C

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
232	NiTi	1,320	0,210	0,900	0,0520	0,0083	0,0354	7,436 m		ground	Max. 15 °C
233	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	1,668 m		ground	Max. 15 °C
234	NiTi	1,320	0,215	0,890	0,0520	0,0085	0,0350	10,030 m		ground	Max. 15 °C
235	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	13,900 m		ground	Max. 15 °C
236	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,129 m		ground	Max. 15 °C
237	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	14,410 m		ground	Max. 15 °C
238	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	15,000 m		ground	Max. 15 °C
239	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	16,090 m		ground	Max. 15 °C
240	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	173,217 m		ground	Max. 15 °C
241	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	18,000 m		ground	Max. 15 °C
242	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	20,800 m		ground	Max. 15 °C
243	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	21,500 m		ground	Max. 15 °C
244	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	27,020 m		ground	Max. 15 °C
245	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	29,625 m		ground	Max. 15 °C
246	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,380 m		ground	Max. 15 °C
247	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,710 m		ground	Max. 15 °C
248	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	3,948 m		ground	Max. 15 °C
249	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	37,943 m		ground	Max. 15 °C
250	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	39,549 m		ground	Max. 15 °C
251	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,200 m		ground	Max. 15 °C
252	NiTi	1,320	0,225	0,870	0,0520	0,0089	0,0343	4,276 m		ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
253	NiTi	1,320	0,235	0,850	0,0520	0,0093	0,0335	8,103 m		ground	Max. 15 °C
254	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	2,584 m		ground	Max. 15 °C
255	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	3,374 m		ground	Max. 15 °C
256	NiTi	1,350	0,120	1,110	0,0531	0,0047	0,0437	7,225 m		ground	Max. 15 °C
257	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	10,634 m		ground	Max. 15 °C
258	NiTi	1,370	0,205	0,960	0,0539	0,0081	0,0378	3,394 m		ground	Max. 15 °C
259	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	-5,524 m		ground	Max. 15 °C
260	NiTi	1,390	0,120	1,150	0,0547	0,0047	0,0453	10,187 m		ground	Max. 15 °C
261	NiTi	1,390	0,130	1,130	0,0547	0,0051	0,0445	5,670 m		ground	Max. 15 °C
262	NiTi	1,448	0,191	1,066	0,0570	0,0075	0,0420	3,701 m		ground	Max. 15 °C
263	NiTi	1,500	0,250	1,000	0,0591	0,0098	0,0394	1,373 m		ground	Max. 15 °C
264	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	7,028 m		ground	Max. 15 °C
265	NiTi	1,524	0,279	0,966	0,0600	0,0110	0,0380	7,383 m		ground	Max. 15 °C
266	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	1,300 m		ground	Max. 15 °C
267	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	55,080 m		ground out-/oxidic inside	Max. 15 °C
268	NiTi	1,550	0,200	1,150	0,0610	0,0079	0,0453	96,900 m		ground out-/oxidic inside	Max. 15 °C
269	NiTi	1,550	0,250	1,050	0,0610	0,0098	0,0413	14,007 m		ground	Max. 15 °C
270	NiTi	1,590	0,215	1,160	0,0626	0,0085	0,0457	28,532 m		ground out-/oxidic inside	Max. 15 °C
271	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	22,144 m		ground	Max. 15 °C
272	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	243,816 m		ground out-/oxidic inside	Max. 15 °C
273	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	270,135 m		ground out-/oxidic inside	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
274	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	306,800	m	ground out-/oxidic inside	Max. 15 °C
275	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	6,077	m	ground	Max. 15 °C
276	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	64,425	m	ground	Max. 15 °C
277	NiTi	1,600	0,260	1,080	0,0630	0,0102	0,0425	9,605	m	ground	Max. 15 °C
278	NiTi	1,600	0,474	0,653	0,0630	0,0187	0,0257	7,000	St	ground	Max. 15 °C
279	NiTi	1,605	0,220	1,165	0,0632	0,0087	0,0459	3,490	m	ground	Max. 15 °C
280	NiTi	1,620	0,240	1,140	0,0638	0,0094	0,0449	39,435	m	ground out-/oxidic inside	Max. 15 °C
281	NiTi	1,626	0,140	1,346	0,0640	0,0055	0,0530	9,289	m	ground	Max. 15 °C
282	NiTi	1,626	0,241	1,144	0,0640	0,0095	0,0450	100,000	St	ground	Max. 15 °C
283	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	10,817	m	ground out-/oxidic inside	Max. 15 °C
284	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	20,737	m	ground out-/oxidic inside	Max. 15 °C
285	NiTi	1,630	0,220	1,190	0,0642	0,0087	0,0469	4,970	m	ground out-/oxidic inside	Max. 15 °C
286	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	3,820	m	ground out-/oxidic inside	Max. 15 °C
287	NiTi	1,630	0,225	1,180	0,0642	0,0089	0,0465	7,170	m	polished	Max. 15 °C
288	NiTi	1,630	0,230	1,170	0,0642	0,0091	0,0461	3,478	m	ground	Max. 15 °C
289	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	10,609	m	ground	Max. 15 °C
290	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	13,965	m	ground	Max. 15 °C
291	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	18,165	m	ground	Max. 15 °C
292	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	181,246	m	ground	Max. 15 °C
293	NiTi	1,630	0,235	1,160	0,0642	0,0093	0,0457	55,279	m	ground	Max. 15 °C
294	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	21,363	m	ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
295	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	3,627 m		ground	Max. 15 °C
296	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	343,430 m		ground	Max. 15 °C
297	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		dark oxidized	Max. 15 °C
298	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,000 m		ground	Max. 15 °C
299	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,390 m		ground	Max. 15 °C
300	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	4,958 m		ground	Max. 15 °C
301	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	6,000 m		ground	Max. 15 °C
302	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,700 m		ground	Max. 15 °C
303	NiTi	1,630	0,240	1,150	0,0642	0,0094	0,0453	7,980 m		ground	Max. 15 °C
304	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,080 m		ground out-/oxidic inside	Max. 15 °C
305	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,120 m		ground out-/oxidic inside	Max. 15 °C
306	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,450 m		ground out-/oxidic inside	Max. 15 °C
307	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	2,930 m		ground out-/oxidic inside	Max. 15 °C
308	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	26,850 m		ground	Max. 15 °C
309	NiTi	1,630	0,255	1,120	0,0642	0,0100	0,0441	3,560 m		ground out-/oxidic inside	Max. 15 °C
310	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,150 m		ground	Max. 15 °C
311	NiTi	1,631	0,228	1,175	0,0642	0,0090	0,0463	41,685 m		ground	Max. 15 °C
312	NiTi	1,700	0,125	1,450	0,0669	0,0049	0,0571	111,000 St		ground	Max. 15 °C
313	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	204,474 m		ground out-/oxidic inside	Max. 15 °C
314	NiTi	1,700	0,200	1,300	0,0669	0,0079	0,0512	287,701 m		ground out-/oxidic inside	Max. 15 °C
315	NiTi	1,720	0,230	1,260	0,0677	0,0091	0,0496	67,744 m		ground	Max. 15 °C

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
316	NiTi	1,729	0,220	1,289	0,0681	0,0087	0,0507	36,100 m		ground	Max. 15 °C
317	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	172,007 m		ground	Max. 15 °C
318	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	26,729 m		ground	Max. 15 °C
319	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	3,500 m		ground	Max. 15 °C
320	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	35,060 m		ground	Max. 15 °C
321	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	4,323 m		ground	Max. 15 °C
322	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	40,357 m		ground	Max. 15 °C
323	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	43,041 m		ground	Max. 15 °C
324	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	5,740 m		ground	Max. 15 °C
325	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	6,450 m		ground	Max. 15 °C
326	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	7,900 m		ground	Max. 15 °C
327	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	8,160 m		ground	Max. 15 °C
328	NiTi	1,729	0,240	1,249	0,0681	0,0094	0,0492	81,630 m		ground	Max. 15 °C
329	NiTi	1,730	0,240	1,250	0,0681	0,0094	0,0492	28,250 m		ground	Max. 15 °C
330	NiTi	1,778	0,406	0,966	0,0700	0,0160	0,0380	22,252 m		ground	Max. 15 °C
331	NiTi	1,800	0,060	1,680	0,0709	0,0024	0,0661	5,260 m		ground	Max. 15 °C
332	NiTi	1,800	0,070	1,660	0,0709	0,0028	0,0654	17,365 m		ground	Max. 15 °C
333	NiTi	1,800	0,075	1,650	0,0709	0,0030	0,0650	21,481 m		ground	Max. 15 °C
334	NiTi	1,800	0,080	1,640	0,0709	0,0031	0,0646	6,594 m		ground	Max. 15 °C
335	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	10,338 m		ground	Max. 15 °C
336	NiTi	1,800	0,090	1,620	0,0709	0,0035	0,0638	2,202 m		ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
337	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	10,263	m	ground	Max. 15 °C
338	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	14,726	m	ground	Max. 15 °C
339	NiTi	1,801	0,089	1,623	0,0709	0,0035	0,0639	21,683	m	ground	Max. 15 °C
340	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	3,356	m	ground	Max. 15 °C
341	NiTi	1,820	0,255	1,310	0,0717	0,0100	0,0516	4,716	m	ground	Max. 15 °C
342	NiTi	1,820	0,270	1,280	0,0717	0,0106	0,0504	9,070	m	ground	Max. 15 °C
343	NiTi	1,900	0,370	1,160	0,0748	0,0146	0,0457	3,832	m	ground	Max. 15 °C
344	NiTi	1,907	0,203	1,501	0,0751	0,0080	0,0591	11,009	m	ground	Max. 15 °C
345	NiTi	1,921	0,203	1,515	0,0756	0,0080	0,0596	96,643	m	ground	Max. 15 °C
346	NiTi	2,000	0,070	1,860	0,0787	0,0028	0,0732	8,969	m	ground	Max. 15 °C
347	NiTi	2,000	0,230	1,540	0,0787	0,0091	0,0606	5,990	m	ground	Max. 15 °C
348	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	27,510	m	ground	Max. 15 °C
349	NiTi	2,000	0,240	1,520	0,0787	0,0094	0,0598	36,467	m	ground	Max. 15 °C
350	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	21,199	m	ground	Max. 15 °C
351	NiTi	2,000	0,250	1,500	0,0787	0,0098	0,0591	36,134	m	ground	Max. 15 °C
352	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	1,383	m	ground	Max. 15 °C
353	NiTi	2,030	0,250	1,530	0,0799	0,0098	0,0602	9,847	m	ground	Max. 15 °C
354	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	333,511	m	ground	Max. 15 °C
355	NiTi	2,032	0,280	1,472	0,0800	0,0110	0,0580	79,725	m	ground	Max. 15 °C
356	NiTi	2,130	0,075	1,980	0,0839	0,0030	0,0780	1,089	m	ground	Max. 15 °C
357	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	14,305	m	ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
358	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	23,347 m		ground	Max. 15 °C
359	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	32,850 m		ground	Max. 15 °C
360	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	6,506 m		ground	Max. 15 °C
361	NiTi	2,159	0,076	2,007	0,0850	0,0030	0,0790	7,169 m		ground	Max. 15 °C
362	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	130,730 m		ground	Max. 15 °C
363	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	25,753 m		ground	Max. 15 °C
364	NiTi	2,159	0,254	1,651	0,0850	0,0100	0,0650	3,772 m		ground	Max. 15 °C
365	NiTi	2,161	0,086	1,989	0,0851	0,0034	0,0783	341,218 m		ground	Max. 15 °C
366	NiTi	2,164	0,081	2,002	0,0852	0,0032	0,0788	14,486 m		ground	Max. 15 °C
367	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	1,840 m		ground	Max. 15 °C
368	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	13,550 m		ground	Max. 15 °C
369	NiTi	2,184	0,212	1,760	0,0860	0,0083	0,0693	9,847 m		ground	Max. 15 °C
370	NiTi	2,184	0,241	1,702	0,0860	0,0095	0,0670	8,283 m		ground	Max. 15 °C
371	NiTi	2,184	0,381	1,422	0,0860	0,0150	0,0560	6,294 m		ground	Max. 15 °C
372	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	28,627 m		ground out-/oxidic inside	Max. 15 °C
373	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	57,200 m		ground out-/oxidic inside	Max. 15 °C
374	NiTi	2,190	0,079	2,032	0,0862	0,0031	0,0800	9,659 m		ground out-/oxidic inside	Max. 15 °C
375	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	25,542 m		ground	Max. 15 °C
376	NiTi	2,200	0,240	1,720	0,0866	0,0094	0,0677	8,472 m		ground	Max. 15 °C
377	NiTi	2,200	0,270	1,660	0,0866	0,0106	0,0654	42,972 m		ground	Max. 15 °C
378	NiTi	2,200	0,325	1,550	0,0866	0,0128	0,0610	2,040 m		ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
379	NiTi	2,200	0,550	1,100	0,0866	0,0217	0,0433	1,880 m		ground	Max. 15 °C
380	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	6,936 m		ground	Max. 15 °C
381	NiTi	2,286	0,216	1,854	0,0900	0,0085	0,0730	74,575 m		ground	Max. 15 °C
382	NiTi	2,286	0,254	1,778	0,0900	0,0100	0,0700	2,821 m		ground	Max. 15 °C
383	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	1,414 m		ground	Max. 15 °C
384	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	2,624 m		ground	Max. 15 °C
385	NiTi	2,300	0,250	1,800	0,0906	0,0098	0,0709	4,584 m		ground	Max. 15 °C
386	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	107,669 m		ground out-/oxidic inside	Max. 15 °C
387	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	19,268 m		ground out-/oxidic inside	Max. 15 °C
388	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	27,620 m		ground out-/oxidic inside	Max. 15 °C
389	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	33,102 m		ground out-/oxidic inside	Max. 15 °C
390	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	42,991 m		ground out-/oxidic inside	Max. 15 °C
391	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	60,800 m		ground out-/oxidic inside	Max. 15 °C
392	NiTi	2,300	0,500	1,300	0,0906	0,0197	0,0512	7,000 m		ground out-/oxidic inside	Max. 15 °C
393	NiTi	2,310	0,255	1,800	0,0909	0,0100	0,0709	28,010 m		ground	Max. 15 °C
394	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	29,031 m		ground	Max. 15 °C
395	NiTi	2,340	0,170	2,000	0,0921	0,0067	0,0787	40,566 m		ground	Max. 15 °C
396	NiTi	2,350	0,145	2,060	0,0925	0,0057	0,0811	8,866 m		ground	Max. 15 °C
397	NiTi	2,372	0,183	2,006	0,0934	0,0072	0,0790	8,280 m		ground	Max. 15 °C
398	NiTi	2,400	0,075	2,250	0,0945	0,0030	0,0886	5,203 m		ground	Max. 15 °C
399	NiTi	2,400	0,076	2,248	0,0945	0,0030	0,0885	13,315 m		ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
400	NiTi	2,400	0,085	2,230	0,0945	0,0033	0,0878	1,654	m	ground	Max. 15 °C
401	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	34,413	m	dark oxidized	Max. 15 °C
402	NiTi	2,400	0,200	2,000	0,0945	0,0079	0,0787	8,635	m	ground	Max. 15 °C
403	NiTi	2,400	0,300	1,800	0,0945	0,0118	0,0709	8,126	m	ground	Max. 15 °C
404	NiTi	2,400	0,500	1,400	0,0945	0,0197	0,0551	11,313	m	ground	Max. 15 °C
405	NiTi	2,403	0,198	2,007	0,0946	0,0078	0,0790	4,644	m	ground	Max. 15 °C
406	NiTi	2,413	0,407	1,600	0,0950	0,0160	0,0630	20,940	m	ground	Max. 15 °C
407	NiTi	2,440	0,320	1,800	0,0961	0,0126	0,0709	1,760	m	dark oxidized	Max. 15 °C
408	NiTi	2,449	0,221	2,007	0,0964	0,0087	0,0790	2,881	m	ground	Max. 15 °C
409	NiTi	2,464	0,089	2,286	0,0970	0,0035	0,0900	2,629	m	ground	Max. 15 °C
410	NiTi	2,500	0,070	2,360	0,0984	0,0028	0,0929	3,920	m	ground	Max. 15 °C
411	NiTi	2,500	0,080	2,340	0,0984	0,0031	0,0921	3,708	m	ground	Max. 15 °C
412	NiTi	2,500	0,190	2,120	0,0984	0,0075	0,0835	25,725	m	ground	Max. 15 °C
413	NiTi	2,500	0,550	1,400	0,0984	0,0217	0,0551	6,995	m		Max. 15 °C
414	NiTi	2,550	0,180	2,190	0,1004	0,0071	0,0862	9,673	m	ground	Max. 15 °C
415	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	13,249	m	ground	Max. 15 °C
416	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	2,999	m	ground out-/oxidic inside	Max. 15 °C
417	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	6,577	m	ground	Max. 15 °C
418	NiTi	2,565	0,381	1,803	0,1010	0,0150	0,0710	76,526	m	ground	Max. 15 °C
419	NiTi	2,590	0,076	2,438	0,1020	0,0030	0,0960	2,188	m	ground	Max. 15 °C
420	NiTi	2,600	0,200	2,200	0,1024	0,0079	0,0866	17,406	m	ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
421	NiTi	2,600	0,510	1,580	0,1024	0,0201	0,0622	112,705	m	ground	Max. 15 °C
422	NiTi	2,618	0,065	2,488	0,1031	0,0026	0,0980	73,023	m	ground	Max. 15 °C
423	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	41,055	m	ground	Max. 15 °C
424	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	56,811	m	ground	Max. 15 °C
425	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	59,796	m	ground	Max. 15 °C
426	NiTi	2,637	0,074	2,489	0,1038	0,0029	0,0980	9,617	m	ground	Max. 15 °C
427	NiTi	2,680	0,089	2,502	0,1055	0,0035	0,0985	4,405	m	ground	Max. 15 °C
428	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	6,022	m	ground	Max. 15 °C
429	NiTi	2,692	0,406	1,880	0,1060	0,0160	0,0740	9,177	m	ground	Max. 15 °C
430	NiTi	2,700	0,600	1,500	0,1063	0,0236	0,0591	1,143	m	ground	Max. 15 °C
431	NiTi	2,743	0,432	1,879	0,1080	0,0170	0,0740	10,281	m	ground	Max. 15 °C
432	NiTi	2,760	0,190	2,380	0,1087	0,0075	0,0937	4,993	m	ground	Max. 15 °C
433	NiTi	2,800	0,230	2,340	0,1102	0,0091	0,0921	4,246	m	ground	Max. 15 °C
434	NiTi	2,800	0,300	2,200	0,1102	0,0118	0,0866	2,971	m	ground	Max. 15 °C
435	NiTi	2,800	0,610	1,580	0,1102	0,0240	0,0622	18,142	m	ground	Max. 15 °C
436	NiTi	2,819	0,371	2,077	0,1110	0,0146	0,0818	7,000	St	ground	Max. 15 °C
437	NiTi	2,870	0,173	2,524	0,1130	0,0068	0,0994	13,868	m	ground	Max. 15 °C
438	NiTi	3,000	0,080	2,840	0,1181	0,0031	0,1118	5,982	m	ground	Max. 15 °C
439	NiTi	3,000	0,150	2,700	0,1181	0,0059	0,1063	35,351	m	ground	Max. 15 °C
440	NiTi	3,000	0,250	2,500	0,1181	0,0098	0,0984	4,131	m	ground	Max. 15 °C
441	NiTi	3,000	0,260	2,480	0,1181	0,0102	0,0976	5,204	m	ground	Max. 15 °C

Stock list - Tubescurrent status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
442	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,471 m		ground out-/oxidic inside	Max. 15 °C
443	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	1,863 m		ground out-/oxidic inside	Max. 15 °C
444	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	10,931 m		ground out-/oxidic inside	Max. 15 °C
445	NiTi	3,350	0,165	3,020	0,1319	0,0065	0,1189	5,955 m		ground	Max. 15 °C
446	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	5,996 m		ground	Max. 15 °C
447	NiTi	3,363	0,102	3,159	0,1324	0,0040	0,1244	50,776 m		ground	Max. 15 °C
448	NiTi	3,363	0,111	3,141	0,1324	0,0044	0,1237	81,471 m		ground	Max. 15 °C
449	NiTi	3,404	0,458	2,489	0,1340	0,0180	0,0980	8,009 m		ground	Max. 15 °C
450	NiTi	3,500	0,075	3,350	0,1378	0,0030	0,1319	15,571 m		ground	Max. 15 °C
451	NiTi	3,500	0,127	3,246	0,1378	0,0050	0,1278	9,754 m		ground	Max. 15 °C
452	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	22,275 m		ground	Max. 15 °C
453	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	8,819 m		ground	Max. 15 °C
454	NiTi	3,500	0,165	3,170	0,1378	0,0065	0,1248	9,610 m		ground	Max. 15 °C
455	NiTi	3,500	0,203	3,094	0,1378	0,0080	0,1218	4,241 m		ground	Max. 15 °C
456	NiTi	3,500	0,440	2,620	0,1378	0,0173	0,1031	4,291 m		ground	Max. 15 °C
457	NiTi	3,520	0,160	3,200	0,1386	0,0063	0,1260	1,152 m		ground	Max. 15 °C
458	NiTi	3,600	0,200	3,200	0,1417	0,0079	0,1260	7,231 m		ground	Max. 15 °C
459	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	4,000 m		ground	Max. 15 °C
460	NiTi	4,000	0,080	3,840	0,1575	0,0031	0,1512	65,915 m		ground	Max. 15 °C
461	NiTi	4,210	0,500	3,210	0,1657	0,0197	0,1264	3,628 m		ground	Max. 15 °C
462	NiTi	4,250	0,065	4,120	0,1673	0,0026	0,1622	4,333 m		polished	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east US Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
463	NiTi	4,500	0,060	4,380	0,1772	0,0024	0,1724	1,836 m		ground	Max. 15 °C
464	NiTi	4,765	0,130	4,505	0,1876	0,0051	0,1774	1,597 m		ground	Max. 15 °C
465	NiTi	4,800	0,075	4,650	0,1890	0,0030	0,1831	2,905 m		ground	Max. 15 °C
466	NiTi	4,800	0,170	4,460	0,1890	0,0067	0,1756	2,707 m		ground	Max. 15 °C
467	NiTi	4,950	0,155	4,640	0,1949	0,0061	0,1827	3,745 m		polished	Max. 15 °C
468	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	0,227 m		ground	Max. 15 °C
469	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	2,306 m		ground	Max. 15 °C
470	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	29,886 m		ground out-/oxidic inside	Max. 15 °C
471	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	3,398 m		ground out-/oxidic inside	Max. 15 °C
472	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,757 m		ground	Max. 15 °C
473	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	4,835 m		ground out-/oxidic inside	Max. 15 °C
474	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	5,534 m		ground	Max. 15 °C
475	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	54,498 m		ground out-/oxidic inside	Max. 15 °C
476	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	6,244 m		ground	Max. 15 °C
477	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	7,574 m		ground	Max. 15 °C
478	NiTi	4,950	0,625	3,700	0,1949	0,0246	0,1457	93,614 m		ground out-/oxidic inside	Max. 15 °C
479	NiTi	4,980	0,280	4,420	0,1961	0,0110	0,1740	3,032 m		ground	Max. 15 °C
480	NiTi	5,000	0,250	4,500	0,1969	0,0098	0,1772	5,870 m		ground	Max. 15 °C
481	NiTi	5,000	0,400	4,200	0,1969	0,0157	0,1654	26,235 m		ground	Max. 15 °C
482	NiTi	5,004	0,533	3,938	0,1970	0,0210	0,1550	2,263 m		ground out-/oxidic inside	Max. 15 °C
483	NiTi	5,030	0,175	4,680	0,1980	0,0069	0,1843	6,880 m		polished	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
484	NiTi	5,055	0,203	4,649	0,1990	0,0080	0,1830	0,434	m	ground	Max. 15 °C
485	NiTi	5,200	0,200	4,800	0,2047	0,0079	0,1890	20,330	m	ground	Max. 15 °C
486	NiTi	5,207	0,279	4,649	0,2050	0,0110	0,1830	1,400	m	ground	Max. 15 °C
487	NiTi	5,588	0,229	5,130	0,2200	0,0090	0,2020	3,553	m	ground	Max. 15 °C
488	NiTi	5,944	0,572	4,800	0,2340	0,0225	0,1890	1,250	m	ground out-/oxidic inside	Max. 15 °C
489	NiTi	5,990	0,546	4,898	0,2358	0,0215	0,1928	4,110	m	ground out-/oxidic inside	Max. 15 °C
490	NiTi	5,990	0,584	4,822	0,2358	0,0230	0,1898	8,865	m	ground out-/oxidic inside	Max. 15 °C
491	NiTi	5,994	0,537	4,920	0,2360	0,0211	0,1937	16,439	m	ground	Max. 15 °C
492	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	21,525	m	ground	Max. 15 °C
493	NiTi	5,994	0,559	4,876	0,2360	0,0220	0,1920	7,512	m	ground	Max. 15 °C
494	NiTi	6,500	0,220	6,060	0,2559	0,0087	0,2386	0,986	m	ground	Max. 15 °C
495	NiTi	6,700	0,250	6,200	0,2638	0,0098	0,2441	2,135	m	ground	Max. 15 °C
496	NiTi	7,000	0,100	6,800	0,2756	0,0039	0,2677	18,502	m	ground	Max. 15 °C
497	NiTi	7,500	2,025	3,450	0,2953	0,0797	0,1358	5,177	m	ground	Max. 15 °C
498	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,130	m	ground	Max. 15 °C
499	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	6,570	m	ground	Max. 15 °C
500	NiTi	8,000	0,330	7,340	0,3150	0,0130	0,2890	9,837	m	ground	Max. 15 °C
501	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	4,550	m	ground	Max. 15 °C
502	NiTi	8,000	0,381	7,238	0,3150	0,0150	0,2850	8,316	m	ground	Max. 15 °C
503	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	0,645	m	ground	Max. 15 °C
504	NiTi	8,000	0,750	6,500	0,3150	0,0295	0,2559	7,223	m	ground	Max. 15 °C

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
505	NiTi	8,500	0,220	8,060	0,3346	0,0087	0,3173	3,458 m		ground	Max. 15 °C
506	NiTi	9,900	0,625	8,650	0,3898	0,0246	0,3406	1,110 m		ground	Max. 15 °C
507	NiTi	10,000	0,310	9,380	0,3937	0,0122	0,3693	13,438 m		ground	Max. 15 °C
508	NiTi	10,000	0,406	9,188	0,3937	0,0160	0,3617	7,497 m		ground	Max. 15 °C
509	NiTi	10,000	0,450	9,100	0,3937	0,0177	0,3583	1,410 m		ground	Max. 15 °C
510	NiTi	10,000	0,480	9,040	0,3937	0,0189	0,3559	3,585 m		ground	Max. 15 °C
511	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	1,193 m		ground	Max. 15 °C
512	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	1,269 m		ground	Max. 15 °C
513	NiTi	10,000	0,500	9,000	0,3937	0,0197	0,3543	2,374 m		ground	Max. 15 °C
514	NiTi	10,000	0,550	8,900	0,3937	0,0217	0,3504	4,688 m		ground	Max. 15 °C
515	NiTi	10,000	0,720	8,560	0,3937	0,0283	0,3370	0,874 m		ground	Max. 15 °C
516	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	1,050 m		ground	Max. 15 °C
517	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	13,864 m		ground	Max. 15 °C
518	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	2,854 m		ground	Max. 15 °C
519	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	6,601 m		ground	Max. 15 °C
520	NiTi	10,000	0,787	8,426	0,3937	0,0310	0,3317	8,806 m		ground	Max. 15 °C
521	Phynox / 2.4711	1,600	0,250	1,100	0,0630	0,0098	0,0433	11,034 m			
522	Tantal	1,600	0,090	1,420	0,0630	0,0035	0,0559	2,207 m			
523	Tantal	1,982	0,051	1,880	0,0780	0,0020	0,0740	3,897 m			
524	Tantal	4,800	0,400	4,000	0,1890	0,0157	0,1575	4,647 m			
525	Tantal	4,900	0,500	3,900	0,1929	0,0197	0,1535	2,529 m			

Stock list - Tubes

current status: **24.09.2021**

To receive a quote, please contact
The minimum order value is € 400.

Nicole Odenwald (Phone +49(0)7231.208.426, nicole.odenwald@euroflex.de)
or Michaela Müller (Phone +49(0)7231.208.249, michaela.mueller@euroflex.de)
or Valerie Stumpf (Phone +49(0)7231.208.560, valerie.stumpf@euroflex.de)

midwest/east U Alec Niedermaier (Phone +1 952-649-2853, alec.niedermaier@euroflex.de)
west USA or Keyur Amin (Phone +1 714-317-0971, keyur.amin@euroflex.de)

Pos	Material	OD (mm)	WT (mm)	ID (mm)	OD (inch)	WT (inch)	ID (inch)	Available	Me	Surface	AF
526	Tantal-Wolfram	1,880	0,077	1,727	0,0740	0,0030	0,0680	18,162	m		
527	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	11,210	m	ground	
528	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	26,480	m	ground	
529	Titan Gr. 2	0,790	0,270	0,250	0,0311	0,0106	0,0098	28,310	m		
530	Titan Gr. 2	0,820	0,156	0,508	0,0323	0,0061	0,0200	74,736	m		
531	Titan Gr. 2	1,100	0,150	0,800	0,0433	0,0059	0,0315	664,655	m		
532	Titan Gr. 2	1,225	0,050	1,125	0,0482	0,0020	0,0443	45,777	m		
533	Titan Gr. 2	1,250	0,100	1,050	0,0492	0,0039	0,0413	62,150	m	ground	
534	Titan Gr. 2	2,134	0,102	1,930	0,0840	0,0040	0,0760	6,027	m		
535	Titan Gr. 2	2,540	0,102	2,337	0,1000	0,0040	0,0920	6,490	m		
536	Titan Gr. 2	4,000	0,050	3,900	0,1575	0,0020	0,1535	22,670	m		
537	Titan Gr. 2	4,480	0,075	4,330	0,1764	0,0030	0,1705	24,120	m		
538	Titan Gr. 2	6,883	0,356	6,172	0,2710	0,0140	0,2430	3,990	m		
539	Titan Gr. 2	7,000	0,150	6,700	0,2756	0,0059	0,2638	6,050	m		
540	Titan Gr. 2	7,925	0,889	6,147	0,3120	0,0350	0,2420	5,980	m		